

L7 Drive

Designing your future with
LS Mecapion L7 Series.

Your reasonable selection for total solution

The wide range of LS Mecapion line up will satisfy your requirements for the motion system through optimal application and use of the products.

With the excellent functionality, high precision and high-speed control, LS Mecapion AC servo system is customer-friendly and cost-effective.



Moving towards tomorrow

The Best Automation **Brand** in Korea
The World Class Leader in Automation System

LS Mecapion has supplied not only the servo drives and servo motors of high quality and high efficiency but also rotary encoders and actuators for the Korean and Global Industries for the past 20 years.

We are making efforts to provide a variety of products to our customers all over the world to satisfy their requirements. We have provided cutting-edge technologies that consider the needs of our customers by adopting the best functionality as well as innovative ideas.

We have accumulated a deep and wide range of experiences in the field of the control system for years and are venturing into new possibilities to provide the technologies of a higher level to our customers.

We hope that you don't miss the opportunity to use the proven, **world-class products** from **LS Mecapion** to improve the performance and value of your equipment.

We hope that we can provide the best services and partnerships for our customers by utilizing our expertise and technologies.



L7 SERIES SYSTEM

Features of L7 Drive

Compact Size

Capacity	400W			1kW			3.5kw		
Series	L7	VS	Competitor	L7	VS	Competitor	L7	VS	Competitor
L [mm]	38	80	40	58	88	60	88	137	90
W [mm]	169	187	168	169	210	168	169	256	168
H [mm]	173	132	170	198	195	195	198	225	195

Compared with VS

Slim up to
52%
More

Compared with a representative competitor

Slim up to
5%
More

Ultra-thin 38 mm width (400 W)

Its small footprint allows flexible installation, reducing the size of the equipment.

400W



1kW




3.5kW



Easy to USE

The automatic inertia detection function for easier gain adjustment.

- Fast and accurate inertia detection
- Off-line tuning
- Parameters for inertia detection (speed and distance) provided



Encoder based on two-way high-speed serial communication

- Automatic recognition for motors and encoders
- BiSS protocol
- Wire-saving system (7-line) for encoder, resistant to noise

BiSS
INTERFACE

Support for various motors and encoders [L7NH and L7P Series]

- Support for standard BiSS encoders as well as other encoders

Motor	Encoder
Rotary	Quadrature / BiSS Interface
DD	Tamagawa serial absolute
Linear	EnDat 2.2 / Resolver


Features of L7 Drive

● Sufficient input/output contacts and various functions

- L7S: Digital input contacts: 10, output contacts: 8 / Analog input contacts: 2 and output contacts: 2
- L7N: Digital input contacts: 6, output contacts: 4 / Analog input contacts: 2 and output contacts: 2
- L7NH: Digital input contacts: 8, output contacts: 4 / Analog input contacts: 1 and output contacts: 2
- L7P: Digital input contacts: 16, output contacts: 8 / Analog input contacts: 2 and output contacts: 2
- PEGASUS: Digital input contacts: 4, output contacts: 2 / Analog input contacts: 1 and output contacts: 1
- Flexible assignment of input/output signals by parameters and contact setting based on the input/output contact type (N.O / N.C contacts)


● Using the rotary switch to configure the drive node address [L7NH, L7P, and PEGASUS]

- Using the rotary switch to configure the drive node address conveniently
- L7NH: 0–99, L7P: 0–31, PEGASUS: 0–15



● Various homing functions [L7NH, L7P, and PEGASUS]

- The drive provides the homing function.
- You can specify the speed, acceleration, offset, and homing method.




● Easy firmware upgrade [L7NH, L7P, and PEGASUS]

- Supporting the USB OTG function to allow firmware download with a USB memory
- Useful where space is limited or environmentally unfavorable



● Built-in regenerative braking resistance in the drive

- Drive installed inside to improve user convenience (100 W – 3.5 kW)
- Providing the connection for external installation
- Enhanced protection algorithm



● Plug-in type power connector

- Expanded to 100 W – 3.5 kW for improved wiring convenience



L7 SERIES SYSTEM

Features of L7 Drive

■ Reliability


- Main capacitor quality improved
 - Long-life type capacitor applied (2.5 times improvement)

- Convenient DC reactor installable
 - Power connection to DC-link
 - Easier wiring and smaller size compared to 3-phase AC reactor
 - Connection for DC input (PI, N)

- Stable turn-off function based on the detection of the control power turn-off

- CE certification and RoHS certification

- Enhanced protection function
 - Triple protection function for the protection of power module
 - Detection of the main power phase loss
 - Temperature sensor installed in the drive and motor for the prevention of overheat
 - Alarm code grouping and dedicated output contacts (ALO0, ALO1, ALO2)
 - Warning function (Digital output WARN)



■ High Performance

- Serial encoder of high resolution (with Biss C)

- Stability improved during precision position control and low-speed operation

- Stable low-speed properties based on precise speed measurement

- Stable speed measurement at low speed

- Calculation speed improved [L7NH, L7P, and PEGASUS]

- FPU (Floating Point Unit) for reliable precision calculation
 - 16 kHz switching frequency for precision current control
 - 32 bit operation for increased synchronous command processing rate (MIPS)


- Dedicated PC program

- L7S, and L7N: LIVE-I.C.E / L7NH, L7P, and PEGASUS: Drive CM
 - PC program for shortened equipment tuning time and debugging
 - Monitoring for speed, torque, current feedback, position values and positional error values and alarm occurrence time


Features of L7 Drive

■ Intelligent Control

- Notch filter for resonance suppression
 - 4-step notch filter
 - 2-step vibration suppression filter at the load position
 - FFT function for real-time frequency analysis




- Various gain switching modes for improved control performance
 - P/PI auto-switching function to reduce overshooting during acceleration/deceleration
 - Various Gain1 \leftrightarrow Gain2 switching modes
- Various dynamic brake control modes
 - Configuring the operation mode at stop and after stop



■ Network Based – EtherCAT Network Type

- A wide range of products
 - L7N: EtherCAT communication command type
 - L7NH: All-in-one EtherCAT communication command type
 - PEGASUS: Motor drive-integrated EtherCAT communication command type
- High performance
 - Synchronization mechanism of high speed, high accuracy, and real-time communication
 - Various Gain1 \leftrightarrow Gain2 switching modes
- Open network
 - An international standard network with 1,600 members over the world
- Low cost
 - Standard Ethernet connector and cabling supported and slave–master implemented at a low cost
- Easy to use
 - Various topology types supported and easy diagnosis for devices
- L7 drive with a built-in EtherCAT interface
 - 100BASE-TX (100 Mbps) real-time communication
 - CiA402 (IEC61800-7) drive profile supported
 - Connection with various masters and slaves
 - Up to 100 m connection between nodes
 - Precision synchronization mechanism of 1 us or less

Field Bus



L7 SERIES SYSTEM

Features of L7 Drive

● Various operation modes

- L7N: Using the EtherCAT communication to support Cyclic (P/S/T) and Profile (P/S/T) modes
- L7NH and PEGASUS: Using the EtherCAT communication to support Cyclic & Profile (P/S/T) modes, EOE, COE, and FOE

● Safe torque off function

- Torque-off forced by hardware signals without involvement of the drive CPU and FPGA (ASIC); international standards adopted (IEC61508))

● Flexible I/O setup

- Mapping and level (A/B) setup by parameters

● High-speed position capture


- Touch probe function (PROBE1 and PROBE2)

● Adjustment function linked with XGT series from LSIS

- Inertia detection, position/speed gain manual adjustment, gain switching setup, etc.

● EtherCAT drive compatibility

- Verified by CTT (Conformance Test Tool)






Servo Setup Software

Live-I.C.E : L7S and L7N Series


● Monitoring function

- Monitoring for I/O input contact and I/O output contact
- Driving Information monitoring: Monitoring and displaying the parameter values
- Communication connection monitoring : Displaying the current communication connection status using animation in real time



● Setup function

- Using the PC to read and write parameters
- Manual JOG function: Manual jog speed adjustment and forward/reverse test
- Automatic gain tuning
- Alarm history and alarm reset



● Graph function

- Data Trace: Graphic presentation of pre-defined channels in real time
- Trigger Monitoring: Graphic presentation by the channel and trigger settings
- Alarm Trace: Graphic presentation of alarm history for channels



● Download software

- OS Download: Firmware version upgrade software


L7 SERIES SYSTEM

Servo Setup Software

Drive CM : L7NH, L7P and PEGASUS Series


I/O CONFIGURATION

- Setting the output function and its signal level for I/O input contacts and I/O output signal pins
- Limiting the analog input torque and using the analogue voltage to override the speed
- Analog monitoring output for the gain tuning or internal state variables of the drive




Monitoring function

- Implementation of 4-channel tracer or trigger monitor
- Performing various operations, including Manual Jog, Program Jog, PTP Move, etc., and monitoring the operation state
- Monitoring Zoom or Pan / Mouse Wheel / Rollover or Cursor



Setup function

- Configuring the data structure including parameters, state variables, commands, etc, inside the drive
- Using Manual Jog and Program Jog to carry out the test
- Using Offline Auto Tuning for one-touch adjustment
- Customer convenience functions such as PTP movement, homing, and touch probe



Indexer setup [L7P only]

- Using Index Edit to enter/configure the index parameters
- Using Indexer Test to configure the operation and provide testing function

INDEX

Servo Drive

L7S Series _13

L7N Series _25

L7NH Series _31

L7P Series _45



Servo Motor



S Series _60

F Series _72

MDM Series _87

Options

Servo motor cable _97

Servo drive cable _111

Other options _112

Integrated Servo System

PEGASUS Series _115

L7 SERIES SYSTEM

Contents

Servo Drive

L7S Series

General Pulse Type, Analog Command Type

- Servo Drive Designation _ 13
- Product Feature _ 18
- External Dimensions _ 20



L7N Series

EtherCAT Communication Command Type

- Servo Drive Designation _ 25
- Product Feature _ 28
- External Dimensions _ 29



L7NH Series

All-in-one EtherCAT Communication Command Type

- Servo Drive Designation _ 31
- Product Feature _ 37
- External Dimensions _ 39



L7P Series

Indexer Function Type

- Servo Drive Designation _ 45
- Product Feature _ 51
- External Dimensions _ 53



General Pulse Type, Analog Command Type

I L7S Series



■ Servo Drive Designation

L7	S	A	004	B	AA
Model Name	Communication	Input Power Supply	Capacity	Encoder Type	Option
Servo Series	S : Standard I/O Type	A : 200VAC B : 400VAC	001 : 100W 002 : 200W 004 : 400W 008 : 750W 010 : 1.0kW 020 : 2.0kW 035 : 3.5kW 050 : 5.0kW 075 : 7.5kW 150 : 15.0kW	A : Quadrature (Pulse Type) B : Serial (Communication Type)	Exclusive Option Code

* Range

- 200V : 0.1kW~5.0kW
- 400V : 1.0kW~15kW

L7 SERIES SYSTEM

L7S Series

Characteristic

● Easy to USE

- Easy Gain Tuning with Automatic Inertia Estimating Function
- Easy Setting Built-in Panel Operator
- Many I/O Contacts and Various Functions
(Digital Input: 10 contacts, Digital Output: 8 contacts / Analog input, output : 2 contacts)]


● Reliability for Protection Function

- CE, RoHS Certificated
- Drive Protection Function and Warning Function

● High Response for Precision Control

- High Resolutions Serial type Encoder(19Bit, BiSS)
- Improved Speed Response($\approx 1\text{Khz}$) Frequency

Identifying the Part of L7S



- ① Operation keys (Mode, Up, Down, Set)
- ② Charge Lamp
- ③ Main Power Connector (L1, L2, L3)
- ④ DC Reactor Connector(PO, PI)
 - Short-Circuit when not used
- ⑤ Regenerative resistance connector (B+, B, BI)
 - Short-Circuit B, BI terminals when standard type
 - Use B+, B terminals when using external resistor
- ⑥ Control Power Connector (C1, C2)
- ⑦ Front Cover
- ⑧ Motor Power Cable Connector (U, V, W)
- ⑨ Heat Sink
- ⑩ Display
- ⑪ CN5 : USB Connector
- ⑫ CN4 : RS-422 Communication Connector
- ⑬ CN3 : RS-422 Communication Connector
- ⑭ CN1 : Control Signal Connector
- ⑮ CN2 : Encoder Signal Connector
- ⑯ Ground

L7S Drive Combination Table

■ L7SA Incremental Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder Cable	Power Cable		
					Quadrature Type	INC	For power	Power + Brake	Brake
3,000	5,000	□40	SAR3A	L7SA001A	* 2,048 P/R	APCS-E□□□AS	APCS-P□□□GS	APCS-P□□□KB	APCS-P□□□KB
		□40	SAR5A	L7SA001A					
		□40	SA01A	L7SA001A					
		□40	SA015A	L7SA002A					
		□60	SB01A	L7SA002A	APCS-E□□□BS	APCS-P□□□HS	APCS-P□□□NB	APCS-P□□□NB	APCS-P□□□NB
		□60	SB02A	L7SA002A					
		□60	SB04A	L7SA004A					
		□80	SC04A	L7SA004A					
		□80	SC06A	L7SA008A		APCS-P□□□JS	APCS-P□□□PB	APCS-P□□□PB	APCS-P□□□PB
		□80	SC08A	L7SA008A					
		□80	SC10A	L7SA010A					
		□130	SE09A	L7SA008A	APCS-E□□□AS	APCS-P□□□GS	APCS-P□□□KB	APCS-P□□□KB	APCS-P□□□KB
		□130	SE15A	L7SA020A					
		□130	SE22A	L7SA020A					
		□130	SE30A	L7SA035A					
		□180	SF30A	L7SA035A					
		□180	SF50A	L7SA050A					
2,000	3,000	□80	SC03D	L7SA004A	* 3,000 P/R	APCS-P□□□HS	APCS-P□□□NB	APCS-P□□□NB	APCS-P□□□NB
		□80	SC05D	L7SA008A					
		□80	SC06D	L7SA008A					
		□80	SC07D	L7SA008A					
		□130	SE06D	L7SA008A					
		□130	SE11D	L7SA010A					
		□130	SE16D	L7SA020A					
		□130	SE22D	L7SA020A					
		□180	SF22D	L7SA020A	APCS-E□□□BS	APCS-P□□□IS	APCS-P□□□PB	APCS-P□□□PB	APCS-P□□□PB
		□180	LF35D	L7SA035A					
		□180	SF55D	L7SA050A					
		□220	SG22D	L7SA020A					
		□220	LG35D	L7SA035A					
		□220	SG55D	L7SA050A					
		□130	SE05G	L7SA008A					
		□130	SE09G	L7SA010A					
1,500	3,000	□130	SE13G	L7SA020A	APCS-E□□□AS	APCS-P□□□HS	APCS-P□□□NB	APCS-P□□□NB	APCS-P□□□NB
		□130	SE17G	L7SA020A					
		□180	SF20G	L7SA035A					
		2,700	□180	LF30G					
		3,000	□180	SF44G					
		3,000	□220	SG20G					
		2,700	□220	LG30G					
		3,000	□220	SG44G					
		□130	SE03M	L7SA004A	APCS-E□□□BS	APCS-P□□□HS	APCS-P□□□NB	APCS-P□□□NB	APCS-P□□□NB
		□130	SE06M	L7SA008A					
		□130	SE09M	L7SA010A					
		□130	SE12M	L7SA020A					
		□180	SF12M	L7SA020A					
		□180	SF20M	L7SA035A					
		1,700	□180	LF30M					
		2,000	□180	SF44M					
1,000	2,000	□130	SG12M	L7SA020A	APCS-E□□□AS	APCS-P□□□HS	APCS-P□□□NB	APCS-P□□□NB	APCS-P□□□NB
		□220	SG20M	L7SA035A					
		1,700	□220	LG30M					
		2,000	□220	SG44M					
		□130	HE09A	L7SA008A					
		□130	HE15A	L7SA020A	APCS-E□□□BS	APCS-P□□□HS	APCS-P□□□LB	APCS-P□□□LB	APCS-P□□□SB
		□130	HE30A	L7SA050A					
		□60	HB01A	L7SA002A					
		□60	HB02A	L7SA002A					
		□60	HB04A	L7SA004A					
3,000	3,500	□130	HE09A	L7SA008A	* 1,024 P/R	APCS-E□□□AS	APCS-P□□□GS	APCS-P□□□SB	APCS-P□□□SB
		□130	HE15A	L7SA020A	* 2,048 P/R	APCS-E□□□BS	APCS-P□□□HS		
		□130	HE30A	L7SA050A					

L7 SERIES SYSTEM

L7S Drive Combination Table

L7SA Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder Cable		Power Cable		
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake
3,000	5,000	18Bit Serial / M-Turn Abs	□40	FALR5A	L7SA001B	APCS-E□□□□ES	APCS-E□□□□ES1	APCS-P□□□□LS	APCS-P□□□□QS	APCS-P□□□□QS
			□40	FAL01A	L7SA001B					
			□40	FAL015A	L7SA004B					
			□60	FBL01A	L7SA001B					
			□60	FBL02A	L7SA002B					
			□60	FBL04A	L7SA004B					
			□80	FCL04A	L7SA004B					
			□80	FCL06A	L7SA008B					
			□80	FCL08A	L7SA008B					
			□80	FCL10A	L7SA010B					
2,000	3,000	19Bit Serial / M-Turn Abs	□60	FB01A	L7SA001B			APCS-P□□□□FS	APCS-P□□□□QS	APCS-P□□□□QS
			□60	FB02A	L7SA002B					
			□60	FB04A	L7SA004B					
			□80	FC04A	L7SA004B					
			□80	FC06A	L7SA008B					
			□80	FC08A	L7SA008B					
			□80	FC10A	L7SA010B					
			□130	FE09A	L7SA010B					
			□130	FE15A	L7SA020B					
			□130	FE22A	L7SA020B					
1,500	3,000	APCS-E□□□□DS	□130	FE30A	L7SA035B	APCS-E□□□□DS1	APCS-P□□□□HS	APCS-P□□□□NB	APCS-P□□□□SB	
			□180	FF30A	L7SA035B					
			□180	FF50A	L7SA050B					
			□80	FCL03D	L7SA004B					
			□80	FCL05D	L7SA008B					
			□80	FCL06D	L7SA008B					
			□80	FCL07D	L7SA008B					
			□80	FC03D	L7SA004B					
			□80	FC05D	L7SA008B					
			□80	FC06D	L7SA008B					
1,000	2,000	APCS-E□□□□DS	□80	FC07D	L7SA008B	APCS-E□□□□ES1	APCS-P□□□□FS	APCS-P□□□□QS	APCS-P□□□□SB	
			□130	FE06D	L7SA008B					
			□130	FE11D	L7SA010B					
			□130	FE16D	L7SA020B					
			□130	FE22D	L7SA020B					
			□180	FF22D	L7SA020B					
			□180	FF35D	L7SA035B					
			□180	FF55D	L7SA050B					
			3,000	FG22D	L7SA020B					
			2,700	FG35D	L7SA035B					
PEGASUS Series	3,000	APCS-E□□□□DS	3,000	FG55D	L7SA050B	APCS-E□□□□DS1	APCS-P□□□□HS	APCS-P□□□□NB	APCS-P□□□□SB	
			□130	FE05G	L7SA008B					
			□130	FE09G	L7SA010B					
			□130	FE13G	L7SA020B					
			□130	FE17G	L7SA020B					
			□180	FF20G	L7SA020B					
			2,700	FF30G	L7SA035B					
			3,000	FF44G	L7SA050B					
			3,000	FG20G	L7SA020B					
			2,700	FG30G	L7SA035B					
Options	2,000	APCS-E□□□□DS	3,000	FG44G	L7SA050B	APCS-E□□□□DS1	APCS-P□□□□HS	APCS-P□□□□NB	APCS-P□□□□SB	
			□130	FE03M	L7SA004B					
			□130	FE06M	L7SA008B					
			□130	FE09M	L7SA010B					
			□130	FE12M	L7SA020B					
			□180	FF12M	L7SA020B					
			□180	FF20M	L7SA020B					
			1,700	FF30M	L7SA035B					
			2,000	FF44M	L7SA050B					
			1,700	FG30M	L7SA035B					
			2,000	FG44M	L7SA050B					

L7S Drive Combination Table

L7SB Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder Cable		Power Cable		
					Serial Type	Single Turn	Multi Turn	For power	Power + Brake	Brake
3,000	5,000		□130	FEP09A	L7SB010B			APCF-P□□□HS	APCF-P□□□NB	
			□130	FEP15A	L7SB020B					
			□130	FEP22A	L7SB035B					
			□130	FEP30A	L7SB035B					
			□180	FFP30A	L7SB035B					
			□180	FFP50A	L7SB050B					
2,000	3,000		□130	FEP06D	L7SB010B			APCF-P□□□HS	APCF-P□□□NB	
			□130	FEP11D	L7SB010B					
			□130	FEP16D	L7SB020B					
			□130	FEP22D	L7SB020B					
			□180	FFP22D	L7SB020B					
			□180	FFP35D	L7SB035B					
			□180	FFP55D	L7SB050B					
	2,500		□180	FFP75D	L7SB075B			APCF-P□□□JS	APCF-P□□□LB	APCF-P□□□SB
	3,000		□220	FGP22D	L7SB020B					
			□220	FGP35D	L7SB035B					
			□220	FGP55D	L7SB050B					
1,500	3,000		□220	FGP75D	L7SB075B	APCS-E□□□DS	APCS-E□□□DS1	APCF-P□□□HS	APCF-P□□□NB	
			□220	FGP110D	L7SB150B					
			□130	FEP05G	L7SB010B					
			□130	FEP09G	L7SB010B					
			□130	FEP13G	L7SB020B					
	2,700		□130	FEP17G	L7SB020B			APCF-P□□□JS	APCF-P□□□PB	
			□180	FFP20G	L7SB020B					
			□180	FFP30G	L7SB035B					
			□180	FFP44G	L7SB050B			APCF-P□□□MS	APCF-P□□□LB	
	2,500		□180	FFP60G	L7SB075B					
			□180	FFP75G	L7SB075B					
			□220	FGP20G	L7SB020B			APCF-P□□□JS	APCF-P□□□MS	
	3,000		□220	FGP30G	L7SB035B					
			□220	FGP44G	L7SB050B			APCF-P□□□MS	APCF-P□□□SB	
			□220	FGP60G	L7SB075B					
1,000	2,000		□220	FGP85G	L7SB150B			APCF-P□□□JS	APCF-P□□□MS	
			□220	FGP110G	L7SB150B					
			□220	FGP150G	L7SB150B			APCF-P□□□MS	APCF-P□□□SB	
			□130	FEP03M	L7SB010B					
			□130	FEP06M	L7SB010B			APCF-P□□□HS	APCF-P□□□NB	
	2,000		□130	FEP09M	L7SB010B					
			□130	FEP12M	L7SB020B			APCF-P□□□IS	APCF-P□□□PB	
			□180	FFP12M	L7SB020B					
			□180	FFP20M	L7SB020B			APCF-P□□□JS	APCF-P□□□LB	
			□180	FFP30M	L7SB035B					
1,000	2,000		□180	FFP44M	L7SB050B			APCF-P□□□JS	APCF-P□□□MS	
			□220	FGP12M	L7SB020B					
			□220	FGP20M	L7SB020B			APCF-P□□□JS	APCF-P□□□MS	
			□220	FGP30M	L7SB050B					
			□220	FGP44M	L7SB050B			APCF-P□□□MS	APCF-P□□□SB	
			□220	FGP60M	L7SB075B					

PEGASUS Series MDM Series Options S Series F Series L7P Series L7NH Series L7N Series L7S Series

L7 SERIES SYSTEM

L7SA Drive Product Features

Item	Type Name	L7SA001□	L7SA002□	L7SA004□	L7SA008□	L7SA010□	L7SA020□	L7SA035□	L7SA050□
Input Power	Main Power Supply	3 Phase AC200 ~ 230[V](-15 ~ +10[%]), 50 ~ 60[Hz]							
	Control Power Supply	Single Phase AC200 ~ 230[V](-15 ~ +10[%]), 50 ~ 60[Hz]							
	Rated Current[A]	1.4	1.7	3.0	5.2	6.75	13.5	16.7	32
	Peak Current[A]	4.2	5.1	9.0	15.6	20.25	40.5	50.1	96
	Encoder Type	Quad. Type Incremental Line Driver Max 6000 [P/R] Serial Type : 18bit(FA type), 19bit, 20bit(MDM series)							
Control Performance	Speed Control	Speed Control Range	Maximum 1: 5000						
		Frequency Response	Maximum 1 [kHz] or above (When using 19bit Serial Encoder)						
		Speed Command	DC -10 [V]~+10 [V] (Reverse rotation in case of negative voltage)						
		Accel/Decel Time	Straight or S-curve acceleration/deceleration (0~10,000 [ms], possible to be set by one [ms] unit)						
		Speed Variation Ratio	±0.01 [%] or lower [when load changes between 0 and 100%] ±0.1[%] or lower [temperature 25 ±10°C]						
Control Performance	Position Control	Input Frequency	1[Mpps], Line Driver / 200[kpps], Open Collector						
		Input Pulse Type	Symbol + Pulse Series, CW+CCW, A/B Phase						
		Electric Gear Ratio	Four digital gear ratios can be set, selected and tuned.						
	Torque Control	Torque Command	DC -10~+10 [V] (Reverse direction torque in case of negative voltage)						
		Speed Limit	DC 0~10 [V], internal speed command within ±1[%]						
Input/Output Signal	Analog Input	Repetition accuracy	Within ±1[%]						
		Input Range	DC -10 ~ 10[V]						
	Analog Output	Resolution	12[bit]						
		Output Range	DC -10 ~ 10[V]						
	Digital Input	Resolution	12[bit]						
Communication	Digital Input	Total 10 Input Channels(assignment available) SVON, SPD1, SPD2, SPD3, ALMRST, DIR, CCWLIM, CWLIM, EMG, STOP, EGEAR1, EGEAR2, PCON, GAIN2, P_CLR, T_LMT, MODE, ABS_RQ, ZCLAMP Above 19 functions can be used selectively for assignment Signal can be set as positive logic or negative logic							
		Total 5 Channels(assignment available), 3 Channels(set as alarm code) ALARM, READY, ZSPD, BRAKE, INPOS, TLMT, VLMT, INSPD, WARN Above 9 outputs can be used selectively for assignment Signal can be set as positive logic or negative logic							
		Digital Output							
		RS422	Accessible to PC software and the RS422 server						
		USB	Status monitoring, JOG operation, parameter upload/download are available with PC Software						
Built-in functions	Encoder	Encoder	Serial BiSS encoder and quadrature encoder supported						
		Encoder Output Type	Random pre-scale output through FPGA (maximum 6.4 Mpps)						
		Dynamic Braking	Standard built-in (activated when the servo alarm goes off or when the servo is off)						
		Regenerative Braking	Both default built-in and external installation possible						
		Display	Seven segments (5 DIGIT)						
Environment	Protective Function	Setting Function	Loader (SET, MODE, UP, and [DOWN] keys)						
		Additional Function	Auto gain tuning, phase Z detection, manual JOG operation, program JOG operation, automatic analog input calibration						
		Overcurrent, overload, overvoltage, insufficient voltage, main power input problem, control power input problem, overspeed, motor cable, overheating(power module overheating, abnormal drive operation's temp), encoder problem, over-regenerative, sensor problem, communication problem							
		Temperature	0 ~ 50[°C]						
		Humidity	Below 90[%]RH(avoid dew-condensation)						
	Environment	Environment	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.						

L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

L7SB Drive Product Features

Item	Type Name	L7SB010B	L7SB020B	L7SB035B	L7SB050B	L7SB075B	L7SB150B
Input Power	Main Power Supply	3 Phase AC380 ~ 480[V](-15 ~ +10[%]), 50 ~ 60[Hz]					
	Control Power Supply	Single Phase AC380 ~ 480[V](-15 ~ +10[%]), 50 ~ 60[Hz]					
	Rated Current[A]	3.7	8	10.1	17.5	22.8	39
	Peak Current[A]	11.1	24	30.3	52.5	57	97.5
	Encoder Type	Quad. Type Incremental Line Driver Max 6000 [P/R] Serial Type : 18bit(FA type), 19bit, 20bit(MDM series)					
Control Performance	Speed Control	Speed Control Range	Maximum 1: 5000				
		Frequency Response	Maximum 1 [kHz] or above (when the 19-bit serial encoder is applied)				
		Speed Command	DC -10 [V]~+10 [V] (Reverse rotation in case of negative voltage)				
		Accel/Decel Time	Straight or S-curve acceleration/deceleration (0~10,000 [ms], possible to be set by one [ms] unit)				
		Speed Variation Ratio	±0.01 [%] or lower [when load changes between 0 and 100%] ±0.1[%] or lower [temperature 25 ±10°C]				
	Position Control	Input Frequency	1[Mpps], Line Driver / 200[kpps], Open Collector				
		Input Pulse Type	Symbol + pulse series, CW+CCW, A/B phase				
		Electric Gear Ratio	Four digital gear ratios can be set, selected and tuned.				
	Torque Control	Torque Command	DC -10~+10 [V] (Reverse direction torque in case of negative voltage)				
		Speed Limit	DC 0~10 [V], internal speed command within ±1[%]				
Input/Output Signal	Analog Input	Input Range	DC 0 ~ 10[V]				
		Resolution	12[bit]				
		Output Range	DC 0 ~ 10[V]				
		Resolution	12[bit]				
	Digital Input		A total of 10 input channels (allocable) SVON, SPD1, SPD2, SPD3, ALMRST, DIR, CCWLIM, CWLIM, EMG, STOP, EGEAR1, EGEAR2, PCON, GAIN2, P_CLR, T_LMT, MODE, ABS_RQ, ZCLAMP You can selectively allocate a total of 19 functions. You can set the positive/negative logic of the selected signal.				
	Digital Output		A total of 5 channels (allocable), 3 channels (fixed with alarm codes) ALARM, READY, ZSPD, BRAKE, INPOS, TLMT, VLMT, INSPD, WARN You can selectively allocate a total of nine kinds of output. You can set the positive/negative logic of the selected signal.				
Communication	RS422	Accessible to PC software and the RS422 server					
	USB	Status monitoring through PC software, JOG operation, and parameter uploading/downloading are possible.					
	Encoder	Serial BiSS encoder and quadrature encoder supported					
	Encoder Output Type	Random pre-scale output through FPGA (maximum 6.4 Mpps)					
Built-in functions	Dynamic Braking	Standard built-in (activated when the servo alarm goes off or when the servo is off)					
	Regenerative Braking	Both default built-in and external installation possible					
	Display	Seven segments (5 DIGIT)					
	Setting Function	Loader (SET, MODE, UP, and [DOWN] keys)					
	Additional Function	Auto gain tuning, phase Z detection, manual JOG operation, program JOG operation, automatic analog input calibration					
	Protective Function	Overcurrent, overload, overvoltage, voltage lack, main power input error, control power input error, overspeed, motor cable, heating error (power module heating, drive temperature error), encoder error, excessive regeneration, sensor error, communication error					
Environment	Temperature	0 ~ 50[°C]					
	Humidity	90[%] RH or lower (no condensation)					
	Environment	Indoors, a place free from corrosive gas or combustible gas, or a place without liquid or conductive dust.					

L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series


19

L7 SERIES SYSTEM

External Dimensions of L7SA Drive


■ L7SA001□ ~ L7SA004□ [Weight : 1.2kg]

* Unit [mm]



■ L7SA008□ ~ L7SA010□ [Weight : 1.5kg(Fan-Cooling included)]


* Unit [mm]



External Dimensions of L7SA Drive


■ L7SA020□ ~ L7SA035□ [Weight : 2.5kg(Fan-Cooling included)]

*Unit [mm]



■ L7SA050□ [Weight : 5.5kg(Fan-Cooling included)]

*Unit [mm]



L7S Series

L7N Series

L7NH Series

L7P Series

F Series

MDM Series

Options


PEGASUS Series

L7 SERIES SYSTEM

External Dimensions of L7SB Drive


■ L7SB010B [Weight : 1.5kg(Fan–Cooling included)]

* Unit [mm]



■ L7SB020B / L7SB035B [Weight : 2.5kg(Fan–Cooling included)]


* Unit [mm]



External Dimensions of L7SB Drive


L7SB050B [Weight : 5.5kg(Fan–Cooling included)]

*Unit [mm]



L7SB075B [Weight : 8.5kg(Fan–Cooling included)]

*Unit [mm]



L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series


Options

L7 SERIES SYSTEM

External Dimensions of L7SB Drive

■ L7SB150B [Weight : 15.5kg(Fan-Cooling included)]

* Unit [mm]




EtherCAT Communication Command Type

I L7N Series



■ Servo Drive Designation



L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series

Options

L7 SERIES SYSTEM

L7N Series

Characteristic

Real-time control by EtherCAT

- High speed, Real-time capability and Synchronization mechanism
- 100BASE-TX(100Mbps) EtherNET based real-time communication


Support Various Operation Mode

- Cyclic(P/S/T) Mode and Profile (P/S/T)Mode, Homming Mode

High Response for Precision Control

- High Resolutions Serial type Encoder(19Bit, BiSS)
- Improved Speed Response(=1Khz) Frequency

Identifying the Part of L7N Drive



- ① Operation keys (Mode, Up, Down, Set)
- ② Charge lamp
- ③ Main power connector (L1, L2, L3)
- ④ DC reactor connector(PO, PI)
 - Short circuit when not used
- ⑤ Regenerative Resistor Connector (B+, B, BI)
 - Short-Circuit B, BI terminals when standard type
 - Use B+, B terminals when using external resistor
- ⑥ Control Power Connector (C1, C2)
- ⑦ Front cover
- ⑧ Servo Motor Connecting Terminals (U, V, W)
- ⑨ Heat Sink
- ⑩ Display
- ⑪ Status LED
- ⑫ CN5:USB connector
- ⑬ CN4:EtherCAT Communication Port (IN)
- ⑭ CN3:EtherCAT Communication Port (OUT)
- ⑮ CN6 : STO Connector
- ⑯ CN1 : Control Signal Connector
- ⑰ CN2 : Encoder Signal Connector
- ⑱ PE(Protective Earth)

L7N Drive Combination Table

L7N Serial Type

Rated Speed (rpm)	Maximum speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder Cable		Power Cable						
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake	Brake			
3,000	5,000	<input type="checkbox"/> 40 FALR5A L7NA001B <input type="checkbox"/> 40 FAL01A L7NA001B <input type="checkbox"/> 40 FAL015A L7NA004B <input type="checkbox"/> 60 FBL01A L7NA001B <input type="checkbox"/> 60 FBL02A L7NA002B <input type="checkbox"/> 60 FBL04A L7NA004B <input type="checkbox"/> 80 FCL04A L7NA004B <input type="checkbox"/> 80 FCL06A L7NA008B <input type="checkbox"/> 80 FCL08A L7NA008B <input type="checkbox"/> 80 FCL10A L7NA010B <input type="checkbox"/> 60 FB01A L7NA001B <input type="checkbox"/> 60 FB02A L7NA002B <input type="checkbox"/> 60 FB04A L7NA004B <input type="checkbox"/> 80 FC04A L7NA004B <input type="checkbox"/> 80 FC06A L7NA008B <input type="checkbox"/> 80 FC08A L7NA008B <input type="checkbox"/> 80 FC10A L7NA010B <input type="checkbox"/> 130 FE09A L7NA010B <input type="checkbox"/> 130 FE15A L7NA020B <input type="checkbox"/> 130 FE22A L7NA020B <input type="checkbox"/> 130 FE30A L7NA035B <input type="checkbox"/> 180 FF30A L7NA035B <input type="checkbox"/> 180 FF50A L7NA050B	<small>* 18Bit Serial / M-Turn Abs</small>	APCS-E□□□ES	APCS-E□□□ESI	APCS-P□□□LS	APCS-B□□□QS	APCS-P□□□FS	APCS-P□□□HS	APCS-P□□□NB	APCS-P□□□IS	APCS-P□□□PB	APCS-P□□□JS	APCS-P□□□LB
2,000	3,000	<input type="checkbox"/> 80 FCL03D L7NA004B <input type="checkbox"/> 80 FCL05D L7NA008B <input type="checkbox"/> 80 FCL06D L7NA008B <input type="checkbox"/> 80 FCL07D L7NA008B <input type="checkbox"/> 80 FC03D L7NA004B <input type="checkbox"/> 80 FC05D L7NA008B <input type="checkbox"/> 80 FC06D L7NA008B <input type="checkbox"/> 80 FC07D L7NA008B <input type="checkbox"/> 130 FE06D L7NA008B <input type="checkbox"/> 130 FE11D L7NA010B <input type="checkbox"/> 130 FE16D L7NA020B <input type="checkbox"/> 130 FE22D L7NA020B <input type="checkbox"/> 180 FF22D L7NA020B <input type="checkbox"/> 180 FF35D L7NA035B <input type="checkbox"/> 180 FF55D L7NA050B	<small>* 19Bit Serial / M-Turn Abs</small>	APCS-E□□□ES	APCS-E□□□ESI	APCS-P□□□LS	APCS-B□□□QS	APCS-P□□□FS	APCS-P□□□HS	APCS-P□□□NB	APCS-P□□□IS	APCS-P□□□PB	APCS-P□□□JS	APCS-P□□□LB
1,500	3,000	<input type="checkbox"/> 130 FE05G L7NA008B <input type="checkbox"/> 130 FE09G L7NA010B <input type="checkbox"/> 130 FE13G L7NA020B <input type="checkbox"/> 130 FE17G L7NA020B <input type="checkbox"/> 180 FF20G L7NA020B <input type="checkbox"/> 180 FF30G L7NA035B <input type="checkbox"/> 180 FF44G L7NA050B	<small>* 19Bit Serial / M-Turn Abs</small>	APCS-E□□□DS	APCS-E□□□DSI	APCS-P□□□LS	APCS-B□□□QS	APCS-P□□□FS	APCS-P□□□HS	APCS-P□□□NB	APCS-P□□□IS	APCS-P□□□PB	APCS-P□□□JS	APCS-P□□□LB
1,000	2,000	<input type="checkbox"/> 130 FE03M L7NA004B <input type="checkbox"/> 130 FE06M L7NA008B <input type="checkbox"/> 130 FE09M L7NA010B <input type="checkbox"/> 130 FE12M L7NA020B <input type="checkbox"/> 180 FF12M L7NA020B <input type="checkbox"/> 180 FF20M L7NA020B <input type="checkbox"/> 180 FF30M L7NA035B <input type="checkbox"/> 180 FF44M L7NA050B	<small>* 19Bit Serial / M-Turn Abs</small>	APCS-E□□□DS	APCS-E□□□DSI	APCS-P□□□LS	APCS-B□□□QS	APCS-P□□□FS	APCS-P□□□HS	APCS-P□□□NB	APCS-P□□□IS	APCS-P□□□PB	APCS-P□□□JS	APCS-P□□□LB

L7 SERIES SYSTEM

L7N Drive Product Features

Item	Type Name	L7NA001B	L7NA002B	L7NA004B	L7NA008B	L7NA010B	L7NA020B	L7NA035B	L7NA050B
Input Power	Main Power Supply	3 Phase AC200 ~ 230[V](-15 ~ +10[%]), 50 ~ 60[Hz]							
	Control Power Supply	Single Phase AC200 ~ 230[V](-15 ~ +10[%]), 50 ~ 60[Hz]							
Rated Current[A]		1.4	1.7	3.0	5.2	6.75	13.5	16.7	32
Peak Current[A]		4.2	5.1	9.0	15.6	20.25	40.5	50.1	96
Encoder Type		Serial Type : 18 bit(FA type), 19bit, 20bit(MDM series)							
Control Performance	Speed Control Range	Maximum 1: 5000							
	Frequency Response	Maximum 1 kHz or more (when the 19-bit serial encoder is applied)							
	Speed Variation Ratio	$\pm 0.01\%$ or lower(When the load changes between 0 and 100%) $\pm 0.1\%$ or less(Temperature of 25°C [± 10])							
	Torque Control Repetition Accuracy	Within $\pm 1\%$							
Supported Drive Modes (CiA402)		Profile Position Mode Profile Velocity Mode Profile Torque Mode Interpolated Position Mode Cyclic Synchronous Position Mode Cyclic Synchronous Velocity Mode Cyclic Synchronous Torque Mode Homing Mode							
Digital Input/Output	Digital Input	Total 6 input channels (allocable) PCON, GAIN2, ALMRST, HOME, P-OT, N-OT Above 6 functions can be used selectively for assignment. Signal can be set as positive logic or negative logic.							
	Touch Probe Input	There are 2 input channels, Provides rising and falling edge detection functions for each channel.							
	Digital Output	Total 4 channels (allocable) ALARM, READY, ZSPD, BRAKE, INPOS, INSPD, WARN Above 7 outputs can be used selectively for assignment. Signal can be set as positive logic or negative logic.							
Additional Communication	USB	Program download is available with USB Communication.							
Built-in Functions	Dynamic Braking	Built-in type(operates when Servo alarm or Servo off)							
	Regenerative Braking	Built-in type, and also external connection is available							
	Display	7 segments(5DIGIT)							
	Setting Function	Loder(SET), (MODE)							
	Additional Function	Auto gain tuning function							
	Protective Function	Overcurrent, overload, overvoltage, insufficient voltage, main power input problem, control power input problem, overspeed, motor cable, overheating(power module overheating, abnormal drive operation's temp), encoder problem, over-regenerative, sensor problem, communication problem							
Operation Environment	Temperature	0 ~ 50[°C]							
	Humidity	Below 90[%]RH(avoid dew-condensation)							
	Environment	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.							

L7S Series

L7N Series

L7NH Series

S Series

F Series

MDM Series


Options

PEGASUS Series

External Dimensions of L7SN Drive


L7NA001B ~ L7NA004B [Weight : 1.0kg]

*Unit [mm]



L7NA008B / L7NA010B [Weight : 1.5kg(Fan-Cooling included)]

*Unit [mm]



L7S Series

L7N Series

L7NH Series L7P Series

S Series

F Series

MDM Series

Options


PEGASUS Series

L7 SERIES SYSTEM

External Dimensions of L7SN Drive


■ L7NA020B / L7NA035B [Weight : 2.5kg(Fan-Cooling included)]

* Unit [mm]



■ L7NA050B [Weight : 5.5kg(Fan-Cooling included)]

* Unit [mm]



All-in-one EtherCAT Communication Command Type

L7NH Series



Servo Drive Designation

L7	NH	A	004	U	AA
Model Name	Communication	Input Power Supply	Capacity	Encoder Type	Option
Servo Series	Network / All-in-One Type	A : 200VAC B : 400VAC	001 : 100W 002 : 200W 004 : 400W 008 : 750W 010 : 1.0kW 020 : 2.0kW 035 : 3.5kW 050 : 5.0kW 075 : 7.5kW 150 : 15kW	U : Universal	Exclusive Option Code

* Range

- 200V : 0.1kW~15kW
- 400V : 1.0kW~15kW

L7 SERIES SYSTEM

L7NH Series

Characteristic

Real-time control through EtherCAT

- High speed, Real-time capability and Synchronization mechanism
- Improved EtherCAT communication speed(min. 250us, DC support)
- Supporting CoE, EoE and FoE
- Improved Speed Response(=1.6Khz) Frequency

Improved Control Performance


- Improved Control bandwidth
- Providing 4-step Notch-Filter
- Vibration control by Real-time FFT
- Real-time gain tuning function

Support various motor and Encoder drive

- Supporting Rotary, DD and Motor drive (supporting3rd party motor)
- Quadrature, BiSS-C, Tamagawa serial abs, EnDat 2,2

Identifying the Part of L7NH Drive

[L7NH]



- 1 Display
- 2 State LED
- 3 Charge Lamp
- 4 Main Power Connector (L1, L2, L3)
- 5 DC Reactor Connector (PO, PI)
- 6 Regenerative Resistance Connector (B+, B, BI)
 - Short-Circuit B, BI terminals when standard type
 - Use B+, B terminals when using external resistor
- 7 Control Power Connector (C1, C2)
- 8 Servo Motor Connecting Terminal (U,V,W)
- 9 Connector for Analog Monitor
- 10 Node Address Setting Switch
- 11 USB Connector
- 12 EtherCAT Communication Port (IN)
- 13 EtherCAT Communication Port (OUT)
- 14 Safety Torque off Connector
- 15 Input / Output signal /Connector
- 16 Encoder Connector (ENCODER)
- 17 PE(Protective Earth)

L7NHA Drive Combination Table

L7NHA Incremental Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable	Power Cable		
					Quadrature Type	INC	For power	Power + Brake	Brake
3,000	5,000		□40	SAR3A	L7NHA001U	* 2,048 P/R	APCS-E□□□AS	APCS-P□□□GS	APCS-P□□□KB
			□40	SAR5A	L7NHA001U				
			□40	SA01A	L7NHA001U				
			□40	SA015A	L7NHA002U				
			□60	SB01A	L7NHA002U				
			□60	SB02A	L7NHA002U				
			□60	SB04A	L7NHA004U				
			□80	SC04A	L7NHA004U				
			□80	SC06A	L7NHA008U				
			□80	SC08A	L7NHA008U				
			□80	SC10A	L7NHA010U				
			□130	SE09A	L7NHA008U				
			□130	SE15A	L7NHA020U				
			□130	SE22A	L7NHA020U				
			□130	SE30A	L7NHA035U				
			□180	SF30A	L7NHA035U				
			□180	SF50A	L7NHA050U				
2,000	3,000		□80	SC03D	L7NHA004U	* 3,000 P/R	APCS-E□□□AS	APCS-P□□□GS	APCS-P□□□KB
			□80	SC05D	L7NHA008U				
			□80	SC06D	L7NHA008U				
			□80	SC07D	L7NHA008U				
			□130	SE06D	L7NHA008U				
			□130	SE11D	L7NHA010U				
			□130	SE16D	L7NHA020U				
			□130	SE22D	L7NHA020U				
			□180	SF22D	L7NHA020U				
			□180	LF35D	L7NHA035U				
			□180	SF55D	L7NHA050U				
			□180	SF75D	L7NHA075U				
	2,500		□220	SG22D	L7NHA020U				
			□220	LG35D	L7NHA035U				
			□220	SG55D	L7NHA050U				
			□220	SG75D	L7NHA075U				
1,500	3,000		□220	SG110D	L7NHA150U	APCS-E□□□BS	APCS-P□□□VS	APCS-P□□□SB	APCS-P□□□SB
			□130	SE05G	L7NHA008U				
			□130	SE09G	L7NHA010U				
			□130	SE13G	L7NHA020U				
			□130	SE17G	L7NHA020U				
			□180	SF20G	L7NHA035U				
			□180	SF44G	L7NHA050U				
			□180	SF60G	L7NHA075U				
			□220	SF75G	L7NHA150U				
			□180	LF30G	L7NHA035U				
			□220	SG20G	L7NHA020U				
			□220	LG30G	L7NHA035U				
			□220	SG60G	L7NHA075U				
			□220	SG85G	L7NHA150U				
			□220	SG110G	L7NHA150U				
			□220	SG150G	L7NHA150U				
1,000	2,000		□130	SE03M	L7NHA004U	APCS-E□□□BS	APCS-P□□□VS	APCS-P□□□SB	APCS-P□□□SB
			□130	SE06M	L7NHA008U				
			□130	SE09M	L7NHA010U				
			□130	SE12M	L7NHA020U				
			□180	SF12M	L7NHA020U				
			□180	SF20M	L7NHA035U				
			□180	LF30M	L7NHA035U				
			□180	SF44M	L7NHA050U				
			□220	SG12M	L7NHA020U				
			□220	SG20M	L7NHA035U				
3,000	3,500		□1700	□1700	L7NHA035U	* 1,048 P/R	APCS-E□□□AS	APCS-P□□□GS	APCS-P□□□NB
			□2000	□2000	L7NHA050U				
			□2000	□2000	L7NHA075U				
			□220	□220	L7NHA075U				
			□220	□220	L7NHA050U				
			□220	□220	L7NHA035U				
			□220	□220	L7NHA020U				
3,000	3,500		□60	HB01A	L7NHA002U	* 2,048 P/R	APCS-E□□□BS	APCS-P□□□HS	APCS-P□□□SB
			□60	HB02A	L7NHA002U				
			□60	HB04A	L7NHA004U				
			□130	HE09A	L7NHA008U				
			□130	HE15A	L7NHA020U				
			□130	HE30A	L7NHA050U				

 L7S Series
 L7N Series
 L7NH Series
 L7P Series
 S Series
 F Series
 MDM Series
 Options
 PEGASUS Series

L7 SERIES SYSTEM

L7NHA Drive Combination Table

L7NHA Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable		Power Cable		
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake
3,000	5,000	5,000	□40	FALR5A	L7NHA001U	* 18Bit Serial / M-Turn Abs	APCS-E□□□□ES	APCS-E□□□□ES1	APCS-P□□□□LS	APCS-B□□□□QS
			□40	FAL01A	L7NHA001U					
			□40	FAL015A	L7NHA004U					
			□60	FBL01A	L7NHA001U					
			□60	FBL02A	L7NHA002U					
			□60	FBL04A	L7NHA004U					
			□80	FCL04A	L7NHA004U					
			□80	FCL06A	L7NHA008U					
			□80	FCL08A	L7NHA008U					
			□80	FCL10A	L7NHA010U					
			□60	FB01A	L7NHA001U					
			□60	FB02A	L7NHA002U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□FS	APCS-B□□□□QS	
			□60	FB04A	L7NHA004U					
			□80	FC04A	L7NHA004U					
			□80	FC06A	L7NHA008U					
			□80	FC08A	L7NHA008U					
			□80	FC10A	L7NHA010U					
			□130	FE09A	L7NHA010U					
			□130	FE15A	L7NHA020U					
			□130	FE22A	L7NHA020U					
			□130	FE30A	L7NHA035U					
2,000	3,000	3,000	□80	FCL03D	L7NHA004U	APCS-E□□□□ES	APCS-E□□□□ES1	APCS-P□□□□LS	APCS-B□□□□QS	
			□80	FCL05D	L7NHA008U					
			□80	FCL06D	L7NHA008U					
			□80	FCL07D	L7NHA008U					
			□80	FC03D	L7NHA004U					
			□80	FC05D	L7NHA008U					
			□80	FC06D	L7NHA008U					
			□80	FC07D	L7NHA008U					
			□130	FE06D	L7NHA008U					
			□130	FE11D	L7NHA010U					
1,500	3,000	3,000	□130	FE16D	L7NHA020U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□FS	APCS-B□□□□QS	
			□130	FE22D	L7NHA020U					
			□180	FF22D	L7NHA020U					
			□180	FF35D	L7NHA035U					
			□180	FF55D	L7NHA050U					
			□180	FF75D	L7NHA075U					
			□220	FG22D	L7NHA020U					
			□220	FG35D	L7NHA035U					
			□220	FG55D	L7NHA050U					
			□220	FG75D	L7NHA075U					
1,000	2,000	2,000	□130	FE05G	L7NHA008U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□HS	APCS-P□□□□NB	
			□130	FE09G	L7NHA010U					
			□130	FE13G	L7NHA020U					
			□130	FE17G	L7NHA020U					
			□180	FF20G	L7NHA020U					
			□180	FF30G	L7NHA035U					
			□180	FF44G	L7NHA050U					
			□180	FF60G	L7NHA075U					
			□220	FG20G	L7NHA020U					
			□220	FG30G	L7NHA035U					
PEGASUS Series	Options	S Series	□220	FG44G	L7NHA050U					
			□220	FG60G	L7NHA075U					
			□220	FG75G	L7NHA075U					
			□220	FG20G	L7NHA020U					
			□220	FG30G	L7NHA035U					
			□220	FG44G	L7NHA050U					
			□220	FG60G	L7NHA075U					
			□220	FG85G	L7NHA150U					
MDM Series	F Series	L7P Series	□220	FG11G	L7NHA150U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□VS	APCS-P□□□□SB	
			□220	FG12G	L7NHA150U					
			□220	FG15G	L7NHA150U					
			□220	FE03M	L7NHA004U					
			□130	FE06M	L7NHA008U					
			□130	FE09M	L7NHA010U					
			□130	FE12M	L7NHA020U					
			□180	FF12M	L7NHA020U					
L7S Series	L7N Series	S Series	□180	FF20M	L7NHA020U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□VS	APCS-P□□□□SB	
			□180	FF30M	L7NHA035U					
			□180	FF44M	L7NHA050U					
			□220	FG12M	L7NHA020U					
			□220	FG20M	L7NHA020U					
			□220	FG30M	L7NHA035U					
			□220	FG44M	L7NHA050U					
			□220	FG60M	L7NHA075U					

L7NHB Drive Combination Table

L7NHB Incremental Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable	Power Cable		
					Quadrature Type	INC	For power	Power + Brake	Brake
3,000	5,000		□130	SEP09A	L7NHB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP15A	L7NHB020U				
			□130	SEP22A	L7NHB020U				
			□130	SEP30A	L7NHB035U				
			□180	SFP30A	L7NHB035U				
			□180	SFP50A	L7NHB050U				
2,000	3,000		□130	SEP06D	L7NHB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP11D	L7NHB010U				
			□130	SEP16D	L7NHB020U				
			□130	SEP22D	L7NHB020U				
			□180	SFP22D	L7NHB020U				
			□180	SFP35D	L7NHB035U				
			□180	SFP55D	L7NHB050U		APCF-P□□□JS	APCF-P□□□LB	APCF-P□□□SB
			□180	SFP75D	L7NHB075U				
			□220	SGP22D	L7NHB020U				
			□220	SGP35D	L7NHB035U				
			□220	SGP55D	L7NHB050U				
			□220	SGP75D	L7NHB075U				
1,500	3,000		□130	SEP05G	L7NHB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP09G	L7NHB010U				
			□130	SEP13G	L7NHB020U				
			□130	SEP17G	L7NHB020U				
			□180	SFP20G	L7NHB020U		APCF-P□□□IS	APCF-P□□□PB	
			□180	SFP30G	L7NHB050U				
			□180	SFP44G	L7NHB050U				
			□180	SFP60G	L7NHB075U				
			□180	SFP75G	L7NHB075U		APCF-P□□□JS	APCF-P□□□LB	APCF-P□□□SB
			□220	SGP20G	L7NHB020U				
			□220	SGP30G	L7NHB050U				
			□220	SGP44G	L7NHB050U				
			□220	SGP60G	L7NHB075U		APCF-P□□□MS		
			□220	SGP85G	L7NHB150U				
1,000	2,000		□220	SGP10G	L7NHB150U				
			□220	SGP15G	L7NHB150U				
			□130	SEP03M	L7NHB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP06M	L7NHB010U				
			□130	SEP09M	L7NHB010U				
			□130	SEP12M	L7NHB020U		APCF-P□□□IS	APCF-P□□□PB	APCF-P□□□SB
			□180	SFP12M	L7NHB020U				
			□180	SFP20M	L7NHB020U				
			□180	SFP30M	L7NHB035U				
			□180	SFP44M	L7NHB050U				
			□220	SGP12M	L7NHB020U				
			□220	SGP20M	L7NHB020U				
500	1,000		□220	SGP30M	L7NHB050U		APCF-P□□□JS	APCF-P□□□LB	
			□220	SGP44M	L7NHB050U				
			□220	SGP60M	L7NHB075U				
			□220	SGP85M	L7NHB150U				
			□220	SGP100M	L7NHB150U				
			□130	SEP03L	L7NHB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP06L	L7NHB010U				
			□130	SEP09L	L7NHB010U				
			□130	SEP12L	L7NHB020U		APCF-P□□□IS	APCF-P□□□PB	
			□180	SFP12L	L7NHB020U				
			□180	SFP20L	L7NHB020U				
250	500		□180	SFP30L	L7NHB035U		APCF-P□□□JS	APCF-P□□□LB	
			□180	SFP44L	L7NHB050U				
			□220	SGP12L	L7NHB020U				
			□220	SGP20L	L7NHB020U				
			□220	SGP30L	L7NHB050U				
			□220	SGP44L	L7NHB050U		APCF-P□□□JS	APCF-P□□□LB	
			□220	SGP60L	L7NHB075U				
			□220	SGP85L	L7NHB150U				
			□220	SGP100L	L7NHB150U				
			□130	SEP03S	L7NHB010U				
125	250		□130	SEP06S	L7NHB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP09S	L7NHB010U				
			□130	SEP12S	L7NHB010U				
			□180	SFP12S	L7NHB020U		APCF-P□□□IS	APCF-P□□□PB	
			□180	SFP20S	L7NHB020U				
			□180	SFP30S	L7NHB035U		APCF-P□□□JS	APCF-P□□□LB	
			□180	SFP44S	L7NHB050U				
			□220	SGP12S	L7NHB020U				
			□220	SGP20S	L7NHB020U				
			□220	SGP30S	L7NHB050U				
100	125		□220	SGP44S	L7NHB050U		APCF-P□□□JS	APCF-P□□□LB	
			□220	SGP60S	L7NHB075U				
			□220	SGP85S	L7NHB150U				
			□220	SGP100S	L7NHB150U				
			□130	SEP03T	L7NHB010U				
			□130	SEP06T	L7NHB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP09T	L7NHB010U				
			□130	SEP12T	L7NHB010U				
			□180	SFP12T	L7NHB020U		APCF-P□□□IS	APCF-P□□□PB	
			□180	SFP20T	L7NHB020U				
50	100		□180	SFP30T	L7NHB035U		APCF-P□□□JS	APCF-P□□□LB	
			□180	SFP44T	L7NHB050U				
			□220	SGP12T	L7NHB020U				
			□220	SGP20T	L7NHB020U				
			□220	SGP30T	L7NHB050U				
			□220	SGP44T	L7NHB050U		APCF-P□□□JS	APCF-P□□□LB	
			□220	SGP60T	L7NHB075U				
			□220	SGP85T	L7NHB150U				
			□220	SGP100T	L7NHB150U				
			□130	SEP03U	L7NHB010U				



L7 SERIES SYSTEM

L7NHB Drive Combination Table

L7NHB Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable		Power Cable		
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake
3,000	5,000	□130	FEP09A	L7NHB010U	APCS-E□□□DS1 19Bit Serial / M-Turn Abs	APCF-P□□□HS APCF-P□□□IS APCF-P□□□JS APCF-P□□□MS	APCF-P□□□NB APCF-P□□□PB APCF-P□□□LB	APCF-P□□□SB	APCF-P□□□SB	APCF-P□□□SB
			FEP15A	L7NHB020U						
			FEP22A	L7NHB035U						
			FEP30A	L7NHB035U						
			FFF30A	L7NHB035U						
			FFF50A	L7NHB050U						
	3,000	□130	FEP06D	L7NHB010U						
			FEP11D	L7NHB010U						
			FEP16D	L7NHB020U						
			FEP22D	L7NHB020U						
			FFF22D	L7NHB020U						
			FFF35D	L7NHB035U						
2,000	2,500	□180	FFF55D	L7NHB050U						
			FFF75D	L7NHB075U						
			FGP22D	L7NHB020U						
			FGP35D	L7NHB035U						
			FGP55D	L7NHB050U						
			FGP75D	L7NHB075U						
	3,000	□220	FGP10D	L7NHB150U						
			FGP05G	L7NHB010U						
			FGP09G	L7NHB010U						
			FGP13G	L7NHB020U						
1,500	2,200	□180	FGP17G	L7NHB020U						
			FGP20G	L7NHB020U						
			FGP30G	L7NHB035U						
			FGP44G	L7NHB050U						
			FGP60G	L7NHB075U						
			FGP75G	L7NHB075U						
	2,500	□220	FGP20G	L7NHB020U						
			FGP30G	L7NHB035U						
			FGP44G	L7NHB050U						
			FGP60G	L7NHB075U						
1,000	2,000	□180	FGP85G	L7NHB150U						
			FGP110G	L7NHB150U						
			FGP150G	L7NHB150U						
			FEP03M	L7NHB010U						
			FEP06M	L7NHB010U						
			FEP09M	L7NHB010U						
	1,700	□180	FEP12M	L7NHB020U						
			FFF12M	L7NHB020U						
			FFF20M	L7NHB020U						
			FFF30M	L7NHB035U						
PEGASUS Series	2,000	□180	FFF44M	L7NHB050U						
			FFF12M	L7NHB020U						
			FFF20M	L7NHB020U						
			FFF30M	L7NHB050U						
			FFF44M	L7NHB050U						
			FFF60M	L7NHB075U						

L7NHA Drive Product Features

Item	Type Name	L7NHA001U	L7NHA002U	L7NHA004U	L7NHA008U	L7NHA010U	L7NHA020U	L7NHA035U	L7NHA050U	L7NHA075U	L7NHA150U
Input Power	Main Power Supply	3-Phase AC 200~230 [V] (-15~10[%]), 50~60 [Hz]									
	Control Power Supply	Single-Phase AC 200~230 [V] (-15~10[%]), 50~60 [Hz]									
	Rated Current[A]	1.4	1.7	3.0	5.2	6.75	13.5	16.7	32	39.4	76
	Peak Current[A]	4.2	5.1	9.0	15.6	20.25	40.5	50.1	90.88	98.5	190
	Encoder Type	Quadrature(Incremental) BISS-B, BISS-C(Absolute, Incremental) Tamagawa Serial(Absolute, Incremental) EnDat 2.2 Sinusoidal, Analog Hall									
Control Performance	Speed Control Range	Maximum 1: 5000									
	Frequency Response	Maximum 1[kHz] or above(When the 19-bit Serial Encoder is applied)									
	Speed Variation Ratio	±0.01[%] or lower(When the load changes between 0 and 100%) ±0.1[%] or less(Temperature of 25°C[±10])									
	Torque Control Repetition Accuracy	Within ±1%									
EtherCAT Communication Specifications	Communication Standard	FoE (Firmware download) EoE (Parameter setting by UDP, Tuning, Secondary function, Parameter copy) CoE (IEC 61158 Type12, IEC 61800-7 CIA 402 Drive profile)									
	Physical Layer	100BASE-TX(IEEE802.3)									
	Connector	RJ45 x 2									
	Communication distance	Within connection between nodes 100[m]									
	DC (Distributed Clock)	By DC mode synchronism, minimum DC cycle: 250[us]									
	LED Display	LinkAct IN, LinkAct OUT, RUN, ERR									
	Cia402 Drive Profile	Profile Position Mode Profile Velocity Mode Profile Torque Mode Cyclic Synchronous Position Mode Cyclic Synchronous Velocity Mode Cyclic Synchronous Torque Mode Homing Mode									
Digital Input/Output	Digital Input	Input Voltage range : DC 12[V] ~ DC 24[V] Total 8 input channels (allocable) Above 12 functions can be used selectively for assignment. (*POT, *NOT, *HOME, *STOP, *PCON, *GAIN2, *P_CL, *N_CL, PROBE1, PROBE2, EMG, A_RST) *Basic allocation signal									
	Digital Output	Service rating: DC 24[V] ±10%, 120[mA] Total 4 input channels (allocable) Above 11 functions can be used selectively for assignment. (*BRAKE±, *ALARM±, *READY±, *ZSPD±, INPOS±, TLMT±, VLMT±, INSPD±, WARN±, TGON±, INPOS2±) *Basic allocation signal									
	Safety Function	2 Input Channels (STO1, STO2), 1 Output Channels (EDM±)									
USB Communication	Fuction	Firmware download, Parameter setting, Tuning, Secondary function, Parameter copy									
	Communication Standard	USB 2.0 Full Speed (applies standard)									
	Connect	PC or USB storing medium									
Internal Function	Dynamic Braking	Standard built-in brake (activated when the servo alarm goes off or when the servo is off).									
	Regenerative Braking	Both the default built-in brake and an externally installed brake are possible.									
	Display Function	7 segments(5DIGIT)									
	Self-setting Function	Possible to set the drive node address by using Rotary Switch									
	Additional Function	Auto gain tuning function									
	Protection Function	Overcurrent, overload, overvoltage, insufficient voltage, main power input problem, control power input problem, overspeed, motor cable, overheating(power module overheating, abnormal drive operation's temp), encoder problem, over-regenerative, sensor problem, communication problem									
Environment	Temperature	0 ~ +50[°C] / -20~ +70[°C]									
	Humidity	Below 90[%]RH(avoid dew-condensation)									
	Environment	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.									

L7S Series

L7NH Series

L7P Series

S Series

F Series

PEGASUS Series

MDM Series

Options

L7 SERIES SYSTEM


L7NHB Drive Product Features

Item	Type Name	L7NHB010U	L7NHB020U	L7NHB035U	L7NHB050U	L7NHB075U	L7NHB150U
Input Power	Main Power Supply	3-Phase AC 380~480 [V] (-15~10[%]), 50~60 [Hz]					
	Control Power Supply	Single-Phase AC 380~480 [V] (-15~10[%]), 50~60 [Hz]					
	Rated Current[A]	3.7	8	10.1	17.5	22.8	39
	Peak Current[A]	11.1	24	30.3	47.25	57	97.5
	Encoder Type	Quadrature(Incremental) BISS-B, BISS-C(Absolute, Incremental) Tamagawa Serial(Absolute, Incremental) EnDat 2.2					
Control Performance	Speed Control Range	Maximum 1: 5000					
	Frequency Response	Maximum 1[kHz] or above(When the 19-bit Serial Encoder is applied)					
	Speed Variation Ratio	±0.01[%] or lower(When the load changes between 0 and 100%) ±0.1[%] or less(Temperature of 25°C[±10])					
	Torque Control Repetition Accuracy	Within ±1%					
EtherCAT Communication Specifications	Communication Standard	FoE (Firmware download) EoE (Parameter setting by UDP, Tuning, Secondary function, Parameter copy) CoE (IEC 61158 Type12, IEC 61800-7 CIA 402 Drive profile)					
	Physical Layer	100BASE-TX(IEEE802.3)					
	Connector	RJ45 x 2					
	Communication distance	Within connection between nodes 100[m]					
	DC (Distributed Clock)	By DC mode synchronism, minimum DC cycle: 250[us]					
	LED Display	LinkAct IN, LinkAct OUT, RUN, ERR					
	Cia402 Drive Profile	Profile Position Mode Profile Velocity Mode Profile Torque Mode Cyclic Synchronous Position Mode Cyclic Synchronous Velocity Mode Cyclic Synchronous Torque Mode Homing Mode					
Digital Input/Output	Digital Input	Input Voltage range : DC 12[V] ~ DC 24[V] Total 8 input channels (allocable) Above 12 functions can be used selectively for assignment. (*POT, *NOT, *HOME, *STOP, *PCON, *GAIN2, *P_CL, *N_CL, PROBE1, PROBE2, EMG, A_RST) *Basic allocation signal					
	Digital Output	Service rating: DC 24[V] ±10%, 120[mA] Total 4 input channels (allocable) Above 11 functions can be used selectively for assignment. (*BRAKE±, *ALARM±, *READY±, *ZSPD±, INPOS±, TLMT±, VLMT±, INSPD±, WARN±, TGON±, INPOS2±) *Basic allocation signal					
	Analog Monitor	There are 2 input channels. Above 15 functions can be used selectively for assignment.					
	Safety Function	2 Input Channels (STO1, STO2), 1 Output Channels (EDM±)					
USB Communication	Fuction	Firmware download, Parameter setting, Tuning, Secondary function, Parameter copy					
	Communication Standard	USB 2.0 Full Speed (applies standard)					
	Connect	PC or USB storing medium					
USB Communication	Dynamic Braking	Standard built-in brake (activated when the servo alarm goes off or when the servo is off).					
	Regenerative Braking	Both the default built-in brake and an externally installed brake are possible.					
	Display Function	7 segments(5DIGIT)					
	Self-setting Function	Possible to set the drive node address by using Rotary Switch					
	Additional Function	Auto gain tuning function					
	Protection Function	Overcurrent, overload, overvoltage, insufficient voltage, main power input problem, control power input problem, overspeed, motor cable, overheated(power module overheat, abnormal drive operation's temp), encoder problem, over-regenerative, sensor problem, communication problem					
Operation Environment	Temperature	0 ~ +50[°C] / -20~ +70[°C]					
	Humidity	Below 90[%]RH(avoid dew-condensation)					
	Other	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.					

External Dimensions of L7NHA Drive


■ L7NHA001U ~ L7NHA004U [Weight : 1.0kg]

*Unit [mm]



■ L7NHA008U / L7NHA010U [Weight : 1.5kg(Fan-Cooling included)]

*Unit [mm]




L7 SERIES SYSTEM

External Dimensions of L7NHA Drive


L7NHA020U / L7NHA035U [Weight : 2.5kg(Fan–Cooling included)]

* Unit [mm]



L7NHA050U [Weight : 5.5kg(Fan–Cooling included)]


* Unit [mm]



External Dimensions of L7NHA Drive


L7NHA075U [Weight : 8.5kg(Fan–Cooling included)]

*Unit [mm]



L7NHA150U [Weight : 16.2kg(Fan–Cooling included)]

*Unit [mm]




L7 SERIES SYSTEM

External Dimensions of L7NHB Drive


L7NHB010U [Weight : 1.5kg(Fan-Cooling included)]

* Unit [mm]



L7NHB020U / L7NHB035U [Weight : 2.5kg(Fan-Cooling included)]


* Unit [mm]



External Dimensions of L7NHB Drive


L7NHB050U [Weight : 5.5kg(Fan–Cooling included)]

*Unit [mm]



L7NHB075U [Weight : 8.5kg(Fan–Cooling included)]

*Unit [mm]



L7S Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series


Options

L7 SERIES SYSTEM

External Dimensions of L7NHB Drive

■ **L7NHB150U** [Weight : 15.5kg(Fan-Cooling included)]

* Unit [mm]



Indexer Function Type

I L7P Series



■ Servo Drive Designation

L7	P	A	004	U	AA
Model Name Servo Series	Communication Stand I/O & Index Type	Input Power Supply A : 200VAC B : 400VAC	Capacity 001 : 100W 002 : 200W 004 : 400W 008 : 750W 010 : 1.0kW 020 : 2.0kW 035 : 3.5kW	Encoder Type U : Universal	Option Exclusive Option Code

* Range
 · 200V : 0.1kW~15kW
 · 400V : 1.0kW~15kW

L7S Series
L7N Series
L7NH Series

L7P Series

S Series
F SeriesMDM Series
PEGASUS Series

Options

L7 SERIES SYSTEM

L7P Series

Characteristic

● Providing Program Function built-in single axis position determination module

- Supporting position control mode by pulse input
- Position control mode
- Possible to use without upper controller
- Modbus RTU Protocol (RS-422)

● Improved Control Performance


- Improved Control bandwidth
- Providing 4-step Notch-Filter
- Vibration control by Real-time FFT
- Real-time gain tuning function

● Support various motor and Encoder drive

- Supporting Rotary, DD and Motor drive (supporting 3rd party motor)
- Quadrature, BiSS-C, Tamagawa serial abs, EnDat 2.2

Identifying the Part of L7P Drive

[L7P]



- ① Display
- ② Dip Switch
- ③ Charge Lamp
- ④ Main Power Connector (L1, L2, L3)
- ⑤ DC Reactor Connector (PO, PI) Short-Circuit When Not used
- ⑥ Regenerative Resistor Connector (B+, B, BI)
 - Short-Circuit B, BI terminals when standard type
 - Use B+, B terminals when using external resistor
- ⑦ Control Power connector (C1, C2)
- ⑧ Motor power connector (U, V, W)
- ⑨ Connector for analogue monitor
- ⑩ Switch for nod address setting
- ⑪ USB connector (USB)
- ⑫ RS-422 communication connector (In / Out)
- ⑬ Control signal connector (I/O)
- ⑭ Encoder Connector (ENCODER)
- ⑮ PE(Protective Earth)

L7PA Drive Combination Table

■ L7PA Incremental Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable	Power Cable			
					Quadrature Type	INC	For power	Power + Brake	Brake	
3,000	5,000	□40	SAR3A	L7PA001U	* 2,048 P/R	APCS-E□□□AS	APCS-P□□□GS	APCS-B□□□QS		
		□40	SAR5A	L7PA001U						
		□40	SA01A	L7PA001U						
		□40	SA015A	L7PA002U						
		□60	SB01A	L7PA002U						
		□60	SB02A	L7PA002U						
		□60	SB04A	L7PA004U						
		□80	SC04A	L7PA004U						
		□80	SC06A	L7PA008U						
		□80	SC08A	L7PA008U						
		□80	SC10A	L7PA010U						
		□130	SE09A	L7PA008U						
		□130	SE15A	L7PA020U						
		□130	SE22A	L7PA020U						
		□130	SE30A	L7PA035U						
2,000	3,000	□180	SF30A	L7PA035U	* 3,000 P/R	APCS-E□□□BS	APCS-P□□□HS	APCS-P□□□NB	APCS-B□□□QS	
		□180	SF50A	L7PA050U			APCS-P□□□IS	APCS-P□□□PB		
		□80	SC03D	L7PA004U			APCS-P□□□JS	APCS-P□□□LB		
		□80	SC05D	L7PA008U		APCS-E□□□BS	APCS-P□□□HS	APCS-P□□□NB		
		□80	SC06D	L7PA008U						
		□80	SC07D	L7PA008U						
		□130	SE06D	L7PA008U						
		□130	SE11D	L7PA010U						
		□130	SE16D	L7PA020U						
		□130	SE22D	L7PA020U						
		□180	SF22D	L7PA020U						
		□180	LF35D	L7PA035U						
		□180	SF55D	L7PA050U						
1,500	3,000	2,500	□180	SF75D	L7PA075U		APCS-P□□□JS	APCS-P□□□MS	APCS-P□□□SB	
		3,000	□220	SG22D	L7PA020U					
		3,000	□220	LG35D	L7PA035U					
		3,000	□220	SG55D	L7PA050U					
		2,500	□220	SG75D	L7PA075U					
		2,500	□220	SG110D	L7PA150U					
		3,000	□130	SE05G	L7PA008U					
		3,000	□130	SE09G	L7PA010U					
		3,000	□130	SE13G	L7PA020U					
		3,000	□130	SE17G	L7PA020U					
		3,000	□180	SF20G	L7PA035U					
		2,500	□180	SF44G	L7PA050U	APCS-E□□□BS	APCS-P□□□IS	APCS-P□□□PB		
		2,500	□180	SF60G	L7PA075U		APCS-P□□□JS	APCS-P□□□LB		
		2,000	□220	SF75G	L7PA150U		APCS-P□□□MS	APCS-P□□□PB		
		2,700	□180	LF30G	L7PA035U		APCS-P□□□IS	APCS-P□□□PB		
		3,000	□220	SG20G	L7PA020U		APCS-P□□□JS	APCS-P□□□VS		
		2,700	□220	LG30G	L7PA035U		APCS-P□□□VS	APCS-P□□□VS		
		2,500	□220	SG60G	L7PA075U		APCS-P□□□OS	APCS-P□□□OS		
		2,000	□220	SG85G	L7PA150U		APCS-P□□□BS	APCS-P□□□NB		
		2,000	□220	SG110G	L7PA150U					
		2,000	□220	SG150G	L7PA150U					
1,000	2,000	1,700	□130	SE03M	L7PA004U		APCS-P□□□BS	APCS-P□□□NB	APCS-P□□□SB	
		2,000	□130	SE06M	L7PA008U					
		2,000	□130	SE09M	L7PA010U					
		2,000	□130	SE12M	L7PA020U					
		2,000	□180	SF12M	L7PA020U					
		2,000	□180	SF20M	L7PA035U					
		1,700	□180	LF30M	L7PA035U					
		2,000	□180	SF44M	L7PA050U					
		2,000	□220	SG12M	L7PA020U					
		2,000	□220	SG20M	L7PA035U					
		1,700	□220	LG30M	L7PA035U					
		2,000	□220	SG44M	L7PA050U		APCS-P□□□BS	APCS-P□□□JS		
		2,000	□220	SG60M	L7PA075U					
3,000	3,500	□60	HB01A	L7PA002U	* 1,048 P/R	APCS-E□□□AS	APCS-P□□□GS	APCS-P□□□NB	APCS-P□□□SB	
		□60	HB02A	L7PA002U						
		□60	HB04A	L7PA004U						
		□130	HE09A	L7PA008U	* 2,048 P/R	APCS-E□□□BS	APCS-P□□□HS	APCS-P□□□PB		
		□130	HE15A	L7PA020U						
		□130	HE30A	L7PA050U						

L7 SERIES SYSTEM

L7PA Drive Combination Table

L7PA Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable		Power Cable		
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake
3,000	5,000	* 18Bit Serial Abs	□40	FALR5A	L7PA001U	APCS-E□□□□ES	APCS-E□□□□ES1	APCS-P□□□□LS	APCS-P□□□□QS	
			□40	FAL01A	L7PA001U					
			□40	FAL015A	L7PA004U					
			□60	FBL01A	L7PA001U					
			□60	FBL02A	L7PA002U					
			□60	FBL04A	L7PA004U					
			□80	FCL04A	L7PA004U					
			□80	FCL06A	L7PA008U					
			□80	FCL08A	L7PA008U					
			□80	FCL10A	L7PA010U					
			□60	FB01A	L7PA001U					
			□60	FB02A	L7PA002U					
			□60	FB04A	L7PA004U					
			□80	FC04A	L7PA004U					
			□80	FC06A	L7PA008U					
			□80	FC08A	L7PA008U					
			□80	FC10A	L7PA010U					
			□130	FE09A	L7PA010U					
			□130	FE15A	L7PA020U					
			□130	FE22A	L7PA020U					
			□130	FE30A	L7PA035U					
			□180	FF30A	L7PA035U					
			□180	FF50A	L7PA050U					
2,000	3,000	* 19Bit Serial Abs	□80	FCL03D	L7PA004U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□HS	APCS-P□□□□NB	APCS-P□□□□QS
			□80	FCL05D	L7PA008U					
			□80	FCL06D	L7PA008U					
			□80	FCL07D	L7PA008U					
			□80	FC03D	L7PA004U					
			□80	FC05D	L7PA008U					
			□80	FC06D	L7PA008U					
			□80	FC07D	L7PA008U					
			□130	FE06D	L7PA008U					
			□130	FE11D	L7PA010U					
			□130	FE16D	L7PA020U					
			□130	FE22D	L7PA020U					
			□180	FF22D	L7PA020U					
			□180	FF35D	L7PA035U					
			□180	FF55D	L7PA050U					
			□180	FF75D	L7PA075U					
1,500	3,000	* 19Bit Serial Abs	□220	FG22D	L7PA020U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□HS	APCS-P□□□□NB	APCS-P□□□□QS
			□220	FG35D	L7PA035U					
			□220	FG55D	L7PA050U					
			□220	FG75D	L7PA075U					
			□220	FG11D	L7PA150U					
			□130	FE05G	L7PA008U					
			□130	FE09G	L7PA010U					
			□130	FE13G	L7PA020U					
			□130	FE17G	L7PA020U					
			□180	FF20G	L7PA020U					
			□180	FF30G	L7PA035U					
			□180	FF44G	L7PA050U					
			□180	FF60G	L7PA075U					
			□220	FG20G	L7PA020U					
			□220	FG30G	L7PA035U					
			□220	FG44G	L7PA050U					
1,000	2,000	* 19Bit Serial Abs	□220	FG60G	L7PA075U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□HS	APCS-P□□□□NB	APCS-P□□□□QS
			□220	FG85G	L7PA150U					
			□220	FG11G	L7PA150U					
			□220	FG15G	L7PA150U					
			□130	FE03M	L7PA004U					
			□130	FE06M	L7PA008U					
			□130	FE09M	L7PA010U					
			□130	FE12M	L7PA020U					
			□180	FF12M	L7PA020U					
			□180	FF20M	L7PA020U					
1,700	2,000	* 19Bit Serial Abs	□180	FF30M	L7PA035U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□HS	APCS-P□□□□NB	APCS-P□□□□QS
			□180	FF44M	L7PA050U					
			□220	FG12M	L7PA020U					
			□220	FG20M	L7PA020U					
			□220	FG30M	L7PA035U					
			□220	FG44M	L7PA050U					
1,700	2,000	* 19Bit Serial Abs	□220	FG60M	L7PA075U	APCS-E□□□□DS	APCS-E□□□□DS1	APCS-P□□□□JS	APCS-P□□□□SB	APCS-P□□□□QS

L7PB Drive Combination Table

L7PB Incremental Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable	Power Cable		
					Quadrature Type	INC	For power	Power + Brake	Brake
3,000	5,000		□130	SEP09A	L7PB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP15A	L7PB020U		APCF-P□□□IS		
			□130	SEP22A	L7PB020U		APCF-P□□□JS		
			□130	SEP30A	L7PB035U		APCF-P□□□IS		
			□180	SFP30A	L7PB035U		APCF-P□□□JS		
			□180	SFP50A	L7PB050U		APCF-P□□□IS		
2,000	3,000		□130	SEP06D	L7PB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP11D	L7PB010U		APCF-P□□□IS		
			□130	SEP16D	L7PB020U		APCF-P□□□JS		
			□130	SEP22D	L7PB020U		APCF-P□□□IS		
			□180	SFP22D	L7PB020U		APCF-P□□□JS		
			□180	SFP35D	L7PB035U		APCF-P□□□IS		
			□180	SFP55D	L7PB050U		APCF-P□□□JS		
			□180	SFP75D	L7PB075U		APCF-P□□□IS		
			□220	SGP22D	L7PB020U		APCF-P□□□JS		
			□220	SGP35D	L7PB035U		APCF-P□□□MS	APCF-P□□□SB	
1,500	3,000		□180	SGP55D	L7PB050U	APCS-E□□□BS	APCF-P□□□JS		
			□220	SGP75D	L7PB075U		APCF-P□□□IS		
			□220	SGP10D	L7PB150U		APCF-P□□□JS		
			□130	SEP05G	L7PB010U		APCF-P□□□MS		
			□130	SEP09G	L7PB010U		APCF-P□□□HS	APCF-P□□□NB	
			□130	SEP13G	L7PB020U		APCF-P□□□IS		
			□130	SEP17G	L7PB020U		APCF-P□□□JS		
1,000	2,500		□180	SFP20G	L7PB020U	APCS-E□□□BS	APCF-P□□□MS		
			□180	SFP30G	L7PB050U		APCF-P□□□IS		
			□180	SFP44G	L7PB050U		APCF-P□□□JS		
			□180	SFP60G	L7PB075U		APCF-P□□□MS		
			□180	SFP75G	L7PB075U		APCF-P□□□IS	APCF-P□□□SB	
			□220	SGP20G	L7PB020U		APCF-P□□□JS		
			□220	SGP30G	L7PB050U		APCF-P□□□MS		
1,000	3,000		□220	SGP44G	L7PB050U	APCS-E□□□BS	APCF-P□□□IS		
			□220	SGP60G	L7PB075U		APCF-P□□□JS		
			□220	SGP85G	L7PB150U		APCF-P□□□MS		
			□220	SGP110G	L7PB150U		APCF-P□□□IS		
			□220	SGP150G	L7PB150U		APCF-P□□□JS		
	2,000		□130	SEP03M	L7PB010U	APCS-E□□□BS	APCF-P□□□MS	APCF-P□□□NB	
			□130	SEP06M	L7PB010U		APCF-P□□□IS		
			□130	SEP09M	L7PB010U		APCF-P□□□JS		
			□130	SEP12M	L7PB020U		APCF-P□□□IS		
			□180	SFP12M	L7PB020U		APCF-P□□□JS		
			□180	SFP20M	L7PB020U		APCF-P□□□MS		
			□180	SFP30M	L7PB035U		APCF-P□□□IS		
1,000	1,700		□180	SFP44M	L7PB050U	APCS-E□□□BS	APCF-P□□□JS	APCF-P□□□LB	
			□220	SGP12M	L7PB020U		APCF-P□□□IS		
			□220	SGP20M	L7PB020U		APCF-P□□□JS		
			□220	SGP30M	L7PB050U		APCF-P□□□MS		
			□220	SGP44M	L7PB050U		APCF-P□□□IS		
			□220	SGP60M	L7PB075U		APCF-P□□□JS		
	2,000		□220	SGP85M	L7PB150U		APCF-P□□□MS		

L7 SERIES SYSTEM

L7PB Drive Combination Table

■ L7PB Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable		Power Cable			
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake	Brake
3,000	5,000	□130	FEP09A	L7PB010U	* 19Bit Serial Abs	APCS-E□□□DS1	APCF-P□□□HS	APCF-P□□□NB	APCF-P□□□S	APCF-P□□□PB	APCF-P□□□JS
			FEP15A	L7PB020U							
			FEP22A	L7PB035U							
			FEP30A	L7PB035U							
			FFP30A	L7PB035U							
			FFP50A	L7PB050U							
2,000	3,000	□130	FEP06D	L7PB010U							
			FEP11D	L7PB010U							
			FEP16D	L7PB020U							
			FEP22D	L7PB020U							
			FFP22D	L7PB020U							
			FFP35D	L7PB035U							
1,500	2,500	□180	FFP55D	L7PB050U							
			FFP75D	L7PB075U							
			FGP22D	L7PB020U							
			FGP35D	L7PB035U							
			FGP55D	L7PB050U							
			FGP75D	L7PB075U							
1,000	2,000	□220	FEP10D	L7PB150U							
			FEP05G	L7PB010U							
			FEP09G	L7PB010U							
			FEP13G	L7PB020U							
			FEP17G	L7PB020U							
			FFP20G	L7PB020U							
1,000	2,000	□180	FFP30G	L7PB035U							
			FFP44G	L7PB050U							
			FFP60G	L7PB075U							
			FFP75G	L7PB075U							
			FGP20G	L7PB020U							
			FGP30G	L7PB035U							
1,000	2,000	□220	FGP44G	L7PB050U							
			FGP60G	L7PB075U							
			FGP85G	L7PB150U							
			FGP110G	L7PB150U							
			FGP150G	L7PB150U							
			FEP03M	L7PB010U							
1,000	2,000	□130	FEP06M	L7PB010U							
			FEP09M	L7PB010U							
			FEP12M	L7PB020U							
			FFP12M	L7PB020U							
			FFP20M	L7PB020U							
			FFP30M	L7PB035U							
1,000	2,000	□180	FFP44M	L7PB050U							
			FGP12M	L7PB020U							
			FGP20M	L7PB020U							
			FGP30M	L7PB050U							
			FGP44M	L7PB050U							
			FGP60M	L7PB075U							

L7PA Drive Product Features

Item	Type Name	L7PA001U	L7PA002U	L7PA004U	L7PA008U	L7PA010U	L7PA020U	L7PA035U	L7PA050U	L7PA075U	L7PA150U
Input Power	Main Power Supply	3-Phase AC 200~230[V](-15~10[%]), 50~60[Hz]									
	Control Power Supply	Single-Phase AC 200~230[V](-15~10[%]), 50~60[Hz]									
	Rated Current[A]	1.4	1.7	3.0	5.2	6.75	13.5	16.7	32	39.4	76
	Peak Current[A]	4.2	5.1	9.0	15.6	20.25	40.5	50.1	90.88	98.5	190
	Encoder Type	Quadrature(Incremental) BISS-B, BISS-C(Absolute, Incremental) Tamagawa Serial(Absolute, Incremental) EnDat 2.2									
Control Performance	Speed Control Range	Maximum 1: 5000									
	Frequency Response	Maximum 1 [kHz] or above (When using 19bit Serial Encoder)									
	Speed Variation Ratio	$\pm 0.01 [\%]$ or lower [when load changes between 0 and 100%] $\pm 0.1 [\%]$ or lower [temperature 25 $\pm 10^\circ\text{C}$]									
	Accel/Decel Time	Straight or S-curveacceleration/deceleration (0~10,000[ms], 0~1,000[ms] Unitconfigurable)									
	Input Frequency	1[Mpps], line drive / 200[kpps], Open Collectorpr									
	Input Pulse Type	Symbol + Pulse Series, CW+CCW, A/B Phase									
RS422 Communication Specifications	Communication Specifications	ANSI/TIA/EIA-422 StandardSpecficiations									
	Communication Protocol	MODBUS-RTU									
	Connector	RJ45 x 2									
	Synchro Method	Asynchronous									
	Transmission Speed	9600 /19200/38400/57600 [bps] Can be configured at [0x3002]									
	Transmission Distance	Maximum 200 [m]									
Input/Output Signal	Power Consumption	100[mA] Less than									
	Terminating Resistance	Dip S/W(On/Off), Built-In 120Ω									
	Digital Input	Input voltage range: DC 12[V] ~ DC 24[V] Total 16 input channel (allocatable) 32 function inputs can be selectively allocated (*SV_ON, *POT, *NOT, *A-RST, *START, *STOP, *REGT, *EMG, *HOME, *HSTART, *ISEL0, *ISEL1, *ISEL2, *ISEL3, *ISEL4, *ISEL5, PCON, GAIN2, P_CL, N_CL, MODE, PAUSE, ABSRQ, JSTART, JDIF, PCLR, AOVR, SPD1/LVSF1, SPD2/LVSF2, SPD3, PROBE1, PROBE2) * Basic allocationsignal.									
	Digital Output	Use rating: DC 24[V] $\pm 10\%$, 120[mA] Total 8 input channel (allocatable) 19 function inputs can be selectively allocated (*ALARM \pm , *READY \pm , *BRAKE \pm , *INPOS1 \pm , *ORG \pm , *EOS \pm , *TGON \pm , *TLMT \pm , VLMT \pm , INSPD \pm , ZSPD \pm , WARN \pm , INPOS2 \pm , IOUT0 \pm , IOUT1 \pm , IOUT2 \pm IOUT3 \pm , IOUT4 \pm , IOUT5 \pm) * Standard Allocationsignal									
	Analog input	Total 2 channels analogspeedoverrideinput(-10[V] ~ +10[V]) analogtorquecommand input(-10[V] ~ +10[V])									
	Analog output	Total 2 channels 15 function inputs can be selectively allocated									
USB Communciation	Protection	Firmware download, parametersetting, tuning, auxiliary function,parametercopy									
	Communication Specifications	Complies with USB 2.0 Full Speed Specifications									
	Connection Device	PC or USB storage media									
Built-in functions	Dynamic Braking	Standard built-in(activated by servoalarm or servo OFF)									
	Regenerative Braking	Built-in, external brake attachable									
	Display	7 Segment(5 DIGIT)									
	Setting Function	Drive node address can be set using rotary switch									
	Additional Function	Gaintuning, alarm history, JOG operation, origin search									
	Protective Function	Excessie current, overload, excessive current limit, overheating, excessive voltage, low voltage, excessive speed, encoder fail, position following fail, current sensing fail									
Environment	Temperature	0 ~ 50[°C] / -20 ~ 65 °C									
	Humidity	Below 90[%]RH(avoid dew-condensation)									
	Environment	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.									

L7S Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series

Options

L7 SERIES SYSTEM


L7PB Drive Product Features

Item	Type Name	L7PB010U	L7PB020U	L7PB035U	L7PB050U	L7PB075U	L7PB150U
Input Power	Main Power Supply	3 Phase AC380 ~ 480[V](-15 ~ +10[%]), 50 ~ 60[Hz]					
	Control Power Supply	Single Phase AC380 ~ 480[V](-15 ~ +10[%]), 50 ~ 60[Hz]					
	Rated Current[A]	3.7	8	10.1	17.5	22.8	39
	Peak Current[A]	11.1	24	30.3	47.25	57	97.5
	Encoder Type	Universal Encoder Feedback Quadrature(Incremental) BISS-B, BISS-C(Absolute, Incremental) Tamagawa Serial(Absolute, Incremental) EnDat 2.2					
Control Performance	Speed Control Range	Maximum 1: 5000					
	Frequency Response	Maximum 1 [kHz] or above (When using 19bit Serial Encoder)					
	Speed Variation Ratio	±0.01 [%] or lower [when load changes between 0 and 100%] ±0.1[%] or lower [temperature 25 ±10°C]					
	Accel/Decel Time	Straight or S-curve acceleration/deceleration (0~10,000 [ms], possible to be set by one [ms] unit)					
	Input Frequency	1[Mpps], Line Driver / 200[kpps], Open Collector					
	Input Pulse Type	Symbol + Pulse Series, CW+CCW, A/B Phase					
RS422 Communication Specifications	Communication Specifications	ANSI/TIA/EIA-422 StandardSpecficiations					
	Communication Protocol	MODBUS-RTU					
	Connector	RJ45 x 2					
	Synchro Method	Asynchronous					
	Transmission Speed	9600 /19200/38400/57600 [bps] Can be configured at [0x3002]					
	Transmission Distance	Maximum 200 [m]					
	Power Consumption	100[mA] Less than					
	Terminating Resistance	Dip S/W(On/Off), Built-In 120Ω					
Input/Output Signal	Digital Input	Input voltage range: DC 12[V] ~ DC 24[V] Total 16 input channel (allocatable) 30 function inputs can be selectively allocated *SV_ON, *POT, *NOT, *A-RST, *START, *STOP, *REGT, *EMG, *HOME, *HSTART, *SEL0, *SEL1, *SEL2, *SEL3, *SEL4, *SEL5, *PCON, *GAIN2, *P_CL, *N_CL, *PAUSE, *ABS_RQ, *JSTART, *JDIR, *PCLR, *AOVR, *SPD1/LVFS1, *SPD2/LVFS2, *SPD3, *MODE주) * Basic allocationsignal.					
	Digital Output	Use rating: DC 24[V] ±10%, 120[mA] Total 8 input channel (allocatable) 19 function inputs can be selectively allocated *ALARM±, *READY±, *BRAKE±, *INPOS1±, *ORG±, *EOS±, *TGON±, *TLMT±, VLMT±, INSPD±, ZSPD±, WARN±, INPOS2±, IOUT0±, IOUT1±, IOUT2± IOUT3±, IOUT4±, IOUT5± * Basic allocationsignal.					
Analog Input/output	Analog input	Total 2 channels analog speed override input(-10[V] ~ +10[V]) analog torque command input(-10[V] ~ +10[V])					
	Analog output	Total 2 channels 15 function inputs can be selectively allocated					
USB Communication	Protection	Firmware download, parameter setting, tuning, auxiliary function, parameter copy					
	Communication Specifications	Complies with USB 2.0 Full Speed Specifications					
	Connection Device	PC or USB storage media					
Built-in functions	Dynamic Braking	Standard built-in(activated by servo alarm or servo OFF)					
	Regenerative Braking	Built-in, external brake attachable					
	Display	7 Segment(5 DIGIT)					
	Setting Function	Drive node address can be set using rotary switch					
	Additional Function	Gain tuning, alarm history, JOG operation, origin search					
	Protective Function	Excessive current, overload, excessive current limit, overheating, excessive voltage, low voltage, excessive speed, encoder fail, position following fail, current sensing fail					
Environment	Temperature	0 ~ 50 [°C] / -20 ~ 70 [°C]					
	Humidity	Below 80[%]RH(avoid dew-condensation) / Below 90[%]RH(avoid dew-condensation)					
	Environment	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.					

External Dimensions of L7P Drive


L7PA001U ~ L7PA004U [Weight : 1.0kg]

* Unit [mm]



L7PA008U / L7PA010U [Weight : 1.5kg(Fan-Cooling included)]

* Unit [mm]




L7 SERIES SYSTEM

External Dimensions of L7PA Drive


L7PA020U / L7PA035U [Weight : 2.5kg(Fan–Cooling included)]

* Unit [mm]



L7PA050U [Weight : 5.5kg(Fan–Cooling included)]


* Unit [mm]



External Dimensions of L7PA Drive


L7PA075U [Weight : 8.5kg(Fan–Cooling included)]

* Unit [mm]



L7PA150U [Weight : 16.2kg(Fan–Cooling included)]

* Unit [mm]



L7S Series

L7N Series

L7P Series

S Series

F Series

MDM Series

Options


PEGASUS Series

L7 SERIES SYSTEM

External Dimensions of L7PB Drive


L7PB010U [Weight : 1.5kg(Fan-Cooling included)]

* Unit [mm]



L7PB020U / L7PB035U [Weight : 2.5kg(Fan-Cooling included)]


* Unit [mm]



External Dimensions of L7PB Drive


L7PB050U [Weight : 5.5kg(Fan–Cooling included)]

*Unit [mm]



L7PB075U [Weight : 8.5kg(Fan–Cooling included)]

*Unit [mm]




L7 SERIES SYSTEM

External Dimensions of L7PB Drive

■ L7PB150U [Weight : 15.5kg(Fan-Cooling included)]

* Unit [mm]



Contents

Servo Motor

S Series

Solid/Hollow Type Rotating Servo Motor

- Servo Motor Designation 60
- Product Feature 61
- External Dimensions 67



F Series

Flat Type Rotating Servo Motor

- Servo Motor Designation 72
- Product Feature 73
- External Dimensions 83



MDM Series

Direct-Drive Motor


- Servo Motor Designation 87
- Product Feature 88
- External Dimensions 93




L7 SERIES SYSTEM

Solid/Hollow Type Rotating Servo Motor

I S Series



Servo Motor Designation



S Series Motor Characteristics (200V)

Motor Specifications [Rated 3000r/min]

Servo Motor (APM-□□□□)		SAR5A	SA01A	SA015A	SB01A	SB02A	SB04A	SC04A	SC06A	SC08A	SC10A				
Applicable Drive (L7□A□□)		L7□A001		L7□A002		L7□A004		L7□A008		L7□A010					
Flange Size(□)		□40				□60				□80					
Rated Output	[kW]	0.05	0.1	0.15	0.1	0.2	0.4	0.4	0.6	0.8	1				
Rated Torque	[N · m]	0.16	0.32	0.48	0.32	0.64	1.27	1.27	1.91	2.55	3.19				
	[kgf · cm]	1.62	3.25	4.87	3.25	6.49	12.99	12.99	19.49	25.98	32.48				
Instantaneous Maximum Torque	[N · m]	0.48	0.96	1.43	0.96	1.91	3.82	3.82	5.73	7.64	9.56				
	[kgf · cm]	4.87	9.74	14.62	9.74	19.48	38.96	38.96	58.47	77.95	97.43				
Rated Current	[A]	1.2	1.38	1.73	1.65	1.63	2.89	2.89	3.58	4.83	5.37				
Max. Current	[A]	3.6	4.14	5.19	4.95	4.89	8.67	8.46	10.74	14.49	16.11				
Rated Speed	[r/min]	3000													
Max. Speed	[r/min]	5000													
Inertia	[kg · m ² × 10 ⁻⁴]	0.02	0.05	0.06	0.11	0.18	0.32	0.67	1.09	1.51	1.93				
	[gf · cm × s ²]	0.02	0.05	0.07	0.12	0.19	0.33	0.69	1.11	1.54	1.97				
Allowable Load Inertia Ratio	30 times of motor inertia			20 times of motor inertia			15 times of motor inertia								
Rated Power Rate	[kW/s]	10.55	23.78	35.34	8.89	22.26	50.49	24.05	33.39	43.02	52.57				
Speed/Position Detector	Standard(Note1)	Quad. Type Incremental 2048[P/R]				Quad. Type Incremental 3000[P/R]									
	Option	Serial Type 18[Bit]				Serial Type 19[Bit]									
Specifications & Features	Structure	Fully closed · Self cooling IP55 Note1)						Fully closed · Self cooling IP65 Note1)							
	Rated Time	Continuous													
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]													
	Ambient Humidity	20 ~ 80[%] (avoid dew-condensation)													
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.													
	E/V	Elevation/vibration 49[m/s ²](5G)													
Weight	[kg]	0.38	0.5	0.7	0.82	1.08	1.58	1.88	2.52	3.15	3.8				

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked

It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics



L7 SERIES SYSTEM

S Series Motor Characteristics (200V)


Motor Specifications [Rated 3000r/min]

Servo Motor (APM-□□□□)	SE09A	SE15A	SE22A	SE30A	SF30A	SF50A	HB01A	HB02A	HB04A	HE09A	HE15A	HE30A						
Applicable Drive (L7□A□□□)	L7□A008	L7□A020		L7□A035	L7□A050		L7□A002	L7□A004	L7□A008	L7□A020	L7□A050							
Flange Size(□)	□130				□180				□60									
Rated Output [kW]	0.9	1.5	2.2	3	3	5	0.1	0.2	0.4	0.9	1.5	3						
Rated Torque [N·m]	2.86	4.77	7	9.55	9.55	15.91	0.32	0.64	1.27	2.86	4.77	9.55						
[kgf·cm]	29.23	48.72	71.45	97.43	97.43	162.38	3.25	6.49	12.99	29.23	48.72	97.43						
Instantaneous Maximum Torque [N·m]	8.59	14.32	21.01	28.64	28.64	47.74	0.96	1.91	3.82	8.59	14.32	28.64						
Maximum Torque [kgf·cm]	87.69	146.15	214.35	292.29	292.29	487.15	9.74	19.48	38.96	87.69	146.15	292.29						
Rated Current [A]	4.95	8.23	11.98	17.16	16.7	27.4	1.65	1.63	2.89	4.95	8.23	17.16						
Max. Current [A]	14.85	24.69	35.94	51.48	50.1	82.2	4.95	4.89	8.67	14.85	24.69	51.48						
Rated Speed [r/min]	3000																	
Max. Speed [r/min]	5000						3500											
Inertia [$\text{kg} \cdot \text{m}^2 \times 10^{-4}$]	6.66	12	17.34	22.68	30.74	52.13	0.27	0.33	0.46	19.56	22.27	31.81						
[$\text{gf} \cdot \text{cm} \times \text{s}^2$]	6.8	12.24	17.69	23.14	31.37	53.19	0.27	0.34	0.47	19.96	22.72	32.46						
Allowable Load Inertia Ratio	10 times of motor inertia				5 times of motor inertia				20 times of motor inertia									
Rated Power Rate [kW/s]	12.32	18.99	28.28	40.20	29.66	48.58	3.34	11.98	34.47	4.10	10.01	22.03						
Speed/Position Detector	Standard(Note1)	Quad, Type Incremental 3000[P/R]						Quad, Type Incremental 1024[P/R]										
Option	Serial Type 19[Bit]																	
Specifications & Features	Structure	Fully closed · Self cooling IP65 Note1)						Fully closed · Self cooling IP55 Note1)										
Rated Time	Continuous																	
Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]																	
Ambient Humidity	90[%]RH Below (avoid dew-condensation)																	
Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,																	
E/V	Elevation/vibration 49[m/s ²](5G)																	
Weight [kg]	5.5	7.5	9.7	11.8	12.4	17.7	0.9	1.2	1.7	5.8	7.4							

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics



S Series Motor Characteristics (200V)


■ Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)		SC03D	SC05D	SC06D	SC07D	SE06D	SE11D	SE16D	SE22D
Applicable Drive (L7□A□□)		L7□A004	L7□A008			L7□A010	L7□A020		
Flange Size(□)		□80				□130			
Rated Output	[kW]	0.3	0.45	0.55	0.65	0.6	1.1	1.6	2.2
Rated Torque	[N · m]	1.43	2.15	2.63	3.1	2.86	5.25	7.64	10.5
	[kgf · cm]	14.61	21.92	26.79	31.66	29.23	53.59	77.94	107.17
Instantaneous Maximum Torque	[N · m]	4.3	6.45	7.88	9.31	8.59	15.75	22.92	31.51
	[kgf · cm]	43.84	65.77	80.38	94.99	87.69	160.76	233.83	321.52
Rated Current	[A]	2.59	3.23	3.82	4.42	3.97	6.28	9.23	12.37
Max. Current	[A]	7.77	9.69	11.46	13.26	11.91	18.84	27.69	37.11
Rated Speed	[r/min]	2000							
Max. Speed	[r/min]	3000							
Inertia	[kg · m ² × 10 ⁻⁴]	0.67	1.09	1.51	1.93	6.66	12	17.34	22.68
	[gf · cm × s ²]	0.69	1.11	1.54	1.97	6.8	12.24	17.69	23.14
Allowable Load Inertia Ratio		15 times of motor inertia				10 times of motor inertia			
Rated Power Rate	[kW/s]	30.43	42.27	45.69	49.97	12.32	22.98	33.65	48.64
Speed/Position Detector	Standard(Note1)	Quande, Type Incremental 3000[P/R]							
	Option	Serial Type 19[Bit]							
Specifications & Features	Structure	Fully closed · Self cooling IP65 Note1)							
	Rated Time	Continuous							
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]							
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)							
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.							
	E/V	Elevation/vibration 49[m/s ²](5G)							
Weight	[kg]	1.9	2.5	3.2	3.9	5.5	7.5	9.7	11.8

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked

It can be satisfied protection grade when you use private cable only.

■ Speed-Torque Characteristics



L7 SERIES SYSTEM

S Series Motor Characteristics (200V)

Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)		SF22D	LF35D	SF55D	SF75D	SG22D	LG35D	SG55D	SG75D	SG110D						
Applicable Drive (L7□A□□)		L7□A020	L7□A035	L7□A050	L7□A075	L7□A020	L7□A035	L7□A050	L7□A075	L7□A150						
Flange Size(□)		□180					□220									
Rated Output	[kW]	2,2	3,5	5,5	7,5	2,2	3,5	5,5	7,5	11						
Rated Torque	[N · m]	10,5	16,71	26,26	35,81	10,5	16,71	26,26	35,81	52,5						
	[kgf · cm]	107,17	170,5	267,93	365,36	107,2	170,52	267,9	365,4	535,9						
Instantaneous Maximum Torque	[N · m]	31,51	50,13	78,77	89,51	31,51	50,13	78,77	89,51	157,55						
	[kgf · cm]	321,52	511,51	803,8	913,41	321,52	511,51	803,8	913,4	1,607,60						
Rated Current	[A]	13,5	15,85	30,25	34,6	12,3	16,05	30,25	35,49	51,39						
Max. Current	[A]	40,5	47,55	90,75	86,5	36,9	48,15	90,75	88,73	154,17						
Rated Speed	[r/min]	2000					2500									
Max. Speed	[r/min]	3000			2500	3000			2500							
Inertia	[kg · m ² × 10 ⁻⁴]	30,74	52,13	83,6	121,35	51,42	80,35	132,41	172,91	291,36						
	[gf · cm × s ²]	31,35	53,16	85,31	123,74	52,47	81,99	135,11	176,44	297,31						
Allowable Load Inertia Ratio																
Rated Power Rate	[kW/s]	35,88	53,56	82,56	105,75	21,45	34,75	52,07	74,15	94,65						
Speed/Position Detector	Standard(Note1)	Quad. Type Incremental 3000[P/R]					Serial Type 19[Bit]									
	Option															
Specifications & Features	Structure	Fully closed · Self cooling IP65 Note1)														
	Rated Time	Continuous														
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]														
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)														
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.														
	E/V	Elevation/vibration 49[m/s ²](5G)														
Weight	[kg]	12,4	17,7	26,3	35,6	17	22	30,8	37,5	66,2						

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.
It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics



S Series Motor Characteristics (200V)


Motor Specifications [Rated 1500r/min]

Servo Motor (APM-□□□□)		SE05G	SE09G	SE13G	SE17G	SF20G	LF30G	SF44G	SF60G	SF75G	SG20G	LG30G	SG44G	SG60G	SG85G	SG110G	SG150G
Applicable Drive (L7□A□□)		L7□A008	L7□A010	L7□A20		L7□A035	L7□A050	L7□A075	L7□A150	L7□A20	L7□A035	L7□A050	L7□A075	L7□A150	L7□A150	L7□A150	L7□A150
Flange Size(□)		□130							□180							□220	
Rated Output	[kW]	0.45	0.85	1.3	1.7	1.8	2.9	4.4	6	7.5	1.8	2.9	4.4	6	8.5	11	15
Rated Torque	[N · m]	2.86	5.41	8.28	10.82	11.46	18.46	28.01	38.19	47.74	11.46	18.46	28.01	38.19	54.11	69.99	95.45
	[kgf · cm]	29.23	55.21	84.44	110.42	116.92	188.37	285.8	389.7	497.2	116.92	188.37	285.8	389.7	552.1	714.2	974
Instantaneous Maximum Torque	[N · m]	8.59	16.23	24.83	32.46	34.37	55.38	78.43	95.48	119.35	34.47	55.38	78.43	95.48	162.32	209.97	238.63
	[kgf · cm]	87.69	165.63	253.32	331.26	350.75	565.1	800.35	974.3	1,217.90	350.8	565.1	800.35	974.3	1,656.30	2,142.60	2,435
Rated Current	[A]	3.97	6.47	10	12.75	14.7	15.92	31.75	38	45.6	13.1	16.19	31.5	38	52.94	59.3	75.6
Max. Current	[A]	11.91	19.41	30	38.25	44.1	47.64	88.9	91.75	114	39.3	48.57	88.9	102	158.82	177.9	189
Rated Speed	[r/min]	1500															
Max. Speed	[r/min]	3000				3000	2700	3000	2500	2500	3000	2700	3000	2500	2500	2000	2000
Inertia	[kg · m ² × 10 ⁻⁴]	6.66	12	17.34	22.68	30.74	52.13	83.6	121.35	143.82	51.42	80.35	132.41	172.91	291.36	291.36	424.57
	[gf · cm × s ²]	6.8	12.24	17.69	23.14	31.37	53.19	85.31	123.83	146.76	52.47	81.99	135.11	176.44	297.31	297.31	416.08
Allowable Load Inertia Ratio		10 times of motor inertia							5 times of motor inertia								
Rated Power Rate	[kW/s]	12.32	24.4	39.49	51.63	42.71	65.37	93.83	120.21	158.47	25.53	42.41	59.24	84.36	100.48	168.27	223.44
Speed/Position Detector	Standard(Note1)	Quad. Type Incremental 3000[P/R]															
	Option	Serial Type 19[Bit]															
Specifications & Features	Structure	Fully closed · Self cooling IP65 Note1															
	Rated Time	Continuous															
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]															
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)															
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.															
	E/V	Elevation/vibration 49[m/s ²](5G)															
Weight	[kg]	5.5	7.5	9.7	11.8	12.4	17.7	26.3	35.6	39.4	17	22	30.8	37.52	66.2	66.3	92.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked

It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics



L7 SERIES SYSTEM

S Series Motor Characteristics (200V)

Motor Specifications [Rated 1000r/min]

Servo Motor (APM-□□□□)		SE03M	SE06M	SE09M	SE12M	SF12M	SF20M	LF30M	SF44M	SG12M	SG20M	LG30M	SG44M	SG60M
Applicable Drive (L7□A□□□)		L7□A004	L7□A008	L7□A010	L7□A020		L7□A035		L7□A050	L7□A020	L7□A035	L7□A050	L7□A075	
Flange Size(□)		□130				□180				□220				
Rated Output	[kW]	0.3	0.6	0.9	1.2	1.2	2	3	4.4	1.2	2	3	4.4	6
Rated Torque	[N · m]	2.86	5.73	8.59	11.46	11.46	19.1	28.64	42.01	11.46	19.1	28.64	42.01	57.29
	[kgf · cm]	29.23	58.46	87.69	116.92	116.92	194.86	292.29	428.69	116.92	194.86	292.29	428.69	584.6
Instantaneous Maximum Torque	[N · m]	8.59	17.19	25.78	34.37	34.37	57.29	85.93	117.63	34.37	57.29	85.93	117.63	171.87
	[kgf · cm]	87.69	175.3	263.06	350.75	350.75	584.58	876.88	1,200.26	350.75	584.58	876.88	1,200.26	1,753.80
Rated Current	[A]	2.51	4.15	5.78	7.63	8.4	14.4	15.6	31.24	8.87	15.02	16.42	31.83	38
Max. Current	[A]	7.53	12.45	17.34	22.89	25.2	43.2	46.8	87.47	26.61	45.06	49.26	89.12	98.3
Rated Speed	[r/min]	1000												
Max. Speed	[r/min]	2000					1700	2000					1700	2000
Inertia	[kg · m ² × 10 ⁻⁴]	6.66	12	17.34	22.68	30.74	52.13	83.6	121.35	51.42	80.35	132.41	172.91	291.36
	[gf · cm × s ²]	6.8	12.24	17.69	23.14	31.37	53.19	85.31	123.83	52.47	81.99	135.11	176.44	297.31
Allowable Load Inertia Ratio		10 times of motor inertia					5 times of motor inertia							
Rated Power Rate	[kW/s]	12.32	27.35	42.59	57.89	42.71	69.95	98.15	145.45	25.53	45.39	61.97	102.08	112.65
Speed/Position Detector	Standard(Note1)	Quad, Type Incremental 3000[P/R]												
	Option	Serial Type 19[Bit]												
Specifications & Features	Structure	Fully closed · Self cooling IP65 Note1												
	Rated Time	Continuous												
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]												
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)												
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.												
	E/V	Elevation/vibration 49[m/s ²](5G)												
Weight	[kg]	5.5	7.5	9.7	11.8	12.4	17.7	26.3	35.6	17	22	30.8	37.5	66.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked

It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics




External Dimensions of S Series Motor

SA Series

Plug Specifications

[Power]




Spec. : 172167-1
(Made by AMP)

Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W
4	Green	Ground

(Power Connector Pin Table)

[Brake]




Spec. : 172165-1
(Made by AMP)

Pin No.	Signal
1	BK+
2	BK-

(Brake Connector Pin Table)


[Encoder]



Spec. : 172171-1(Made by AMP)

Pin No.	Signal	Pin No.	Signal
1	A	9	V
2	\bar{A}	10	\bar{V}
3	B	11	W
4	\bar{B}	12	\bar{W}
5	Z	13	+5V
6	\bar{Z}	14	0V
7	U	15	SHIELD
8	\bar{U}		

(Parallel Encoder Connector Pin Table)

Note1) Use DC[24V] for brake input power supply.**Note2)** The () is for brake-attached type.**Note3)** For external dimensions for oil-sealed type. Please kindly contact us separately.**Note4)** Refer to page 24 for serial encoder pin table.

Model	External Dimensions				Key			Weight(kg)
	L	LM	LC	CB	T	W	U	
SAR3A	101.3(137.6)	76.3(112.6)	42.5(42.4)	66.3(102.3)	5	5	1.8	0.32(0.67)
SAR5A	108.3(144.6)	83.3(119.6)	49.5(49.4)	73.3(109.3)				0.38(0.73)
SA01A	125.3(161.6)	100.3(136.6)	66.5(66.4)	90.3(126.6)				0.5(0.85)
SA015A	145.3	120.3	86.5	110.3				0.7

SB Series

Plug Specifications

[Power]




Spec. : 172167-1
(Made by AMP)

Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W
4	Green	Ground

(Power Connector Pin Table)

[Brake]




Spec. : 172165-1
(Made by AMP)

Pin No.	Signal
1	BK+
2	BK-

(Brake Connector Pin Table)


[Encoder]



Spec. : 172171-1(Made by AMP)

Pin No.	Signal	Pin No.	Signal
1	A	9	V
2	\bar{A}	10	\bar{V}
3	B	11	W
4	\bar{B}	12	\bar{W}
5	Z	13	+5V
6	\bar{Z}	14	0V
7	U	15	SHIELD
8	\bar{U}		

(Parallel Encoder Connector Pin Table)

Note1) Use DC[24V] for brake input power supply.**Note2)** The () is for brake-attached type.**Note3)** For external dimensions for oil-sealed type. Please kindly contact us separately.**Note4)** Refer to page 24 for serial encoder pin table.

Model	External Dimensions				Key			Weight(kg)
	L	LM	LC	CB	T	W	U	
SB01A	122(162)	92(132)	52.5(52.3)	59.5(99.5)	5	5	3	0.82(1.4)
SB02A	136(176)	106(146)	66.5(66.3)	73.5(113.5)				1.08(1.66)
SB04A	164(204)	134(174)	94.5(94.3)	101.5(141.5)				1.58(2.16)


L7 SERIES SYSTEM

External Dimensions of S Series Motor

SC Series

Plug Specifications


[Power]



Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W
4	Green	Ground

(Power Connector Pin Table)


[Brake]



Pin No.	Signal
1	BK+
2	BK-

(Brake Connector Pin Table)

[Encoder]



Pin No.	Signal	Pin No.	Signal
1	A	9	V
2	Ā	10	V̄
3	B	11	W
4	B̄	12	W̄
5	Z	13	+5V
6	Z̄	14	0V
7	U	15	SHIELD
8	Ū		


(Spec. : 172171-1(Made by AMP)) (Parallel Encoder Connector Pin Table)

Note1) Use DC[24V] for brake input power supply.

Note2) The () is for brake-attached type.

Note3) For external dimensions for oil-sealed type. Please kindly contact us separately.

Note4) Refer to page 24 for serial encoder pin table.




Model	External Dimensions					Key	Weight(kg)
	L	LM	LC	CB	S		
SC04A, SC03D	158.5(199.8)	118.5(158.8)	79(78.8)	86(126.3)	14		1.88(2.92)
SC06A, SC05D	178.5(218.8)	138.5(178.8)	99(98.8)	106(146.3)	16	5	2.52(3.56)
SC08A, SC06D	198.5(238.8)	158.5(198.8)	119(118.8)	126(166.3)	16		3.15(4.22)
SC10A, SC07D	218.5(258.8)	178.5(218.8)	139(138.8)	146(186.3)	16	5	3.80(4.94)

SE Series

Plug Specifications

[Power]



Pin No.	Signal
A	U
B	V
C	W
D	Ground

(Spec. : MS3102A20-4P (Standard))

Pin No. Signal Pin No. Signal

A	U	D	Ground
B	V	E	BK+
C	W	F	BK-

(Spec. : MS3102A20-15P (Brake-attached type))

Pin No. Signal Pin No. Signal

A	A	M	V
B	Ā	N	V̄
C	B	P	W
D	B̄	R	W̄
E	Z	H	+5V
F	Z̄	G	0V
K	U	J	SHIELD
L	Ū		


(Spec. : MS3102A20-29P (Parallel Encoder Connector Pin Table))

Note1) Use DC[24V] for brake input power supply.

Note2) The () is for brake-attached type.

Note3) For external dimensions for oil-sealed type. Please kindly contact us separately.

Note4) Refer to page 24 for serial encoder pin table.




Model	External Dimensions					Key	Weight(kg)
	L	LM	LC	S	T		
SE09A, SE06D, SE05G, SE03M	201.3(239.3)	143.3(181.3)	93.8(93.6)	20.5	5	5	5.5(7.04)
SE15A, SE11D, SE09G, SE06M	225.3(263.3)	167.3(205.3)	117.8(117.6)	20.5	5	5	7.54(9.08)
SE22A, SE16D, SE13G, SE09M	249.3(287.3)	191.3(229.3)	141.8(141.6)	20.5	6	6	9.68(11.22)
SE30A, SE22D, SE17G, SE12M	273.3(311.3)	215.3(253.3)	165.8(165.6)	20.5	6	6	11.78(13.32)

External Dimensions of S Series Motor


SF, LF Series

Plug Specifications




Pin No.	Signal
A	U
B	V
C	W
D	Ground

Spec. : MS3102A22-22P
(Standard)




Pin No.	Signal	Pin No.	Signal
A	U	D	Ground
B	V	E	BK+
C	W	F	BK-

Spec. : MS3102A24-10P
(Brake-attached type)




Pin No.	Signal	Pin No.	Signal
A	A	M	V
B	A'	N	V
C	B	P	W
D	B'	R	W
E	Z	H	+5V
F	Z'	G	0V
K	U	J	SHIELD
L	U'		

Spec. : MS3102A20-29P
(Parallel Encoder Connector Pin Table)




SG, LG Series

Plug Specifications




Pin No.	Signal
A	U
B	V
C	W
D	Ground

Spec. : MS3102A22-22P
(Standard)




Pin No.	Signal
A	BK+
B	BK-
C	NC

Spec. : MS3102A14S-7P
(Brake-attached type)



Pin No.	Signal	Pin No.	Signal
A	A	M	V
B	A'	N	V
C	B	P	W
D	B'	R	W
E	Z	H	+5V
F	Z'	G	0V
K	U	J	SHIELD
L	U'		

Spec. : MS3102A20-29P
(Parallel Encoder Connector Pin Table)



Note1) In case of SG, use DC[90V] for brake input power supply.

Note2) The () is for brake-attached type.

Note3) For external dimensions for oil-sealed type. Please kindly contact us separately.

Note4) Refer to page 24 for serial encoder pin table.

Note5) Use MS3102A32-17 for SG60M Power connector.

Model	External Dimensions					Key					Weight(kg)	
	L	LM	LC	LR	S	QK	T	W	U			
SG22D, SG20G, SG12M	236.5(302.7)	171.5(237.7)	122(121.2)								16.95(30.76)	
LG35D, LG30G, SG20M	256.5(322.7)	191.5(257.7)	142(142.2)	65	19	56.4 (122.6)	35 ₀ -0.016	55	8	10	21.95(35.7)	
SG55D, SG44G, LG30M	292.5(358.7)	227.5(293.7)	178(177.2)								30.8(44.94)	
SG75D, SG60G, SG44M	320.5(386.7)	255.5(321.7)	206(205.2)								37.52(50.94)	
SG110D, SG85G, SG60M	418.5(484.7)	353.5(419.7)	304(303.2)	65	21	66 (132.2)	45 ₀ -0.015				66.2(82.6)	
SG110G, SG110G	469	354	304	115	21		42 ₀ -0.016	96	10	12	5	MS3102A22-22P
SG150G, SG150G	575	459	409	115	35	55 ₀ -0.016	96	10	16	6	66.3	
											MS3102A32-17P	
											92.2	


L7 SERIES SYSTEM

External Dimensions of S Series Motor

HB Series [Hollow Shaft type]

Plug Specifications |

[Power]




Spec. : 172167-1
(Made by AMP)

Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W
4	Green	Ground


(Power Connector Pin Table)

[Encoder]



Spec. : 172171-1(Made by AMP) (Parallel Encoder Connector Pin Table)


Pin No.	Signal	Pin No.	Signal
1	A	9	V
2	\bar{A}	10	\bar{V}
3	B	11	W
4	\bar{B}	12	\bar{W}
5	Z	13	+5V
6	\bar{Z}	14	0V
7	U	15	SHIELD
8	\bar{U}		



HE Series [Hollow Shaft type]

Plug Specifications |

[Power]




Spec. : MS3102A20-4P
(Standard)

Pin No.	Signal
A	U
B	V
C	W
D	Ground

(Power Connector Pin Table)


[Encoder]



Spec. : MS3102A20-29P

Pin No.	Signal	Pin No.	Signal
A	A	M	V
B	\bar{A}	N	\bar{V}
C	B	P	W
D	\bar{B}	R	\bar{W}
E	Z	H	+5V
F	\bar{Z}	G	0V
K	U	J	SHIELD
L	\bar{U}		

(Parallel Encoder Connector Pin Table)



Brake and Heat Sink Specification

Electric Brake Specifications

Applicable Motor Series	APM-SA,FAL	APM-SB,FB,FBL	APM-SC, FC,FCL	APM-SE,SEP,FE,FEP	APM-SF,SFP,FF,FFF	APM-SG,SGP,FG,FGP
Purpose	Maintenance					
Input voltage [V]	DC 24V	DC 24V	DC 24V	DC 24V	DC 24V	DC 90V
Static friction torque [N · m]	0.32	1.47	3.23	10.4	40	74
Capacity [W]	6	6.5	9	19.4	25	32
Coil resistance [Ω]	96	89	64	29.6	23	327
Rated current [A]	0.25	0.27	0.38	0.81	1.04	0.28
Braking mechanism	Spring brake					
Insulation grade	Grade F					

Note1) For the Electronic Brake that is attached to our Servo Motor, the same specific–ations are to be applied as per the series.

Note2) Do not use it for braking purpose because the electronic brake is only for maintaining the stopped condition.

Note3) The characteristics of electronic brake is measured at 20°C

Note4) Please make sure to always check the voltage specification on the motor because indicated brake specifications are subject to change.


Heat Sink Specifications

Type	Dimensions(mm)	Materials
AP04	250x250x6	Aluminum
AP06	250x250x6	
AP08	250x250x12	
AP13	350x350x20	
AP18	550x550x30	
AP22	650x650x35	

NOTE 1) The data on the product features is measured when those heat sinks are applied.

S Series Encoder Pin Map

SA, SB, SC Series



Plug Specification :
172169-1
(AMP)

Single Turn (N)		Multi Turn (M)	
Pin No.	Signal	Pin No.	Signal
1	MA	1	MA
2	MA	2	MA
3	SLO	3	SLO
4	SLO	4	SLO
5	—	5	VOD_B
6	—	6	GND_B
7	+5V	7	+5V
8	0V	8	0V
9	SHIELD	9	SHIELD

(Serial Encoder Connector Pin Table)

SE, SF, SG Series



17 Pole Plug
(MS3102A20-29P)

Single Turn (N)		Multi Turn (M)	
Pin No.	Signal	Pin No.	Signal
A	MA	M	—
B	MA	N	—
C	SLO	P	—
D	SLO	R	—
E	—	H	+5V
F	—	G	0V
K	—	J	MA
L	—	—	—

(Serial Encoder Connector Pin Table)


L7 SERIES SYSTEM

Flat Type Servo Motor

I F Series



Servo Motor Designation



F Series Motor Characteristics (200V)

Motor Specifications [Rated 3000r/min, 2000r/min]

Servo Motor (APM-□□□□)	FALR5A	FAL01A	FAL015A	FBL01A	FBL02A	FBL04A	FCL04A	FCL06A	FCL08A	FCL10A	FCL03D	FCL05D	FCL06D	FCL07D
Applicable Drive	L7□A001	L7□A002	L7□A001	L7□A002	L7□A004	L7□A004	L7□A004	L7□A008	L7□A010	L7□A004	L7□A008	L7□A008	L7□A008	L7□A008
Flange Size(□)	□40			□60							□80			
Rated Output	[kW]	0.05	0.1	0.15	0.1	0.2	0.4	0.4	0.6	0.75	1	0.3	0.45	0.55
Rated Torque	[N · m]	0.16	0.32	0.48	0.32	0.64	1.27	1.27	1.91	2.39	3.18	1.43	2.15	2.63
	[kgf · cm]	1.62	3.25	4.87	3.25	6.49	12.99	12.99	19.49	24.36	32.48	14.62	21.92	26.8
Instantaneous Maximum Torque	[N · m]	0.48	0.96	1.43	0.96	1.91	3.82	3.82	5.73	7.16	9.55	4.3	6.45	7.88
	[kgf · cm]	4.87	9.74	14.62	9.74	19.48	38.96	38.98	58.47	73.08	97.44	43.85	65.77	80.39
Rated Current	[A]	0.95	1.25	1.76	0.95	1.45	2.6	2.58	3.81	5.02	5.83	2.5	3.05	3.83
Max. Current	[A]	2.85	3.75	5.28	2.85	4.35	7.8	7.75	11.42	15.07	17.5	7.51	9.16	9.18
Rated Speed	[r/min]						3000						2000	
Max. Speed	[r/min]						5000						3000	
Inertia	[kg · m ² × 10 ⁻⁴]	0.023	0.042	0.063	0.091	0.147	0.248	0.53	0.897	1.264	1.632	0.53	0.897	1.264
	[gf · cm × s ²]	0.024	0.043	0.065	0.093	0.15	0.253	0.541	0.915	1.29	1.665	0.541	0.915	1.29
Allowable Load Inertia Ratio	30 times of motor inertia			20 times of motor inertia							15 times of motor inertia			
Rated Power Rate	[kW/s]	10.55	23.78	35.34	11.09	27.6	27.57	30.6	40.66	45.09	62.08	38.73	51.47	54.56
Speed/Position Detector	Standard(Note1)	Serial Multi-Turn Built-in Type (18bit)										Serial Multi-Turn Built-in Type (19bit)		
Option								X						
Specifications & Features	Structure											Fully closed · Self cooling IP67 Note1		
	Rated Time											Continuous		
	Ambient Temp											Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]		
	Ambient Humidity											90[%]RH Below (avoid dew-condensation)		
	Atmosphere											Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.		
	E/V											Elevation/vibration 49[m/s ²](5G)		
Weight	[kg]	0.31	0.45	0.61	0.56	0.74	1.06	1.52	2.14	2.68	3.3	1.26	2.12	2.66
														2.78

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked
It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics



L7 SERIES SYSTEM

F Series Motor Characteristics (200V)

Motor Specifications [Rated 3000r/min]

Servo Motor (APM-□□□□)	FB01A	FB02A	FB04A	FC04A	FC06A	FC08A	FC10A	FE09A	FE15A	FE22A	FE30A	FF30A	FF50A
Applicable Drive	L7□A001	L7□A002	L7□A004	L7□A004	L7□A008	L7□A010	L7□A010	L7□A020	L7□A035	L7□A035	L7□A050	L7□A050	L7□A050
Flange Size(□)	□60				□80				□130				□180
Rated Output [kW]	0.1	0.2	0.4	0.4	0.6	0.75	1	0.9	1.5	2.2	3	3	5
Rated Torque [N · m]	0.32	0.64	1.27	1.27	1.91	2.39	3.18	2.86	4.77	7	9.55	9.55	15.91
[kgf · cm]	3.25	6.5	12.99	13	19.5	24.36	32.5	29.2	48.7	71.4	97.4	97.4	162.3
Instantaneous Maximum Torque [N · m]	0.96	1.91	3.82	3.82	5.73	7.16	9.55	8.59	14.32	21.01	28.65	28.65	47.74
[kgf · cm]	9.74	19.49	38.98	38.98	58.47	73.08	97.44	87.7	146.1	214.3	292.2	292.3	487
Rated Current [A]	0.95	1.45	2.6	2.58	3.81	5.02	6.7	6.45	9.15	13.24	16.09	15.26	26.47
Max. Current [A]	2.86	4.35	7.79	7.75	11.42	15.07	20.09	19.35	27.45	39.72	48.27	45.78	79.41
Rated Speed [r/min]								3000					
Max. Speed [r/min]								5000					
Inertia [kg · m ² × 10 ⁻⁴]	0.09	0.15	0.25	0.5	0.88	1.25	1.62	5.66	10.18	14.62	19.04	27.96	46.56
[gf · cm × s ²]	0.09	0.15	0.25	0.51	0.89	1.27	1.65	5.77	10.39	14.92	19.43	28.53	47.51
Allowable Load Inertia Ratio	20 times of motor inertia				15 times of motor inertia			10 times of motor inertia			5 times of motor inertia		
Rated Power Rate [kW/s]	11.38	27.95	65.9	32.62	41.69	45.78	62.74	14.47	22.38	33.59	47.85	32.59	54.33
Speed/Position Detector	Standard(Note1)							Serial Type 19[bit]					
Option								X					
Specifications & Features	Structure							Fully closed · Self cooling IP65 Note1					
Rated Time								Continuous					
Ambient Temp								Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]					
Ambient Humidity								90[%]RH Below (avoid dew-condensation)					
Atmosphere								Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,					
E/V								Elevation/vibration 49[m/s ²](5G)					
Weight [kg]	0.7	0.9	1.3	1.6	2.2	2.7	3.8	5	6.7	8.5	10.1	12.5	17.4

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked
It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics




F Series Motor Characteristics (200V)

Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)	FC03D	FC05D	FC06D	FC07D	FE06D	FE11D	FE16D	FE22D
Applicable Drive	L7□A004			L7□A008		L7□A010		L7□A020
Flange Size(□)			□80			□130		
Rated Output [kW]	0.3	0.45	0.55	0.65	0.6	1.1	1.6	2.2
Rated Torque [N · m]	143	215	2.6	3.1	2.86	5.25	7.63	10.5
[kgf · cm]	14.6	21.9	26.8	31.7	29.2	53.6	77.9	107.1
Instantaneous Maximum Torque [N · m]	4.3	6.45	7.88	9.31	8.59	15.75	22.92	31.51
[kgf · cm]	43.8	65.8	80.4	95	87.7	160.7	233.8	321.4
Rated Current [A]	2.5	3.05	3.06	3.83	4.56	6.47	10.98	12.97
Max. Current [A]	7.51	9.16	9.18	11.5	13.68	19.41	32.94	38.91
Rated Speed [r/min]				2000				
Max. Speed [r/min]				3000				
Inertia [kg · m ² × 10 ⁻⁴]	0.5	0.88	1.25	1.62	5.66	10.18	14.62	19.04
[gf · cm × s ²]	0.51	0.89	1.27	1.65	5.77	10.39	14.92	19.43
Allowable Load Inertia Ratio			15 times of motor inertia			10 times of motor inertia		
Rated Power Rate [kW/s]	41.28	52.76	55.39	59.64	14.49	27.08	39.89	57.9
Speed/Position Detector	Standard(Note1)				Serial Multi-Turn Built-in Type(19bit)			
Option					X			
Structure					Fully closed · Self cooling IP65 Note1			
Rated Time					Continuous			
Ambient Temp				Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]				
Ambient Humidity				90[%]RH Below (avoid dew-condensation)				
Atmosphere				Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.				
E/V				Elevation/vibration 49[m/s ²](5G)				
Weight [kg]	1.6	2.2	2.7	3.8	5	6.7	8.5	10.1

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked
It can be satisfied protection grade when you use private cable only.

Speed–Torque Characteristics



L7 SERIES SYSTEM


F Series Motor Characteristics (200V)

■ Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)	FF22D	FF35D	FF55D	FF75D	FG22D	FG35D	FG55D	FG75D	FG110D
Applicable Drive	L7□A020	L7□A035	L7□A050	L7□A075	L7□A020	L7□A035	L7□A050	L7□A075	L7□A150
Flange Size(□)	□180				□220				
Rated Output [kW]	2.2	3.5	5.5	7.5	2.2	3.5	5.5	7.5	11
Rated Torque [N·m]	10.5	16.7	26.25	35.81	10.5	16.71	26.25	35.81	52.52
[kgf·cm]	107.1	170.4	267.8	365.4	107.1	170.4	267.8	365.4	535.9
Instantaneous Maximum Torque [N·m]	31.5	50.1	78.76	89.53	31.51	50.12	78.76	89.53	157.55
[kgf·cm]	321.3	511.4	803.4	913.5	321.3	511.3	803.4	913.5	1,607.60
Rated Current [A]	13.07	16.48	28.78	32.95	10.25	14.67	29.74	30.17	51.39
Max.Current [A]	39.21	49.44	86.34	82.37	30.75	44.01	89.22	75.43	154.17
Rated Speed [r/min]				2000					
Max. Speed [r/min]		3000		2500	3000	2700	3000	2500	2500
Inertia [kg·m ² ×10 ⁻⁴]	27.96	46.56	73.85	106.7	41.13	71.53	117.72	149.4	291.36
[gf·cm×s ²]	28.53	47.51	75.36	108.9	41.97	72.99	120.12	152.45	297.31
Allowable Load Inertia Ratio				5 times of motor inertia					
정격파워레이트 [kW/s]	39.43	59.89	93.27	120.15	26.78	38.99	58.51	85.83	94.65
Speed/Position Detector	Standard(Note1)				Serial Type 19[bit]				
Option					X				
Specifications & Features	Structure				Fully closed · Self cooling IP65 Note1)				
	Rated Time				Continuous				
	Ambient Temp				Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]				
	Ambient Humidity				90[%]RH Below (avoid dew-condensation)				
	Atmosphere				Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.				
	E/V				Elevation/vibration 49[m/s ²](5G)				
Weight [kg]	12.5	17.4	25.12	33.8	15.4	20.2	28.12	33.45	66.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.
It can be satisfied protection grade when you use private cable only.

■ Speed-Torque Characteristics




F Series Motor Characteristics (200V)

Motor Specifications [Rated 1500r/min]

Servo Motor (APM-□□□□)	FE05G	FE09G	FE13G	FE17G	FF20G	FF30G	FF44G	FF60G	FF75G	FG20G	FG30G	FG44G	FG60G	FG85G	FG110G	FG150G	
Applicable Drive	L7□A008	L7□A010	L7□A020	L7□A020	L7□A035	L7□A050	L7□A075	L7□A075	L7□A075	L7□A020	L7□A035	L7□A050	L7□A075	L7□A150	L7□A150	L7□A150	
Flange Size(□)	□130				□180				□220								
Rated Output	[kW]	0.45	0.85	1.3	1.7	1.8	2.9	4.4	6	7.5	1.8	2.9	4.4	6	8.5	11	15
Rated Torque	[N · m]	2.86	5.41	8.27	10.82	11.45	18.46	28	38.2	47.7	11.5	18.5	28	38.2	54.11	69.99	95.45
	[kgf · cm]	29.22	55.19	84.41	110.38	116.9	188.3	285.7	389.8	487.2	116.9	188.4	285.8	389.7	552.1	714.2	974
Instantaneous Maximum Torque	[N · m]	8.59	16.23	24.82	32.46	34.35	55.38	78.4	95.5	119.3	34.4	55.4	84	107.0	162.32	209.97	238.63
	[kgf · cm]	87.66	165.57	253.23	331.14	350.6	564.9	799.7	974.9	1,217.3	350.8	565.1	857.4	1,091.8	1,656.30	2,142.60	2,435
Rated Current	[A]	4.56	6.67	11.9	13.36	12.16	15.98	30.7	35.14	35.26	11.18	16.21	31.72	32.18	52.94	59.3	75.6
Max. Current	[A]	13.68	20.01	35.7	40.08	36.48	47.94	85.96	89.85	88.15	33.54	48.63	88.82	96.54	158.82	177.9	189
Rated Speed	[r/min]	1500															
Max. Speed	[r/min]	3000				3000	2700	3000	2500	2200	3000	2700	3000	2500	2500	2000	2000
Inertia	[kg · m ² × 10 ⁻⁴]	5.66	10.18	14.62	19.04	27.96	46.56	73.85	106.7	131.3	14.13	71.53	117.72	149.4	291.36	291.36	424.57
	[gf · cm × s ²]	5.77	10.39	14.92	19.43	28.53	47.51	75.36	108.9	134	41.97	72.99	120.12	152.45	297.31	297.31	416.08
Allowable Load Inertia Ratio		10 times of motor inertia				5 times of motor inertia											
Rated Power Rate	[kW/s]	14.49	28.74	46.81	61.46	46.92	73.14	106.15	136.73	173.63	31.91	47.66	66.64	97.63	100.48	168.27	223.44
Speed/Position Detector	Standard(Note1)	Serial Type 19 [bit]															
	Option	X															
Specifications & Features	Structure	Fully closed · Self cooling IP65 Note1															
	Rated Time	Continuous															
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]															
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)															
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.															
	E/V	Elevation/vibration 49[m/s ²](5G)															
Weight	[kg]	5.0	6.7	8.5	10.1	12.5	17.4	25.2	33.8	38.5	15.4	20.2	28	33.45	66.2	66.3	92.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked
It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics



L7S Series

L7NH Series

S Series

F Series

MDM Series

PEGASUS Series

Options

L7 SERIES SYSTEM

F Series Motor Characteristics (200V)

■ Motor Specifications [Rated 1000r/min]

Servo Motor (APM-□□□□)	FE03M	FE06M	FE09M	FE12M	FF12M	FF20M	FF30M	FF44M	FG12M	FG20M	FG30M	FG44M	FG60M	
Applicable Drive	L7□A004	L7□A008	L7□A010	L7□A020	L7□A020	L7□A035	L7□A050	L7□A020	L7□A035	L7□A050	L7□A075			
Flange Size(□)	□130				□180				□220					
Rated Output	[kW]	0.3	0.6	0.9	1.2	1.2	2	3	4.4	1.2	2	3	4.4	6
Rated Torque	[N · m]	2.86	5.72	8.59	11.46	11.46	19.09	28.64	42.02	11.5	19.1	28.6	42	57.29
	[kgf · cm]	29.22	58.4	87.7	116.9	116.9	194.8	292.2	428.7	116.9	194.9	292.3	428.7	584.6
Instantaneous Maximum Torque	[N · m]	8.59	17.18	25.77	34.22	34.38	57.29	85.94	105.1	34.4	57.3	85.9	126	171.87
	[kgf · cm]	87.66	175.3	262.9	349.1	350.7	584.4	876.6	1,072.4	350.8	584.6	876.9	1,286.1	1,753.80
Rated Current	[A]	2.73	4.56	6.18	10.67	11.01	12.96	16.58	30.6	11.28	13.1	15.52	27.26	38
Max. Current	[A]	8.19	13.68	18.54	32.01	33.03	38.88	49.74	85.68	33.84	39.3	46.56	81.78	102
Rated Speed	[r/min]									1000				
Max. Speed	[r/min]				2000					1700	2000	1700	2000	
Inertia	[kg · m ² × 10 ⁻⁴]	5.66	10.18	14.62	19.04	27.96	46.56	73.85	106.7	41.13	71.53	117.72	149.4	291.36
	[gf · cm × s ²]	5.77	10.39	14.92	19.43	28.53	47.51	75.36	108.9	41.97	72.99	120.12	152.45	297.31
Allowable Load Inertia Ratio					10 times of motor inertia						5 times of motor inertia			
Rated Power Rate	[kW/s]	14.49	32.22	50.48	68.91	46.94	78.27	111.04	165.38	31.91	51	69.7	118.14	112.65
Speed/Position Detector	Standard(Note1)						Serial Type 19 [bit]							
	Option						X							
Specifications & Features	Structure						Fully closed · Self cooling IP65 Note1							
	Rated Time						Continuous							
	Ambient Temp						Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]							
	Ambient Humidity						90[%]RH Below (avoid dew-condensation)							
	Atmosphere						Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.							
	E/V						Elevation/vibration 49[m/s ²](5G)							
Weight	[kg]	5	6.7	8.5	10.1	12.5	17.4	25.2	33.8	15.4	20.2	28	33.5	66.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.
It can be satisfied protection grade when you use private cable only.

■ Speed-Torque Characteristics









F Series Motor Characteristics (400V)

Motor Specifications [Rated 3000r/min]

Servo Motor (APM-□□□□)	FEP09A	FEP15A	FEP22A	FEP30A	FFP30A	FFP50A
Applicable Drive	L7□B010□	L7□B020□		L7□B035□		L7□B050□
Flange Size(□)			□130			□180
Rated Output	[kW]	0.9	1.5	2.2	3.0	5.0
Rated Torque	[N · m]	2.86	4.77	7.0	9.55	15.92
	[kgf · cm]	29.23	48.72	71.46	97.44	162.4
Instantaneous Maximum Torque	[N · m]	8.59	14.32	21.01	28.65	39.79
	[kgf · cm]	87.7	146.16	214.37	292.33	406.01
Rated Current	[A]	3.47	6.68	9.12	9.94	16.07
Max. Current	[A]	10.4	20.03	27.35	29.81	48.22
Rated Speed	[r/min]			3000		
Max. Speed	[r/min]			5000		
Inertia	[kg · m ² × 10 ⁻⁴]	5.659	10.179	14.619	19.04	27.96
	[gf · cm × s ²]	5.774	10.387	14.917	19.429	28.531
Allowable Load Inertia Ratio			10 times of motor inertia			5 times of motor inertia
Rated Power Rate	[kW/s]	14.5	22.4	33.55	47.89	32.61
Speed/Position Detector	Standard(Note1)			Serial Type 19 [bit]		
	Option			X		
	Structure			Fully closed · Self cooling IP65 Note1		
	Rated Time			Continuous		
Specifications & Features	Ambient Temp		Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]			
	Ambient Humidity		90[%]RH Below (avoid dew-condensation)			
	Atmosphere		Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.			
	E/V		Elevation/vibration 49[m/s ²](5G)			
Weight	[kg]	5.5	7.54	9.68	11.78	12.4
						17.7

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked
It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics



L7 SERIES SYSTEM


F Series Motor Characteristics (400V)

Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)	FEP06D	FEP11D	FEP16D	FEP22D	FFP22D	FFP35D	FFP55D	FFP75D	FGP22D	FGP35D	FGP55D	FGP75D	FGP110D
Applicable Drive	L7□B010□		L7□B020□		L7□B035□	L7□B050□	L7□B075□	L7□B020□	L7□B035□	L7□B050□	L7□B075□	L7□B150□	
Flange Size(□)	□130				□180				□220				
Rated Output [kW]	0.6	1.1	1.6	2.2	2.2	3.5	5.5	7.5	2.2	3.5	5.5	7.5	11
Rated Torque [N·m]	2.86	5.25	7.64	10.5	10.5	16.71	26.26	35.81	10.5	16.71	26.26	35.81	52.52
[kgf·cm]	29.23	53.59	77.95	107.19	107.19	170.52	267.96	365.41	107.19	170.52	267.96	365.41	535.93
Instantaneous Maximum Torque [N·m]	8.59	15.76	22.92	31.51	31.51	50.13	65.65	89.52	31.51	50.13	78.78	89.52	131.30
[kgf·cm]	87.7	160.78	233.86	321.56	321.56	511.57	669.91	913.52	321.56	511.57	803.89	913.52	1339.82
Rated Current [A]	3.28	3.4	4.97	6.80	6.93	9.09	14.70	18.97	7.12	8.73	16.04	19.10	27.41
Max. Current [A]	9.83	10.19	14.92	20.4	20.8	27.26	44.1	47.42	21.35	26.2	48.11	47.76	67.33
Rated Speed [r/min]							2000						
Max. Speed [r/min]					3000			2500	3000	2700	3000		2500
Inertia [kg · m ² × 10 ⁻⁴]	5.659	10.179	14.619	19.04	27.96	46.56	73.85	106.73	41.13	71.53	117.72	149.4	291.36
[gf · cm × s ²]	5.774	10.387	14.917	19.429	28.531	47.51	75.357	108.908	41.67	72.99	120.12	152.45	297.31
Allowable Load Inertia Ratio				10 times of motor inertia						5 times of motor inertia			
Rated Power Rate [kW/s]	14.5	27.1	39.92	57.95	39.46	59.98	93.38	120.15	26.83	39.04	58.58	85.83	94.65
Speed/Position Detector	Standard(Note1)						Serial Type 19 [bit]						
Option							X						
Structure							Fully closed · Self cooling IP65 Note1)						
Rated Time							Continuous						
Ambient Temp							Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]						
Ambient Humidity							90[%]RH Below (avoid dew-condensation)						
Atmosphere							Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.						
E/V							Elevation/vibration 49[m/s ²](5G)						
Weight [kg]	5.5	7.54	9.68	11.78	12.4	17.7	26.3	35.6	16.95	21.95	30.8	37.52	66.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.
It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics



F Series Motor Characteristics (400V)

Motor Specifications [Rated 1500r/min]

Servo Motor (APM-□□□□)	FEP05G	FEP09G	FEP13G	FEP17G	FFP20G	FFP30G	FFP44G	FFP60G	FFP75G	FPG20G	FPG30G	FPG44G	FPG60G	FPG85G	FGP10G	FGP150G	
Applicable Drive	L7□B010□		L7□B020□		L7□B035□	L7□B050□	L7□B075□	L7□B020□	L7□B035□	L7□B050□	L7□B075□			L7□B150□			
Flange Size(□)		□130				□180								□220			
Rated Output	[kW]	0.45	0.85	1.3	1.7	1.8	2.9	4.4	6	7.5	1.8	2.9	4.4	6	8.5	11	15
Rated Torque	[N · m]	2.86	5.41	8.28	10.82	11.46	18.46	28.01	38.2	47.75	11.46	18.46	28.01	38.2	54.11	70.03	95.49
	[kgf · cm]	29.23	55.22	84.45	110.43	116.93	188.39	285.83	389.77	487.21	116.93	188.39	285.83	389.77	552.17	714.57	974.42
Instantaneous Maximum Torque	[N · m]	8.59	16.23	24.83	32.47	34.38	55.39	84.03	95.49	119.37	34.38	55.39	84.03	95.49	135.28	175.07	238.73
	[kgf · cm]	87.7	165.65	253.35	331.3	350.79	565.16	857.49	974.42	1218.02	350.79	565.16	857.49	974.42	1380.43	1786.43	2436.05
Rated Current	[A]	3.28	3.50	5.39	7.01	7.56	10.04	15.68	20.23	20.01	7.76	9.65	17.11	20.38	28.24	28.28	35.71
Max. Current	[A]	9.83	10.5	16.16	21.02	22.69	30.12	47.04	50.58	50.03	23.29	28.95	51.32	50.95	69.37	68.83	87.7
Rated Speed	[r/min]										1500						
Max. Speed	[r/min]			3000			2700	3000	2500	2200	3000	2700	3000	2500	2000		
Inertia	[kg · m ² × 10 ⁻⁴]	5.659	10.179	14.619	19.04	27.96	46.56	73.85	106.73	131.29	51.42	80.35	132.41	172.91	291.36	51.42	424.5
	[gf · cm × s ²]	5.774	10.387	14.917	19.429	28.531	47.51	75.357	108.908	133.969	52.47	81.99	135.11	176.44	297.31	52.47	433.2
Allowable Load Inertia Ratio		10 times of motor inertia									5 times of motor inertia						
Rated Power Rate	[kW/s]	14.5	28.77	46.85	61.52	46.96	73.21	106.25	136.7	173.64	25.53	45.39	61.97	102.08	100.5	168.3	214.8
Speed/Position Detector	Standard(Note1)										Serial Type 19 [bit]						
Option											X						
Specifications & Features	Structure											Fully closed · Self cooling IP65 Note1)					
	Rated Time											Continuous					
	Ambient Temp											Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]					
	Ambient Humidity											90[%]RH Below (avoid dew-condensation)					
	Atmosphere											Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.					
	E/V											Elevation/vibration 49[m/s ²](5G)					
Weight	[kg]	5.5	7.54	9.68	11.78	12.4	17.7	26.3	35.6	39.4	16.95	21.95	30.8	37.52	66.2	66.3	92.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked
It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics



L7S Series

L7NH Series

F Series

MDM Series

PEGASUS Series

81

L7 SERIES SYSTEM


F Series Motor Characteristics (400V)

Motor Specifications [Rated 1000r/min]

Servo Motor (APM-□□□□)	FEP03M	FEP06M	FEP09M	FEP12M	FFP12M	FFP20M	FFP30M	FFP44M	FGP12M	FGP20M	FGP30M	FGP44M	FGP60M
Applicable Drive	L7□B010□			L7□B020□			L7□B050□			L7□B020□			L7□B150
Flange Size(□)	□130						□180						□220
Rated Output [kW]	0.3	0.6	0.9	1.2	1.2	2	3	4.4	1.2	2	3	4.4	6
Rated Torque [N·m]	2.86	5.73	8.59	11.46	11.46	19.1	28.65	42.02	11.46	19.1	28.65	42.02	57.3
[kgf·cm]	29.23	58.47	87.7	116.93	116.93	194.88	292.33	428.74	116.93	194.88	292.33	428.74	584.65
Instantaneous Maximum Torque [N·m]	8.59	17.19	25.78	34.38	34.38	57.3	85.94	126.05	34.38	57.3	85.94	126.05	143.24
[kgf·cm]	87.7	175.4	263.09	350.79	350.79	584.65	876.98	1286.23	350.79	584.65	876.98	1071.86	1461.63
Rated Current [A]	3.28	3.28	3.33	4.87	4.83	7.94	11.9	16.69	4.75	7.88	11.74	17.39	23.58
Max. Current [A]	9.83	9.83	9.99	14.6	14.5	23.83	35.7	50.08	14.24	23.64	35.22	52.18	57.92
Rated Speed [r/min]	1000												
Max. Speed [r/min]	2000						1700	2000					
Inertia [$\text{kg} \cdot \text{m}^2 \times 10^{-4}$]	5.659	10.179	14.619	19.04	27.96	46.56	73.85	106.73	51.42	80.35	132.41	172.91	291.36
[gf·cm×s ²]	5.774	10.387	14.917	19.429	28.531	47.51	75.357	108.908	52.47	81.99	135.11	176.44	297.31
Allowable Load Inertia Ratio	10 times of motor inertia						5 times of motor inertia						
Rated Power Rate [kW/s]	14.5	32.25	50.53	68.97	46.96	78.38	111.13	165.41	25.53	45.39	61.97	102.08	112.64
Speed/Position Detector	Standard (Note1)												
Option	Serial Type 19 [bit]												
Structure	Fully closed · Self cooling IP65 Note1)												
Rated Time	Continuous												
Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]												
Ambient Humidity	90[%]RH Below (avoid dew-condensation)												
Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.												
E/V	Elevation/vibration 49[m/s ²](5G)												
Weight [kg]	5.5	7.54	9.68	11.78	12.4	17.7	26.3	35.6	16.95	21.95	30.8	37.52	66.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.
It can be satisfied protection grade when you use private cable only.

Speed-Torque Characteristics




External Dimensions of Servo Motor

FAL Series

Plug Specifications


[Power]



Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W
PE	Green	Ground

(Power Connector Pin Table)


[Brake]



Pin No.	Signal
1	BK+
2	BK-

(Brake Connector Pin Table)

[Encoder]



Single Turn (N)	Multi Turn (M)		
Pin No.	Signal	Pin No.	Signal
1	MA	1	MA
2	SLO	2	SLO
3	-	3	GND_B
4	OV	4	OV
5	SHIELD	5	SHIELD
6	MA	6	MA
7	SLO	7	SLO
8	-	8	VDD_B
9	+5V	9	+5V


(Encoder Connector Pin Table)

Note1) Use DC[24V] for brake input power supply.

Note2) The () is for brake-attached type.

Note3) For external dimensions for oil-sealed type.
Please kindly contact us separately.


Note4) In case of FAL Type, the connector can draw
in a direction of only front



FBL Series

Plug Specifications


[Power]



Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W

(Power Connector Pin Table)


[Brake]



Pin No.	Signal
1	BK+
2	BK-

(Brake Connector Pin Table)

[Encoder]




Single Turn (N)	Multi Turn (M)		
Pin No.	Signal	Pin No.	Signal
1	MA	1	MA
2	SLO	2	SLO
3	-	3	GND_B
4	OV	4	OV
5	SHIELD	5	SHIELD
6	MA	6	MA
7	SLO	7	SLO
8	-	8	VDD_B
9	+5V	9	+5V

(Encoder Connector Pin Table)

Note1) Use DC[24V] for brake input power supply.

Note2) The () is for brake-attached type.

Note3) For external dimensions for oil-sealed type.
Please kindly contact us separately.




L7 SERIES SYSTEM

External Dimensions of Servo Motor

FCL Series

Plug Specifications


[Power]



Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W
PE	Green	Ground

(Power Connector Pin Table)


[Brake]



Pin No.	Signal
1	BK+
2	BK-

(Brake Connector Pin Table)

[Encoder]




Single Turn (N)	Multi Turn (M)		
Pin No.	Signal	Pin No.	Signal
1	MA	1	MA
2	SLO	2	SLO
3	-	3	GND_B
4	OV	4	OV
5	SHIELD	5	SHIELD
6	MA	6	MA
7	SLO	7	SLO
8	-	8	VDD_B
9	+5V	9	+5V

(Encoder Connector Pin Table)

Note1) Use DC[24V] for brake input power supply.

Note2) The () is for brake-attached type.

Note3) For external dimensions for oil-sealed type. Please kindly contact us separately.




Model	External Dimensions							Weight (kg)
	L	LM	LC	S	H	T	W	
FCL04A,FCL03D	138.7(179.5)	98.7(139.5)	70(69.8)	14	-0.018	5	5	3 1.52(2.32)/1.26(2.06)
FCL06A,FCL05D	156.7(197.5)	116.7(157.5)	88(87.8)	19	-0.021	6	6	3.5 2.14(2.94)/2.12(2.92)
FCL08A,FCL06D	174.7(215.5)	134.7(175.5)	106(105.8)	19	-0.021	6	6	3.5 2.68(3.48)/2.66(3.46)
FCL10A,FCL07D	192.7(233.5)	152.7(193.5)	124(123.8)	19	-0.021	6	6	3.5 3.30(4.10)/2.78(3.58)

FB Series

Plug Specifications


[Power]



Pin No.	Color	Signal
1	Black	W
2	White	V
3	Red	U

(Power Connector Pin Table)


[Brake]



Pin No.	Signal
1	BK+
2	BK-

(Brake Connector Pin Table)

[Encoder]




Single Turn (N)	Multi Turn (M)		
Pin No.	Signal	Pin No.	Signal
1	MA	1	MA
2	SLO	2	SLO
3	-	3	GND_B
4	OV	4	OV
5	SHIELD	5	SHIELD
6	MA	6	MA
7	SLO	7	SLO
8	-	8	VDD_B
9	+5V	9	+5V

(Encoder Connector Pin Table)

Note1) Use DC[24V] for brake input power supply.

Note2) The () is for brake-attached type.

Note3) For external dimensions for oil-sealed type. Please kindly contact us separately.




Model	External Dimensions			Key			Weight (kg)
	L	LM	LC	T	W	U	
FB01A	109(149.2)	79(119.2)	43.5(43)				0.72(1.3)
FB02A	120(160.2)	90(130.2)	54.5(54)	3	5 ^{-0.012} _{-0.042}	5	0.94(1.49)
FB04A	140(180.2)	110(150.2)	74.5(74)				1.32(1.87)

External Dimensions of Servo Motor

FC Series

Plug Specifications


[Power]



Pin No.	Color	Signal
1	Black	W
2	White	V
3	Red	U
4	Green	Ground

(Power Connector Pin Table)


[Brake]



Pin No.	Signal
1	BK+
2	BK-


(Brake Connector Pin Table)

[Encoder]



Single Turn (N)	Multi Turn (M)		
Pin No.	Signal	Pin No.	Signal
1	MA	1	MA
2	SLO	2	SLO
3	-	3	GND_B
4	OV	4	OV
5	SHIELD	5	SHIELD
6	MA	6	MA
7	SLO	7	SLO
8	-	8	VDD_B
9	+5V	9	+5V


(Encoder Connector Pin Table)

Note1) Use DC[24V] for brake input power supply.**Note2)** The () is for brake-attached type.**Note3)** For external dimensions for oil-sealed type. Please kindly contact us separately.

FE, FEP Series


Plug Specifications

[Power]



Pin No.	Signal
A	U
B	V
C	W
D	Ground


Spec. : MS3102A20-4P (Standard)



Pin No.	Signal	Pin No.	Signal
A	U	D	Ground
B	V	E	BK+
C	W	F	BK-

Spec. : MS3102A20-15P (Brake-attached type)

[Encoder]




Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	OV
K	-	J	SHIELD
L	-		

Spec. : MS3102A20-29P (Serial type)

Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	VOD_B	H	+5V
F	GND_B	G	OV
K	-	J	SHIELD
L	-		


(Multi Turn Encoder Connector Pin Table)

Note1) Use DC[24V] for brake input power supply.**Note2)** The () is for brake-attached type.

Direct-Drive motor



■ Direct-Drive Designation



L7S Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options


PEGASUS Series

L7 SERIES SYSTEM

Features of Mecapion Direct-Drive Motor

- Using the own technologies to produce motors, drives and encoders domestically

- Optimized for low-speed, high-torque and high-precision operation
 - Providing Power connection for the connection of DC-Link Terminal
 - Compact Size and Easy Wring (Compared with 3 phase AC Reactor)
 - Providing Connection for DC Input (PI, N)




- Reduced cogging torque and optimized torque design
 - Optimal ratio of the permanent magnet and coil / slot selected through electromagnetic analysis
 - Using multiple permanent magnets to reduce torque ripple and to maximize torque
 - Using a permanent magnet of high-energy rare earth elements (Nd-Fe-B)

- Using the high-performance rotary optical encoder that adopts the Biss protocol
 - Resolution of 1,048,576 CPR (Single turn Absolute)
 - Using our own encoder technology to reduce the cost and shorten the delivery time

- Compatible with our L7 Series AC Servo Drive (3phase AC 220V)
 - Both standard I/O type (serial communication supported) and network type (EtherCAT) applicable

- Direct Drive Structure

- No backlash impact
- High-precision operation and shortened installation time
- Smooth rotary motion
- Reduced noise



[Speed Reducer + Servo Motor]

[DD Motor]

- Hollow type that is efficient for wiring and piping

- A wide range of products

- Rated output: 63W-.25kW
- Rated torque: 3.0N.m–160N.m (the instantaneous maximum torque should be 3 times the rated torque)
- Rated speed: 150RPM–200RPM
- Frame diameter: 135mm,175mm,230mm,290mm, and 360mm (13 models)

DD Motor Specifications

Ratings and Specifications

- Insulation class : Class B
- Protection class: IP 40
- Cooling type : Fully enclosed self-cooling
- Vibration class : V15
- Insulation resistance : 500 VDC, 10[MΩ] or higher
- Insulation internal voltage: 1800 VAC, 1 second
- Operating voltage: 200 VAC
- Operating temperature : 0 – 40[°C] / Storage temperature: -10~60[°C]
- Ambient humidity : 20 – 80% RH (no condensation)
- Installation location : Place with no toxic substances, such as corrosive and combustible gasses, cutting oil, metal dust, grease or direct sunlight

Line-up Table

Maximum Torque[Nm]			9	18	27	36	54	66	102	120	180	330	480
Rated speed 200[rpm]	Maximum speed 500[rpm]	Φ135	DB03D	DB06D	DB09D								
		Φ175			DC06D		DC12D						
		Φ230					DD12D						
	Maximum speed 400[rpm]	Φ175					DC18D						
		Φ230					DD22D	DD34D					
	Maximum speed 300[rpm]	Φ290							DE40D	DE60D			
Rated speed 150[rpm]	Maximum speed 250[rpm]	Φ360									DFA1D	DFA6D	

L7 SERIES SYSTEM

Motor Designation

Applicable drive to motor

Rated Speed (RPM)	Maximum Speed (RPM)	External Diameter of Motor(Φ)	Applicable Motor	Applicable Drive	encoder type
200	500	Φ135	DB03D	L7□A001□	20 bit single turn serial encoder (Biss/Absolute)
		Φ135	DB06D	L7□A002□	
		Φ135	DB09D	L7□A004□	
	500	Φ175	DC06D	L7□A002□	
		Φ175	DC12D	L7□A004□	
	400	Φ175	DC18D	L7□A008□	
	500	Φ230	DD12D	L7□A004□	
	400	Φ230	DD22D	L7□A008□	
	400	Φ230	DD34D	L7□A010□	
	300	Φ290	DE40D	L7□A010□	
	300	Φ290	DE60D	L7□A020□	
150	250	Φ360	DFA1G	L7□A020□	
		Φ360	DFA6G	L7□A035□	

Appearances of Motor



Features of Direct Drive Motor

Motor Designation	MDM-DB□□D□H			MDM-DC□□D□H		
	03	06	09	06	12	18
Applicable Drive (L7□-A□□□□)	L7□A001□	L7□A002□	L7□A004□	L7□A002□	L7□A004□	L7□A008□
Flange Size	mm	Φ135		Φ175		
Rated Output	W	63	126	188	126	251
Rated Torque	N·m	3	6	9	6	12
Max Torque	N·m	9	18	27	18	36
Rated Current	Arms	1.12	1.46	2.63	1.48	2.41
Max Current	Arms	3.36	4.38	7.89	4.44	7.23
Rated Speed	rpm	200		200		
Max Speed	rpm	500	500	500	500	400
Constant of Torque	N·m/Arms	2.76	4.25	3.57	4.18	5.13
Inertia	kg·m ² ×10 ⁻⁴	5.74	8.67	11.5	27.32	38.9
Rated Power Rate	kW/s	15.68	42.35	70.43	13.18	52.71
Angular acceleration	rad/s ²	191.2	141.6	127.7	455.03	323.9
positioning accuracy	arc-sec			±15		
positioning repeatability	arc-sec			±1.3		
Axial run-out	mm			0.015		
Radial run-out	mm			0.03		
Allowed Moment Load	N	1500		3300		
Max. Instantaneous	N·m	40		70		
Encoder Type	20-bit single turn serial encoder (Biss/Absolute)					
Weight (Approx.)	kg	6.3	7.2	9.2	8.7	10.6
Working Environment	Ambient Temp	operating : 0~40[°C] / storage : -20~60[°C]				
	Ambient Humidity	20~80[%] RH(avoid dew-condensation)				
	Atmosphere	Avoid direct sunlight, No corrosive gas, Inflammable gas, Oil mist, or Dust				

* In case of allowable load inertia ratio, please apply within 30 times of rotator inertia

Speed-Torque Characteristics



L7S Series

L7NH Series

S Series

F Series

MDM Series

PEGASUS Series

Options

L7 SERIES SYSTEM

Features of Direct Drive Motor

Motor Designation	MDM-DD□□D□H			MDM-DE□□D□H		MDM-DF□□G□H	
	12	22	34	40	60	A1	A6
Applicable Drive (L7□-A□□□□)	L7□A004□	L7□A008□	L7□A010□	L7□A010□	L7□A020□	L7□A020□	L7□A035□
Flange Size	mm	$\Phi 230$			$\Phi 290$		$\Phi 360$
Rated Output	W	251	461	712	838	1,257	1,728
Rated Torque	N·m	12	22	34	40	60	110
Max Torque	N·m	36	66	102	120	180	330
Rated Current	Arms	2.58	3.33	5.72	5.3	8.33	9.48
Max Current	Arms	7.74	9.99	17.16	15.9	24.99	28.44
Rated Speed	rpm	200			200		150
Max Speed	rpm	500	400	400	300	300	250
Constant of Torque	N·m/Arms	4.8	6.81	6.13	7.77	7.42	11.95
Inertia	$\text{kg}\cdot\text{m}^2 \times 10^{-4}$	54.14	68.15	82.16	311.55	371.71	1410.2
Rated Power Rate	kW/s	26.6	71.02	140.7	51.36	96.68	85.9
Angular acceleration	rad/s^2	450.9	309.6	241.5	778.35	619.1	1281.13
positioning accuracy	arc-sec	± 15					
positioning repeatability	arc-sec	± 1.3					
Axial run-out	mm	0.015					
Radial run-out	mm	0.03					
Allowed Moment Load	N	4000		11000		15000	
Max, Instantaneous	N·m	93		250		350	
Encoder Type		20-bit single turn serial encoder (Biss/Absolute)					
Weight (Approx.)	kg	17.3	19.6	21.9	28.2	35	54
Working Environment	Ambient Temp	operating : 0~40[°C] / storage : -20~60[°C]					
	Ambient Humidity	20~80[%] RH (avoid dew-condensation)					
	Atmosphere	Avoid direct sunlight, No corrosive gas, Inflammable gas, Oil mist, or Dust					


* In case of allowable load inertia ratio, please apply within 30 times of rotator inertia

Speed-Torque Characteristics




External Dimensions of Direct-Drive Rotary Motor

■ MDM-DB03D, MDM-DB06D, MDM-DB09D



■ MDM-DC06D, MDM-DC12D, MDM-DC18D



L7 SERIES SYSTEM

External Dimensions of Direct-Drive Rotary Motor

■ MDM-DD12D, MDM-DD22D, MDM-DD34D

POWER CONNECTOR

Signal	Line color	PIN NO.
LEAD WIRE	U Red	A
V White	B	
W Black	C	
FG Green	D	

ENCODER CONNECTOR

D.D SERVO ENCODER CABLE			
No.	Encoder Signal	No.	Encoder Signal
1	MA	9	+5V
2	SLO	10	-
3	-	11	-
4	0V	12	-
5	Shield	13	-
6	MA	14	-
7	SLO	15	-
8	-		

External Dimensions

Motor Series

Motor Series	External Dimensions		Weight(kg)
	L		
MDM-DD12D	82.5		17.3
MDM-DD22D	100.5		19.6
MDM-DD34D	118.5		21.9

■ MDM-DE40D, MDM-DE60D

POWER CONNECTOR

Signal	Line color	PIN NO.
LEAD WIRE	U Red	A
V White	B	
W Black	C	
FG Green	D	

ENCODER CONNECTOR

D.D SERVO ENCODER CABLE			
No.	Encoder Signal	No.	Encoder Signal
1	MA	9	+5V
2	SLO	10	-
3	-	11	-
4	0V	12	-
5	Shield	13	-
6	MA	14	-
7	SLO	15	-
8	-		


External Dimensions

Motor Series

Motor Series	External Dimensions		Weight(kg)
	L		
MDM-DE40D	95.4		28.2
MDM-DE60D	113.4		35

External Dimensions of Direct-Drive Rotary Motor

■ MDM-DFA1G, MDM-DFA6G



L7S Series

L7N Series

L7NH Series L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

Contents

■ Options

Servo motor options

- Signal cable _ 97
- Power cable _ 100

Servo drive options

- Signal cable _ 109
- Connector _ 110

Other options

- Braking resistance _ 112
- Noise Filter _ 114

Servo Motor Option

■ Signal Cable [Incremental]

Type	Product Type	Model Name ^(Note)	Applicable Drive	Applicable Motor	Specifications																																																																									
For Signal	Parallel Encoder Cable (Small Capacity)	APCS-E□□□AS	L7SA□□□A L7NHA□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC APM-HB SERIES	<p style="text-align: center;">Motor Side Connector</p> <p style="text-align: center;">Drive Side Connector(CN2)</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <th>PIN No.</th> <th>Encoder Signal</th> <th>PIN No.</th> <th>Encoder Signal</th> </tr> <tr><td>1</td><td>A</td><td>9</td><td>V</td></tr> <tr><td>2</td><td>Ā</td><td>10</td><td>Ā</td></tr> <tr><td>3</td><td>B</td><td>11</td><td>W</td></tr> <tr><td>4</td><td>Ā</td><td>12</td><td>W</td></tr> <tr><td>5</td><td>Z</td><td>13</td><td>+5V</td></tr> <tr><td>6</td><td>Ā</td><td>14</td><td>0V</td></tr> <tr><td>7</td><td>U</td><td>15</td><td>SHIELD</td></tr> <tr><td>8</td><td>Ā</td><td></td><td></td></tr> </table> <p style="text-align: center;">(Motor Side Connector)</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <th>PIN No.</th> <th>Encoder Signal</th> <th>PIN No.</th> <th>Encoder Signal</th> </tr> <tr><td>1</td><td>W</td><td>8</td><td>Z</td></tr> <tr><td>2</td><td>Ā</td><td>9</td><td>Ā</td></tr> <tr><td>3</td><td>V</td><td>10</td><td>Ā</td></tr> <tr><td>4</td><td>Ā</td><td>11</td><td>B</td></tr> <tr><td>5</td><td>U</td><td>12</td><td>Ā</td></tr> <tr><td>6</td><td>Ā</td><td>13</td><td>A</td></tr> <tr><td>7</td><td>OV</td><td>14</td><td>+5V</td></tr> <tr><td></td><td></td><td>PLATE</td><td>SHIELD</td></tr> </table> <p style="text-align: center;">(Driver Side Connector)</p>	PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	A	9	V	2	Ā	10	Ā	3	B	11	W	4	Ā	12	W	5	Z	13	+5V	6	Ā	14	0V	7	U	15	SHIELD	8	Ā			PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	W	8	Z	2	Ā	9	Ā	3	V	10	Ā	4	Ā	11	B	5	U	12	Ā	6	Ā	13	A	7	OV	14	+5V			PLATE	SHIELD	<ol style="list-style-type: none"> 1. Motor Side Connector <ol style="list-style-type: none"> a. Cap Spec.(15 Position) : 172163-1(AMP) b. Socket Spec. : 170361-1(AMP) 2. Driver Side Connector(CN2) <ol style="list-style-type: none"> a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone) 3. Cable Spec. : 7P×0.2SQ or 7P×AWG24
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																											
1	A	9	V																																																																											
2	Ā	10	Ā																																																																											
3	B	11	W																																																																											
4	Ā	12	W																																																																											
5	Z	13	+5V																																																																											
6	Ā	14	0V																																																																											
7	U	15	SHIELD																																																																											
8	Ā																																																																													
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																											
1	W	8	Z																																																																											
2	Ā	9	Ā																																																																											
3	V	10	Ā																																																																											
4	Ā	11	B																																																																											
5	U	12	Ā																																																																											
6	Ā	13	A																																																																											
7	OV	14	+5V																																																																											
		PLATE	SHIELD																																																																											
For Signal	Parallel Encoder Cable (Middle Capacity)	APCS-E□□□BS	L7S□□□A L7NH□□□U L7PA□□□U	All Models of APM-SE, SEP APM-SF, SFP APM-SG, SGP APM-LF APM-LG APM-HE SERIES	<p style="text-align: center;">Motor Side Connector</p> <p style="text-align: center;">Drive Side Connector(CN2)</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <th>PIN No.</th> <th>Encoder Signal</th> <th>PIN No.</th> <th>Encoder Signal</th> </tr> <tr><td>A</td><td>A</td><td>M</td><td>V</td></tr> <tr><td>B</td><td>Ā</td><td>N</td><td>Ā</td></tr> <tr><td>C</td><td>B</td><td>P</td><td>W</td></tr> <tr><td>D</td><td>Ā</td><td>R</td><td>Ā</td></tr> <tr><td>E</td><td>Z</td><td>H</td><td>+5V</td></tr> <tr><td>F</td><td>Ā</td><td>G</td><td>0V</td></tr> <tr><td>K</td><td>U</td><td>J</td><td>SHIELD</td></tr> <tr><td>L</td><td>Ā</td><td></td><td></td></tr> </table> <p style="text-align: center;">(Motor Side Connector)</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <th>PIN No.</th> <th>Encoder Signal</th> <th>PIN No.</th> <th>Encoder Signal</th> </tr> <tr><td>1</td><td>W</td><td>8</td><td>Z</td></tr> <tr><td>2</td><td>Ā</td><td>9</td><td>Ā</td></tr> <tr><td>3</td><td>V</td><td>10</td><td>B</td></tr> <tr><td>4</td><td>Ā</td><td>11</td><td>B</td></tr> <tr><td>5</td><td>U</td><td>12</td><td>Ā</td></tr> <tr><td>6</td><td>Ā</td><td>13</td><td>A</td></tr> <tr><td>7</td><td>OV</td><td>14</td><td>+5V</td></tr> <tr><td></td><td></td><td>PLATE</td><td>SHIELD</td></tr> </table> <p style="text-align: center;">(Driver Side Connector)</p>	PIN No.	Encoder Signal	PIN No.	Encoder Signal	A	A	M	V	B	Ā	N	Ā	C	B	P	W	D	Ā	R	Ā	E	Z	H	+5V	F	Ā	G	0V	K	U	J	SHIELD	L	Ā			PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	W	8	Z	2	Ā	9	Ā	3	V	10	B	4	Ā	11	B	5	U	12	Ā	6	Ā	13	A	7	OV	14	+5V			PLATE	SHIELD	<ol style="list-style-type: none"> 1. Motor Side Connector(MS : Military Standard) <ol style="list-style-type: none"> a. Plug Spec. : MS3108A20-29S 2. Drive Side Connector(CN2) <ol style="list-style-type: none"> a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone) 3. Cable Spec. : 7P×0.2SQ or 7P×AWG24
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																											
A	A	M	V																																																																											
B	Ā	N	Ā																																																																											
C	B	P	W																																																																											
D	Ā	R	Ā																																																																											
E	Z	H	+5V																																																																											
F	Ā	G	0V																																																																											
K	U	J	SHIELD																																																																											
L	Ā																																																																													
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																											
1	W	8	Z																																																																											
2	Ā	9	Ā																																																																											
3	V	10	B																																																																											
4	Ā	11	B																																																																											
5	U	12	Ā																																																																											
6	Ā	13	A																																																																											
7	OV	14	+5V																																																																											
		PLATE	SHIELD																																																																											

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

L7 SERIES SYSTEM

Servo Motor Option

■ Signal Cable [Serial]

Type	Product Type	Model Name ^(Note)	Applicable Drive	Applicable Motor	Specifications																																																
For Signal	S Series Motor S-turn Encoder Cable (Small Capacity)	APCS-E□□□CS	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC SERIES	<p>Motor Side Connector</p> <p>Drive Side Connector(CN2)</p> <p>1. Motor Side Connector a. Cap Spec.(9 Position) : 172161-1(AMP) b. Socket Spec. : 170361-1(AMP)</p> <p>2. Drive Side Connector(CN2) a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone)</p> <p>3. Cable Spec. : 3P×0.2SQ or 3P×24AWG</p> <table border="1"> <tr> <td>PIN No.</td> <td>Encoder Signal</td> <td>PIN No.</td> <td>Encoder Signal</td> </tr> <tr> <td>1</td> <td>MA</td> <td>8</td> <td>-</td> </tr> <tr> <td>2</td> <td>MA</td> <td>9</td> <td>-</td> </tr> <tr> <td>3</td> <td>SLO</td> <td>10</td> <td>-</td> </tr> <tr> <td>4</td> <td>SLO</td> <td>11</td> <td>-</td> </tr> <tr> <td>5</td> <td>-</td> <td>12</td> <td>-</td> </tr> <tr> <td>6</td> <td>-</td> <td>13</td> <td>-</td> </tr> <tr> <td>7</td> <td>+5V</td> <td>14</td> <td>+5V</td> </tr> <tr> <td>8</td> <td>0V</td> <td></td> <td></td> </tr> <tr> <td>9</td> <td>SHIELD</td> <td></td> <td></td> </tr> </table> <p>(Motor Side Connector) (Drive Side Connector)</p>	PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	MA	8	-	2	MA	9	-	3	SLO	10	-	4	SLO	11	-	5	-	12	-	6	-	13	-	7	+5V	14	+5V	8	0V			9	SHIELD										
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																		
1	MA	8	-																																																		
2	MA	9	-																																																		
3	SLO	10	-																																																		
4	SLO	11	-																																																		
5	-	12	-																																																		
6	-	13	-																																																		
7	+5V	14	+5V																																																		
8	0V																																																				
9	SHIELD																																																				
For Signal	S Series Motor M-turn Encoder Cable (Small Capacity)	APCS-E□□□CS1	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC SERIES	<p>Motor Side Connector</p> <p>Drive Side Connector(CN2)</p> <p>1. Motor Side Connector a. CAP Spec.(9 Position) : 172161-1(AMP) b. Socket Spec. : 170361-1(AMP)</p> <p>2. Drive Side Connector(CN2) a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone)</p> <p>3. Cable Spec. : 4P×0.2SQ or 4P×24AWG</p> <p>4. Battery Connector Spec. : 5267-02A(MOLEX)</p> <table border="1"> <tr> <td>PIN No.</td> <td>Encoder Signal</td> <td>PIN No.</td> <td>Encoder Signal</td> </tr> <tr> <td>1</td> <td>MA</td> <td>8</td> <td>-</td> </tr> <tr> <td>2</td> <td>MA</td> <td>9</td> <td>-</td> </tr> <tr> <td>3</td> <td>SL</td> <td>10</td> <td>-</td> </tr> <tr> <td>4</td> <td>SL</td> <td>11</td> <td>-</td> </tr> <tr> <td>5</td> <td>VDD B</td> <td>12</td> <td>-</td> </tr> <tr> <td>6</td> <td>GND B</td> <td>13</td> <td>-</td> </tr> <tr> <td>7</td> <td>+5V</td> <td>14</td> <td>+5V</td> </tr> <tr> <td>8</td> <td>0V</td> <td></td> <td></td> </tr> <tr> <td>9</td> <td>SHIELD</td> <td></td> <td></td> </tr> </table> <p>(Motor Side Connector) (Drive Side Connector)</p> <table border="1"> <tr> <td>PIN No.</td> <td>Encoder Signal</td> <td>PIN No.</td> <td>Encoder Signal</td> </tr> <tr> <td>1</td> <td>BATTERY (VDD B)</td> <td>2</td> <td>BATTERY (V GND B)</td> </tr> </table> <p>(Battery Connector)</p>	PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	MA	8	-	2	MA	9	-	3	SL	10	-	4	SL	11	-	5	VDD B	12	-	6	GND B	13	-	7	+5V	14	+5V	8	0V			9	SHIELD			PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	BATTERY (VDD B)	2	BATTERY (V GND B)
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																		
1	MA	8	-																																																		
2	MA	9	-																																																		
3	SL	10	-																																																		
4	SL	11	-																																																		
5	VDD B	12	-																																																		
6	GND B	13	-																																																		
7	+5V	14	+5V																																																		
8	0V																																																				
9	SHIELD																																																				
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																		
1	BATTERY (VDD B)	2	BATTERY (V GND B)																																																		
For Signal	S/F Series Motor S-turn Encoder Cable (Middle Capacity)	APCS-E□□□DS	L7S□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APM-SE, FE, SEP, FEP APM-SF, FF SFP, FFP APM-SG, FG SGP, FGP APM-LF APM-LG SERIES	<p>Motor Side Connector</p> <p>Drive Side Connector(CN2)</p> <p>1. Motor Side Connector(MS : Military Standard) a. Plug Spec. : MS3108A20-29S</p> <p>2. Drive Side Connector(CN2) a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone)</p> <p>3. Cable Spec. : 3P×0.2SQ or 3P×24AWG</p> <table border="1"> <tr> <td>PIN No.</td> <td>Encoder Signal</td> <td>PIN No.</td> <td>Encoder Signal</td> </tr> <tr> <td>A</td> <td>MA</td> <td>M</td> <td>-</td> </tr> <tr> <td>B</td> <td>MA</td> <td>N</td> <td>-</td> </tr> <tr> <td>C</td> <td>SLO</td> <td>P</td> <td>-</td> </tr> <tr> <td>D</td> <td>SLO</td> <td>R</td> <td>-</td> </tr> <tr> <td>E</td> <td>-</td> <td>H</td> <td>+5V</td> </tr> <tr> <td>F</td> <td>-</td> <td>G</td> <td>0V</td> </tr> <tr> <td>K</td> <td>-</td> <td>J</td> <td>SHIELD</td> </tr> <tr> <td>L</td> <td>-</td> <td></td> <td></td> </tr> </table> <p>(Motor Side Connector) (Drive Side Connector)</p>	PIN No.	Encoder Signal	PIN No.	Encoder Signal	A	MA	M	-	B	MA	N	-	C	SLO	P	-	D	SLO	R	-	E	-	H	+5V	F	-	G	0V	K	-	J	SHIELD	L	-														
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																		
A	MA	M	-																																																		
B	MA	N	-																																																		
C	SLO	P	-																																																		
D	SLO	R	-																																																		
E	-	H	+5V																																																		
F	-	G	0V																																																		
K	-	J	SHIELD																																																		
L	-																																																				

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

Servo Motor Option

■ Signal Cable [Serial]

Type	Product Type	Model Name ^(Note)	Applicable Drive	Applicable Motor	Specifications																																																																												
For Signal	S/F Series Motor M-turn Encoder Cable (Middle Capacity)	APCS-E□□□DS1	L7S□□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APM-SE, FE SEP,FEP APM-SF, FF SFP,FPP APM-SG, FG, SGP,FGP APM-LF APM-LG SERIES	<p>Motor Side Connector</p> <table border="1"> <tr><td>PIN No.</td><td>Encoder Signal No.</td><td>PIN No.</td><td>Encoder Signal</td></tr> <tr><td>A</td><td>MA</td><td>M</td><td>-</td></tr> <tr><td>B</td><td>MA</td><td>N</td><td>-</td></tr> <tr><td>C</td><td>SLO</td><td>P</td><td>-</td></tr> <tr><td>D</td><td>SLO</td><td>R</td><td>-</td></tr> <tr><td>E</td><td>VOD_B</td><td>H</td><td>+5V</td></tr> <tr><td>F</td><td>GND_B</td><td>G</td><td>0V</td></tr> <tr><td>G</td><td>-</td><td>J</td><td>SHIELD</td></tr> <tr><td>L</td><td>-</td><td></td><td></td></tr> <tr><td>14</td><td>OV</td><td>14</td><td>+5V</td></tr> </table> <p>Drive Side Connector(CN2)</p> <table border="1"> <tr><td>PIN No.</td><td>Encoder Signal No.</td><td>PIN No.</td><td>Encoder Signal</td></tr> <tr><td>1</td><td>-</td><td>8</td><td>-</td></tr> <tr><td>2</td><td>-</td><td>9</td><td>-</td></tr> <tr><td>3</td><td>MA</td><td>10</td><td>-</td></tr> <tr><td>4</td><td>MA</td><td>11</td><td>-</td></tr> <tr><td>5</td><td>SLO</td><td>12</td><td>-</td></tr> <tr><td>6</td><td>SLO</td><td>13</td><td>-</td></tr> <tr><td>7</td><td>OV</td><td>14</td><td>+5V</td></tr> <tr><td>9</td><td>PLATE</td><td></td><td>SHIELD</td></tr> </table> <p><Driver Side Connector></p> <p><Battery Connector></p> <ol style="list-style-type: none"> 1. Motor Side Connector(MS : Military Standard) <ol style="list-style-type: none"> a. Plug Spec. : MS3108A20-29S 2. Drive Side Connector(CN2) <ol style="list-style-type: none"> a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone) 3. Cable Spec. : 4P×0.25Q or 4P×24AWG 4. Battery Connector Spec. : 5267-02A(MOLEX) 	PIN No.	Encoder Signal No.	PIN No.	Encoder Signal	A	MA	M	-	B	MA	N	-	C	SLO	P	-	D	SLO	R	-	E	VOD_B	H	+5V	F	GND_B	G	0V	G	-	J	SHIELD	L	-			14	OV	14	+5V	PIN No.	Encoder Signal No.	PIN No.	Encoder Signal	1	-	8	-	2	-	9	-	3	MA	10	-	4	MA	11	-	5	SLO	12	-	6	SLO	13	-	7	OV	14	+5V	9	PLATE		SHIELD
PIN No.	Encoder Signal No.	PIN No.	Encoder Signal																																																																														
A	MA	M	-																																																																														
B	MA	N	-																																																																														
C	SLO	P	-																																																																														
D	SLO	R	-																																																																														
E	VOD_B	H	+5V																																																																														
F	GND_B	G	0V																																																																														
G	-	J	SHIELD																																																																														
L	-																																																																																
14	OV	14	+5V																																																																														
PIN No.	Encoder Signal No.	PIN No.	Encoder Signal																																																																														
1	-	8	-																																																																														
2	-	9	-																																																																														
3	MA	10	-																																																																														
4	MA	11	-																																																																														
5	SLO	12	-																																																																														
6	SLO	13	-																																																																														
7	OV	14	+5V																																																																														
9	PLATE		SHIELD																																																																														
For Signal	F Series Motor S-turn Encoder Cable (Small Capacity)	APCS-E□□□ES-□	L7SA□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APM-FAL APM-FB, FBL APM-FC, FCL SERIES	<p>Motor Side Connector</p> <table border="1"> <tr><td>PIN No.</td><td>Encoder Signal</td></tr> <tr><td>1</td><td>MA</td></tr> <tr><td>2</td><td>SLO</td></tr> <tr><td>3</td><td>-</td></tr> <tr><td>4</td><td>OV</td></tr> <tr><td>5</td><td>SHIELD</td></tr> <tr><td>6</td><td>MA</td></tr> <tr><td>7</td><td>SLO</td></tr> <tr><td>8</td><td>+5V</td></tr> <tr><td>9</td><td>+5V</td></tr> </table> <p>Drive Side Connector(CN2)</p> <table border="1"> <tr><td>PIN No.</td><td>Encoder Signal No.</td><td>PIN No.</td><td>Encoder Signal</td></tr> <tr><td>1</td><td>-</td><td>8</td><td>-</td></tr> <tr><td>2</td><td>-</td><td>9</td><td>-</td></tr> <tr><td>3</td><td>MA</td><td>10</td><td>-</td></tr> <tr><td>4</td><td>MA</td><td>11</td><td>-</td></tr> <tr><td>5</td><td>SLO</td><td>12</td><td>-</td></tr> <tr><td>6</td><td>SLO</td><td>13</td><td>-</td></tr> <tr><td>7</td><td>OV</td><td>14</td><td>+5V</td></tr> <tr><td>9</td><td>PLATE</td><td></td><td>SHIELD</td></tr> </table> <p><Motor Side Connector></p> <p><Driver Side Connector></p> <ol style="list-style-type: none"> 1. Motor Side Connector <ol style="list-style-type: none"> a. Cap Spec. : 2201825-1(Tyco) b. Socket Spec. : 2174065-4(Tyco) 2. Drive Side Connector(CN2) <ol style="list-style-type: none"> a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone) 3. Cable Spec. : 3P×0.25Q or 3P×24AWG 	PIN No.	Encoder Signal	1	MA	2	SLO	3	-	4	OV	5	SHIELD	6	MA	7	SLO	8	+5V	9	+5V	PIN No.	Encoder Signal No.	PIN No.	Encoder Signal	1	-	8	-	2	-	9	-	3	MA	10	-	4	MA	11	-	5	SLO	12	-	6	SLO	13	-	7	OV	14	+5V	9	PLATE		SHIELD																				
PIN No.	Encoder Signal																																																																																
1	MA																																																																																
2	SLO																																																																																
3	-																																																																																
4	OV																																																																																
5	SHIELD																																																																																
6	MA																																																																																
7	SLO																																																																																
8	+5V																																																																																
9	+5V																																																																																
PIN No.	Encoder Signal No.	PIN No.	Encoder Signal																																																																														
1	-	8	-																																																																														
2	-	9	-																																																																														
3	MA	10	-																																																																														
4	MA	11	-																																																																														
5	SLO	12	-																																																																														
6	SLO	13	-																																																																														
7	OV	14	+5V																																																																														
9	PLATE		SHIELD																																																																														
For Signal	F Series Motor M-turn Encoder Cable (Small Capacity)	APCS-E□□□ES1-□	L7SA□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APM-FAL APM-FB, FBL APM-FC, FCL SERIES	<p>Motor Side Connector</p> <table border="1"> <tr><td>PIN No.</td><td>Encoder Signal</td></tr> <tr><td>1</td><td>MA</td></tr> <tr><td>2</td><td>SLO</td></tr> <tr><td>3</td><td>GND_B</td></tr> <tr><td>4</td><td>OV</td></tr> <tr><td>5</td><td>SHIELD</td></tr> <tr><td>6</td><td>MA</td></tr> <tr><td>7</td><td>SLO</td></tr> <tr><td>8</td><td>VOD_B</td></tr> <tr><td>9</td><td>+5V</td></tr> </table> <p>Drive Side Connector(CN2)</p> <table border="1"> <tr><td>PIN No.</td><td>Encoder Signal No.</td><td>PIN No.</td><td>Encoder Signal</td></tr> <tr><td>1</td><td>-</td><td>8</td><td>-</td></tr> <tr><td>2</td><td>-</td><td>9</td><td>-</td></tr> <tr><td>3</td><td>MA</td><td>10</td><td>-</td></tr> <tr><td>4</td><td>MA</td><td>11</td><td>-</td></tr> <tr><td>5</td><td>SLO</td><td>12</td><td>-</td></tr> <tr><td>6</td><td>SLO</td><td>13</td><td>-</td></tr> <tr><td>7</td><td>OV</td><td>14</td><td>+5V</td></tr> <tr><td>9</td><td>PLATE</td><td></td><td>SHIELD</td></tr> </table> <p><Driver Side Connector></p> <p><Battery Connector></p> <ol style="list-style-type: none"> 1. Motor Side Connector <ol style="list-style-type: none"> a. Cap Spec. : 2201825-1(Tyco) b. Socket Spec. : 2174065-4(Tyco) 2. Drive Side Connector(CN2) <ol style="list-style-type: none"> a. Cap Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone) 3. Cable Spec. : 4P×0.25Q or 4P×24AWG 4. Battery Connector Spec. : 5267-02A(MOLEX) 	PIN No.	Encoder Signal	1	MA	2	SLO	3	GND_B	4	OV	5	SHIELD	6	MA	7	SLO	8	VOD_B	9	+5V	PIN No.	Encoder Signal No.	PIN No.	Encoder Signal	1	-	8	-	2	-	9	-	3	MA	10	-	4	MA	11	-	5	SLO	12	-	6	SLO	13	-	7	OV	14	+5V	9	PLATE		SHIELD																				
PIN No.	Encoder Signal																																																																																
1	MA																																																																																
2	SLO																																																																																
3	GND_B																																																																																
4	OV																																																																																
5	SHIELD																																																																																
6	MA																																																																																
7	SLO																																																																																
8	VOD_B																																																																																
9	+5V																																																																																
PIN No.	Encoder Signal No.	PIN No.	Encoder Signal																																																																														
1	-	8	-																																																																														
2	-	9	-																																																																														
3	MA	10	-																																																																														
4	MA	11	-																																																																														
5	SLO	12	-																																																																														
6	SLO	13	-																																																																														
7	OV	14	+5V																																																																														
9	PLATE		SHIELD																																																																														

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of □ marked product, the connector can draw in a direction of Front(load) / Rear(half load).(Front Type : No mark, Rear Type : -R)

Note3) In case of FAL Type, the connector can draw in a direction of only front

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

L7S Series

L7N Series

S Series

F Series

PEGASUS Series

L7 SERIES SYSTEM

Servo Motor Option

■ Power Cable [200V]

Type	Product Type	Model Name ^(Note1)	Applicable Drive	Applicable Motor	Specifications										
For Power	S Series Power Cable (Small Capacity)	APCS-P□□□GS	L7SA□□□A L7NHA□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC APM-HB SERIES	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>1</td> <td>U</td> </tr> <tr> <td>2</td> <td>V</td> </tr> <tr> <td>3</td> <td>W</td> </tr> <tr> <td>4</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector a. Cap Spec.(4 Position) : 172159-1(AMP) b. Socket Spec. : 170362-1(AMP)</p> <p>2. Drive Side Connector(U, V, W, FG) a. U, V, W Pin Spec. : 1512 b. FG Pin Spec. : 1.5x4(Ring Terminal)</p> <p>3. Cable Spec. : 4C×0.75SQ or 4C×18AWG</p>	PIN No.	Signal	1	U	2	V	3	W	4	Ground
PIN No.	Signal														
1	U														
2	V														
3	W														
4	Ground														
For Power	S Series Brake Cable (Small Capacity)	APCS-P□□□KB	L7SA□□□A L7NHA□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC APM-HB SERIES	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>1</td> <td>BK+</td> </tr> <tr> <td>2</td> <td>BK-</td> </tr> </table> <p>1. Motor Side Connector a. Cap Spec.(2 Position) : 172157-1(AMP) b. Socket Spec. : 170362-1(AMP)</p> <p>2. Drive Side Connector a. Connecting terminal Spec. : 1.5x3(Ring Terminal)</p> <p>3. Cable Spec. : 2C×0.75SQ or 2C×18AWG</p>	PIN No.	Signal	1	BK+	2	BK-				
PIN No.	Signal														
1	BK+														
2	BK-														
For Power	F Series Power Cable (Small Capacity)	APCS-P□□□FS-□	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-FB APM-FC SERIES	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>1</td> <td>W</td> </tr> <tr> <td>2</td> <td>V</td> </tr> <tr> <td>3</td> <td>U</td> </tr> <tr> <td>4</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector a. Plug Spec. : KN5FT04SJ1(JAE) b. Socket Spec. : ST-KN-S-C1B-3500(JAE)</p> <p>2. Drive Side Connector(U, V, W, FG) a. U, V, W Pin Spec. : 1512 b. FG Pin Spec. : 1.5x4(Ring Terminal)</p> <p>3. Cable Spec. : 4C×0.75SQ or 4C×18AWG</p>	PIN No.	Signal	1	W	2	V	3	U	4	Ground
PIN No.	Signal														
1	W														
2	V														
3	U														
4	Ground														




Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of □ marked product, the connector can draw in a direction of Front(load) / Rear(half load).
(Front Type : No mark, Rear Type : -R)

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

Servo Motor Option

■ Power Cable [200V]

Type	Product Type	Model Name ^(Note)	Applicable Drive	Applicable Motor	Specifications
For Power	L Series Power Cable (Small Capacity)	APCS-P□□□LS-□	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APMC-FAL APMC-FBL APMC-FCL SERIES	<p>Motor Side Connector</p>  <p>Drive Side Connector</p>  <p>1. Motor Side Connector</p> <ul style="list-style-type: none"> a. Plug Spec. : SM-JN8FT04(Suntone) b. Socket Spec. : SMS-201(Suntone) <p>2. Drive Side Connector (U,V,W,FG)</p> <ul style="list-style-type: none"> a. U, V, W Pin Spec. : 1512(Ferrule) b. FG Pin Spec. : 1.5x4 (Ring Terminal) <p>3. Cable Spec. : 4Cx0.75SQ or 4Cx18AWG</p> <p>4. In case of FAL products, Please install Power Cable first before connecting Encoder Cable.</p>
For Power	Brake Cable for Flat Motor (Small Capacity)	APCS-B□□□QS-□	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-FAL APM-FB, FBL APM-FC, FCL SERIES	<p>Motor Side Connector</p>  <p>Brake Power side Connector</p>  <p>1. Motor Side Connector</p> <ul style="list-style-type: none"> a. Plug Spec. : KN5FT02SJ1 b. Socket Spec. : ST-KN-S-C1B-3500 <p>2. Drive Side Connector</p> <ul style="list-style-type: none"> a. Connecting terminal Spec. : 1,5x3(Ring Terminal) <p>3. Cable Spec. : 2C×0.5SQ or 2C×20AWG</p>
For Power	Power Cable (Middle Capacity)	APCS-P□□□HS	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-SE APM-FE APM-HE SERIES	<p>Motor Side Connector</p>  <p>Drive Side Connector</p>  <p>1. Motor Side Connector</p> <ul style="list-style-type: none"> a. Plug Spec. : MS3108A20-4S <p>2. Drive Side Connector</p> <ul style="list-style-type: none"> a. Connecting terminal Spec. : 22x6(Ring Terminal) <p>3. Cable Spec. : 4C×25SQ or 4C×14AWG</p>

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.




Note2) In case of □ marked product, the connector can draw in a direction of Front(load) / Rear(half load).
(Front Type : No mark, Rear Type : -R)

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

L7 SERIES SYSTEM

Servo Motor Option

■ Power Cable [200V]

Type	Product Type	Model Name (Note)	Applicable Drive	Applicable Motor	Specifications														
For Power	Power Cable (Brake Type)	APCS-P□□□NB	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-SE APM-FE SERIES	 <p>Motor Side Connector</p> <p>Drive Side Connector</p> <p>Brake Power side Connector</p> <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> <tr> <td>E</td> <td>BK+</td> </tr> <tr> <td>F</td> <td>BK-</td> </tr> </table> <ol style="list-style-type: none"> 1. Motor Side Connector(MS : Military Standard) <ol style="list-style-type: none"> a. Plug Spec. : MS3108A20-15S 2. Drive Side Connector <ol style="list-style-type: none"> a. U, V, W Pin Spec. : 2512 b. Cable Spec. : 4C×2.5SQ or 4C×14AWG c. FG Pin Spec. : 2.5×4(Ring Terminal) 3. Brake Power side Connector <ol style="list-style-type: none"> a. BK Pin Spec. : 1.5×3(Ring Terminal) b. Cable Spec. : 2C×0.75SQ or 2C×18AWG 	PIN No.	Signal	A	U	B	V	C	W	D	Ground	E	BK+	F	BK-
PIN No.	Signal																		
A	U																		
B	V																		
C	W																		
D	Ground																		
E	BK+																		
F	BK-																		
For Power	Power Cable (Middle Capacity)	APCS-P□□□IS	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	APM-SF30A SF22D, LF35D SF20G, LF30G SF12M, SF20M LF30M, SG22D LG35D, SG20G LG30G, SG12M SG20M, LG30M FF30A, FF22D FF35D, FF20G FF30G, FF12M FF20M, FF30M FG22D, FG35D FG20G, FG30G FG12M, FG20M FG30M	 <p>Motor Side Connector</p> <p>Drive Side Connector</p> <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table> <ol style="list-style-type: none"> 1. Motor Side Connector <ol style="list-style-type: none"> a. Plug Spec. : MS3108A22-22S 2. Drive Side Connector <ol style="list-style-type: none"> a. U, V, W Pin Spec. : 2512 b. FG Pin Spec. : 2.5×4(Ring Terminal) 3. Cable Spec. : 4C×2.5SQ or 4C×14AWG 	PIN No.	Signal	A	U	B	V	C	W	D	Ground				
PIN No.	Signal																		
A	U																		
B	V																		
C	W																		
D	Ground																		
For Power	Power Cable (Brake Type)	APCS-P□□□PB	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	APM-SF30A SF22D, LF35D SF20G, LF30G SF12M, SF20M LF30M, FF30A FF22D, FF35D FF20G, FF30G FF12M, FF20M FF30M	 <p>Motor Side Connector</p> <p>Drive Side Connector</p> <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> <tr> <td>E</td> <td>BK+</td> </tr> <tr> <td>F</td> <td>BK-</td> </tr> </table> <ol style="list-style-type: none"> 1. Motor Side Connector(MS : Military Standard) <ol style="list-style-type: none"> a. PLUG Spec. : MS3108A24-10S 2. Drive Side Connector <ol style="list-style-type: none"> a. U, V, W Pin Spec. : 2512 b. Cable Spec. : 4C×2.5SQ or 4C×14AWG c. FG Pin Spec. : 2.5×4(Ring Terminal) 3. Brake Power side Connector <ol style="list-style-type: none"> a. BK Pin Spec. : 1.5×3(Ring Terminal) b. Cable Spec. : 2C×0.75S or 2C×18AWG 	PIN No.	Signal	A	U	B	V	C	W	D	Ground	E	BK+	F	BK-
PIN No.	Signal																		
A	U																		
B	V																		
C	W																		
D	Ground																		
E	BK+																		
F	BK-																		

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

Servo Motor Option

■ Power Cable [200V]

Type	Product Type	Model Name ^(Note)	Applicable Drive	Applicable Motor	Specifications										
For Power	Power Cable (Middle Capacity)	APCS-P□□□JS	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	APM-SF50A SF55D, SF75D SF44G, SF60G SF44M, SG55D SG75D, SG44G SG60G, SG44M FF50A, FF55D FF75D, FF44G FF60G, FF44M FG55D, FG75D FG44G, FG60G FG44M	<p>Motor Side Connector</p> <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table> <p>Drive Side Connector</p> <p>1. Motor Side Connector(MS : Military Standard) a. Plug Spec. : MS3108A22-22S 2. Drive Side Connector a. Connecting terminal Spec. : 6×5(Ring Terminal) b. Cable Spec. : 4C×6SQ or 4C×10AWG</p>	PIN No.	Signal	A	U	B	V	C	W	D	Ground
PIN No.	Signal														
A	U														
B	V														
C	W														
D	Ground														
For Power	Power Cable (Brake Type)	APCS-P□□□LB	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	APM-SF50A SF55D, SF75D SF44G, SF60G SF44M, FF50A FF50D, FF75D FF44G, FF60G FF40M	<p>Motor Side Connector</p> <p>Drive Side Connector</p> <p>Brake Power side Connector</p> <p>1. Motor Side Connector(MS : Military Standard) a. Plug Spec. : MS3108A24-10S 2. Drive Side Connector a. Connecting terminal Spec. : 6×5(Ring Terminal) b. Cable Spec. : 4C×6SQ or 4C×10AWG 3. Brake Power side Connector a. Connecting terminal Spec. : 1.5×3(Ring Terminal) b. Cable Spec. : 2C×0.75SQ or 2C×18AWG</p>										
For Power	Power Cable (Middle Capacity)	APCS-P□□□MS	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	APM-SG60M FG60M, SF75G FF75G	<p>Motor Side Connector</p> <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table> <p>Drive Side Connector</p> <p>1. Motor Side Connector(MS : Military Standard) a. Plug Spec. : MS3108A32-17S 2. Drive Side Connector a. Connecting terminal Spec. : 10×5(Ring Terminal) 3. Cable Spec. : 4C×6SQ or 4C×10AWG</p>	PIN No.	Signal	A	U	B	V	C	W	D	Ground
PIN No.	Signal														
A	U														
B	V														
C	W														
D	Ground														

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series






PEGASUS Series

Options

L7 SERIES SYSTEM

Servo Motor Option

■ Power Cable [200V]

Type	Product Type	Model Name ^(Note1)	Applicable Drive	Applicable Motor	Specifications											
For Power	Power Cable	APCS-P□□□OS	L7NHA□□□U L7PA□□□U	APM-SG85G APM-FG85G APM-SG110D APM-FG110D APM-SG110G APM-FG110G	  <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table>	PIN No.	Signal	A	U	B	V	C	W	D	Ground	Motor Side Connector Drive Side Connector
PIN No.	Signal															
A	U															
B	V															
C	W															
D	Ground															
For Power	Power Cable	APCS-P□□□VS	L7NHA□□□U L7PA□□□U	APM-SG150G APM-FG150G	  <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table>	PIN No.	Signal	A	U	B	V	C	W	D	Ground	Motor Side Connector Drive Side Connector
PIN No.	Signal															
A	U															
B	V															
C	W															
D	Ground															
For Power	Power Cable (Brake Type)	APCS-P□□□SB	L7SA□□□A L7SA□□□B L7NA□□□B L7PA□□□U	APM-SG APM-LG APM-FG SERIES	  <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>A</td> <td>BK+</td> </tr> <tr> <td>B</td> <td>BK-</td> </tr> </table>	PIN No.	Signal	A	BK+	B	BK-	Motor Side Connector Drive Side Connector				
PIN No.	Signal															
A	BK+															
B	BK-															

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of 400V products, you can use Robotic Cable only.

Cable Length(m)	3	5	10	20
Robotic Cable(F)	F03	F05	F10	F20

Servo Motor Option

■ Power Cable [400V]

Type	Product Type	Model Name <small>(Note)</small>	Applicable Drive	Applicable Motor	Specifications															
For Power	Power Cable	APCF-P□□□HS	L7SB□□□B L7NHB□□□U L7PB□□□U	All Models of APM-SEP APM-FEP SERIES	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector (MS: Military Standard) a. Plug Spec. : MS3108A 20-4S 2. Drive Side Connector (U,V,W,FG) a. U, V, W Pin Spec. : 1512(Ferrule) b. FG Pin Spec. : 1.5x4(Ring Terminal) 3. Cable Spec. : 4Cx1.5SQ or 4Cx15AWG</p>		PIN No.	Signal	A	U	B	V	C	W	D	Ground				
PIN No.	Signal																			
A	U																			
B	V																			
C	W																			
D	Ground																			
For Power	Power Cable (Brake Type)	APCF-P□□□NB	L7SB□□□B L7NHB□□□U L7PB□□□U	All Models of APM-SEP APM-FEP SERIES	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> <tr> <td>E</td> <td>BK+</td> </tr> <tr> <td>F</td> <td>BK-</td> </tr> </table> <p>1. Motor Side Connector (MS: Military Standard) a. Plug Spec. : MS3108A 20-15S 2. Drive Side Connector a. U, V, W Pin Spec. : 1512(Ferrule) b. FG Pin Spec. : 1.5 x 4(Ring Terminal) 3. Power Cable Spec. : 4Cx1.5SQ or 4Cx15AWG 4. Brake Power side Connector a. Connecting terminal Spec. : 1.5 x 3(Ring Terminal) 5. Brake Cable Spec. : 2Cx0.75SQ or 2Cx18AWG</p>		PIN No.	Signal	A	U	B	V	C	W	D	Ground	E	BK+	F	BK-
PIN No.	Signal																			
A	U																			
B	V																			
C	W																			
D	Ground																			
E	BK+																			
F	BK-																			
For Power	Power Cable	APCF-P□□□IS	L7SB□□□B L7NHB□□□U L7PB□□□U	APM-[S/F]FP30A APM-[S/F]FP22D APM-[S/F]FP35D APM-[S/F]FP20G APM-FFP30G APM-[S/F]FP12M APM-[S/F]FP20M APM-[S/F]GP22D APM-[S/F]GP35D APM-[S/F]GP20G APM-FGP30G APM-[S/F]GP12M APM-[S/F]GP20M	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector (MS: Military Standard) a. Plug Spec. : MS3108A 22-22S 2. Drive Side Connector (U,V,W,FG) a. U, V, W Pin Spec. : 2512(Ferrule) b. FG Pin Spec. : 2.5x4 (Ring Terminal) 3. Cable Spec. : 4Cx2.5SQ or 4Cx14AWG</p>		PIN No.	Signal	A	U	B	V	C	W	D	Ground				
PIN No.	Signal																			
A	U																			
B	V																			
C	W																			
D	Ground																			

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of 400V products, you can use Robotic Cable only.

Cable Length(m)	3	5	10	20
Robotic Cable(F)	F03	F05	F10	F20

L7S Series

L7N Series

L7NH Series
L7P Series

S Series
F Series




MDM Series
PEGASUS Series

Options

L7 SERIES SYSTEM

Servo Motor Option

■ Power Cable [400V]

Type	Product Type	Model Name (Note)	Applicable Drive	Applicable Motor	Specifications															
For Power	Power Cable (Brake Type)	APCF-P□□□PB	L7SB□□□B L7NHB□□□U L7PB□□□U	APM-[S/F]FP30A APM-[S/F]FP22D APM-[S/F]FP35D APM-[S/F]FP20G APM-FFP30G APM-[S/F]FP12M APM-[S/F]FP20M	 <p>1. Motor Side Connector (MS: Military Standard) a. Plug Spec. : MS3108A 24-10S 2. Drive Side Connector a. U, V, W Pin Spec. : 2512(Ferrule) b. FG Pin Spec. : 2.5 x 4(Ring Terminal) 3. Power Cable Spec. : 4Cx2.5SQ or 4Cx14AWG 4. Brake Power side Connector a. Connecting terminal Spec. : 1.5 x 3(Ring Terminal) 5. Brake Cable Spec. : 2Cx0.75SQ or 2Cx18AWG</p>	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> <tr> <td>E</td> <td>BK+</td> </tr> <tr> <td>F</td> <td>BK-</td> </tr> </table>	PIN No.	Signal	A	U	B	V	C	W	D	Ground	E	BK+	F	BK-
PIN No.	Signal																			
A	U																			
B	V																			
C	W																			
D	Ground																			
E	BK+																			
F	BK-																			
For Power	Power Cable (Middle Capacity)	APCF-P□□□JS	L7SB□□□B L7NHB□□□U L7PB□□□U	APM-[S/F]FP50A APM-[S/F]FP50D APM-[S/F]FP75D APM-SFP30G APM-[S/F]FP44G APM-[S/F]FP60G APM-[S/F]FP30M APM-[S/F]FP44M APM-[S/F]GP55D APM-[S/F]GP75D APM-SGP30G APM-[S/F]GP44G APM-[S/F]GP60G APM-[S/F]GP30M APM-[S/F]GP44M	 <p>1. Motor Side Connector (MS: Military Standard) a. Plug Spec. : MS3108A 22-22S 2. Drive Side Connector (U,V,W,FG) a. U, V, W Pin Spec. : 4.0x 5(Ring Terminal) 3. Cable Spec. : 4Cx4.0SQ or 4Cx11AWG</p>	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table>	PIN No.	Signal	A	U	B	V	C	W	D	Ground				
PIN No.	Signal																			
A	U																			
B	V																			
C	W																			
D	Ground																			
For Power	Power Cable (Brake Type)	APCF-P□□□LB	L7SB□□□B L7NHB□□□U L7PB□□□U	APM-[S/F]FP50A APM-[S/F]FP55D APM-[S/F]FP75D APM-SGP30G APM-[S/F]FP44G APM-[S/F]FP60G APM-[S/F]FP30M APM-[S/F]FP44M	 <p>1. Motor Side Connector (MS: Military Standard) a. Plug Spec. : MS3108A 24-10S 2. Drive Side Connector a. U, V, W Pin Spec. : 4.0X5(Ring Terminal) 3. Power Cable Spec. : 4Cx4.0SQ or 4Cx11AWG 4. Brake Power side Connector a. Connecting terminal Spec. : 1.5 x 3(Ring Terminal) 5. Brake Cable Spec. : 2Cx0.75SQ or 2Cx18AWG</p>	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> <tr> <td>E</td> <td>BK+</td> </tr> <tr> <td>F</td> <td>BK-</td> </tr> </table>	PIN No.	Signal	A	U	B	V	C	W	D	Ground	E	BK+	F	BK-
PIN No.	Signal																			
A	U																			
B	V																			
C	W																			
D	Ground																			
E	BK+																			
F	BK-																			




Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of 400V products, you can use Robotic Cable only.

Cable Length(m)	3	5	10	20
Robotic Cable(F)	F03	F05	F10	F20

Servo Motor Option

■ Power Cable [400V]

Type	Product Type	Model Name ^(Note1)	Applicable Drive	Applicable Motor	Specifications										
For Power	Power Cable (Middle Capacity)	APCF—P□□□MS	L7SB□□□B L7NHB□□□U L7PB□□□U	APM-[S/F]FP75G [S/F]GP110D [S/F]GP85G [S/F]GP110G [S/F]GP150G [S/F]GP60M	 <table border="1"> <tr> <td>PIN No.</td> <td>PIN No.</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector (MS: Military Standard) a. PLUG Spec. : MS3108A 32-17S 2. Drive Side Connector(U,V,W,FG) a. U, V, W Pin Spec. : 10x5(Ring Terminal) 3. Cable Spec. : 4Cx10SQ or 4Cx7AWG</p>	PIN No.	PIN No.	A	U	B	V	C	W	D	Ground
PIN No.	PIN No.														
A	U														
B	V														
C	W														
D	Ground														
For Power	Brake Cable (same with 200V)	APCS—P□□□SB	L7SB□□□B L7NHB□□□U L7PB□□□U	All Models of APM-SGP APM-FGP SERIES	 <table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>1</td> <td>BK+</td> </tr> <tr> <td>2</td> <td>BK-</td> </tr> </table> <p>1. Motor Side Connector (MS: Military Standard) a. PLUG Spec. : MS3108A 14-17S 2. Drive Side Connector(U,V,W,FG) a. Connecting terminal Spec. : 1.5x3(Ring Terminal) 3. Cable Spec. : 2Cx0.75SQ or 2Cx19AWG</p>	PIN No.	Signal	1	BK+	2	BK-				
PIN No.	Signal														
1	BK+														
2	BK-														
Battery For Encoder	Battery Ass'y	APCS—BATT36	All L7 Drives for M-tum	All Models of APM-F Series	 <table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> <td>Color</td> </tr> <tr> <td>1</td> <td>+</td> <td>Red</td> </tr> <tr> <td>2</td> <td>-</td> <td>Black</td> </tr> </table> <p>1. PLUG Spec. : 5264-02 (Molex) 2. PLUG Pin Spec. : 5263PBT (Molex) 3. Battery Spec. : ER6V/3.6V, 2000mAh (TOSHIBA)</p>	PIN No.	Signal	Color	1	+	Red	2	-	Black	
PIN No.	Signal	Color													
1	+	Red													
2	-	Black													

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of 400V products, you can use Robotic Cable only.

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

L7S Series

L7N Series

L7H Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series

L7 SERIES SYSTEM

Servo Motor Option

■ DDMotor Signal Cable

Type	Product type	Model Name(Note1)	Applicable Motor	Specifications	Specifications																																																																				
For Signal	L7 Encoder Cable	APCS-E□□ZS	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All models of DD motor	<p>D.D SERVO ENCODER CABLE</p> <table border="1"> <thead> <tr> <th>No.</th> <th>Encoder</th> <th>No.</th> <th>Encoder</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>MA</td> <td>10</td> <td>+5V</td> </tr> <tr> <td>2</td> <td>SLO</td> <td>11</td> <td>-</td> </tr> <tr> <td>3</td> <td>-</td> <td>12</td> <td>-</td> </tr> <tr> <td>4</td> <td>OV</td> <td>13</td> <td>-</td> </tr> <tr> <td>5</td> <td>Shield</td> <td>14</td> <td>-</td> </tr> <tr> <td>6</td> <td>MA</td> <td>15</td> <td>-</td> </tr> <tr> <td>7</td> <td>SLO</td> <td>-</td> <td>-</td> </tr> <tr> <td>8</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>ENCODER CONNECTOR</p> <p>Cable Bushing</p> <p>Biss Serial Encoder Encoder Cable Connector</p> <p>Motor Connector</p> <p>Driver Connector</p> <p>Pin No. Encoder Pin No. Encoder</p> <table border="1"> <thead> <tr> <th>1</th> <td>-</td> <td>6</td> <td>-</td> </tr> </thead> <tbody> <tr> <td>2</td> <td>-</td> <td>7</td> <td>-</td> </tr> <tr> <td>3</td> <td>MA</td> <td>10</td> <td>-</td> </tr> <tr> <td>4</td> <td>MA</td> <td>11</td> <td>-</td> </tr> <tr> <td>5</td> <td>SLO</td> <td>12</td> <td>-</td> </tr> <tr> <td>6</td> <td>SLO</td> <td>13</td> <td>-</td> </tr> <tr> <td>7</td> <td>OV</td> <td>14</td> <td>+5V</td> </tr> <tr> <td>Plate</td> <td colspan="3">SHIELD</td> </tr> </tbody> </table>	No.	Encoder	No.	Encoder	1	MA	10	+5V	2	SLO	11	-	3	-	12	-	4	OV	13	-	5	Shield	14	-	6	MA	15	-	7	SLO	-	-	8	-	-	-	1	-	6	-	2	-	7	-	3	MA	10	-	4	MA	11	-	5	SLO	12	-	6	SLO	13	-	7	OV	14	+5V	Plate	SHIELD		
No.	Encoder	No.	Encoder																																																																						
1	MA	10	+5V																																																																						
2	SLO	11	-																																																																						
3	-	12	-																																																																						
4	OV	13	-																																																																						
5	Shield	14	-																																																																						
6	MA	15	-																																																																						
7	SLO	-	-																																																																						
8	-	-	-																																																																						
1	-	6	-																																																																						
2	-	7	-																																																																						
3	MA	10	-																																																																						
4	MA	11	-																																																																						
5	SLO	12	-																																																																						
6	SLO	13	-																																																																						
7	OV	14	+5V																																																																						
Plate	SHIELD																																																																								

■ DDMotor Power Cable

Type	Product type	Model Name(Note1)	Applicable Motor	Specifications	Specifications																
For Signal	L7 Power Cable	APCS-P□□DYS	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	DB03D DB06D DB09D DC06D DC12D DC18D DD12D DD22D DD34D DE40D DE60D	<p>1. Motor Side Connector</p> <p>a. PLUG Spec. : NJC-24-4-ADF(Female connector)</p> <p>2. Drive Side Connector</p> <p>a. U, V, W Pin PG Pin Spec. : UA-F2012(Seoil) (Motor side connector)</p> <p>b. FG Spec. : 1.5×4</p> <p>3. Cable Spec. : 4C×1.5SQ, LAPP Cable(P/N : 00257001)</p> <p>Drive Side Connector</p> <p>Item Lead Wire Signal Pin No. Line color</p> <table border="1"> <thead> <tr> <th>Motor</th> <th>U</th> <td>1</td> <td>Red</td> </tr> </thead> <tbody> <tr> <th></th> <th>V</th> <td>2</td> <td>White</td> </tr> <tr> <th></th> <th>W</th> <td>3</td> <td>Black</td> </tr> <tr> <th></th> <th>Ground</th> <td>4</td> <td>Green</td> </tr> </tbody> </table>	Motor	U	1	Red		V	2	White		W	3	Black		Ground	4	Green
Motor	U	1	Red																		
	V	2	White																		
	W	3	Black																		
	Ground	4	Green																		
For Signal	L7 Power Cable	APCS-P□□DZS	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	DFA1G DFA6G	<p>1. Motor Side Connector</p> <p>a. PLUG Spec. : NJC-24-4-ADF(Female connector)</p> <p>2. Drive Side Connector</p> <p>a. U, V, W Pin PG Pin Spec. : UA-F2012(Seoil) (Motor side connector)</p> <p>b. FG Spec. : 2.5×4</p> <p>3. Cable Spec. : 4C×2.5SQ, LAPP Cable(P/N : 00257011)</p> <p>Drive side connector</p> <p>Item Lead Wire Signal Pin No. Line color</p> <table border="1"> <thead> <tr> <th>Motor</th> <th>U</th> <td>1</td> <td>Red</td> </tr> </thead> <tbody> <tr> <th></th> <th>V</th> <td>2</td> <td>White</td> </tr> <tr> <th></th> <th>W</th> <td>3</td> <td>Black</td> </tr> <tr> <th></th> <th>Ground</th> <td>4</td> <td>Green</td> </tr> </tbody> </table>	Motor	U	1	Red		V	2	White		W	3	Black		Ground	4	Green
Motor	U	1	Red																		
	V	2	White																		
	W	3	Black																		
	Ground	4	Green																		

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In Case of DD Motor, we don't supply power cable for robotic cable.

Cable Length(m)	3	5	10	20
Robotic Cable(F)	F03	F05	F10	F20
General Cable(N)	N03	N05	N10	N20

Servo Drive Option

■ Signal Cable

Type	Product type	Model Name ^(Note1)	Applicable Motor	Specifications	
T/B	CN1 T/B	APC-VSCN1T -□□	L7S□□□□B L7PA□□□U	<p>1. Extended CN1 T/B for VS/L7S</p> <p>2. Available Cable Length : 0.5[m], 1[m], 1.5[m], 2[m], 3[m]</p>	
	CN1 T/B	APCS-L7NCN1T -□□	L7NA□□□B L7NH□□□U	<p>1. Extended CN1 T/B for L7N</p> <p>2. Available Cable Length : 0.5[m], 1[m], 1.5[m], 2[m]</p>	
For Signal	CN1 Cable	APC-CN1□□A	L7S SERIES L7P SERIES	<p>[Upper Controller] [Drive Connection Side CN1]</p> <p>Indicates Pin No</p> <p>1. Drive Side Connection(CN1)</p> <ul style="list-style-type: none"> a. Case Spec. : 10350-52A0-008(3M) b. Connector Spec. : 10150-3000VE(3M) c. Cable Spec. : 20276-SB 25P(AWG28) 	
For Signal	CN1 Cabl	APCS-CN1□□A	L7N SERIES L7NH SERIES	<p>[Upper Controller] [Drive Connection Side CN1]</p> <p>Indicates Pin No</p> <p>1. Drive Side Connection(CN1)</p> <ul style="list-style-type: none"> a. Case Spec. : 10320-52A0-008(3M) b. Connector Spec. : 10120-3000VE(3M) c. Cable Spec. : ROW-SB0.1C×20C(AWG28) 	

Note1) □□ of Model Name indicates the kind and length of cable And the designation is as below. CN1 cable : 1m, 2m, 3m and 5m are available.

Cable Length(m)	3	5	10	20
Robotic Cable(F)	N03	N05	N10	N20
General Cable(N)	F03	F05	F10	F20

*APC-VSCN1T

*APCS-L7NCN1T

Cable Length(m)	0.5	1	1.5	2	3	Cable Length(m)	0.5	1	1.5	2	3
Declaration	None	01	015	02	03	Declaration	None	01	015	02	03

L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series

Options

L7 SERIES SYSTEM

Servo Drive Option

L7 Pin Map

L7S

NO	PIN Function								
1	TRQCOM	11	PR+	21	SPD3	31	/BO	41	RDY
2		12	PR-	22	SPD2	32	AO	42	
3		13		23	SPD1	33	/AO	43	ZSPD
4	ZO	14	ALO2	24	GND24	34	+12VA	44	BRAKE
5	/ZO	15	ALO1	25	GND24	35	-12VA	45	INPOS
6		16	ALO0	26		36	SG	46	DIR
7		17	ALMRST	27	SPDCOM	37	GND	47	SVON
8	GND	18	EMG	28	MINIY1	38	ALARM+	48	STOP
9	PF+	19	CWLIM	29	MINIY2	39	ALARM-	49	PULCOM
10	PF-	20	CCWLIM	30	BO	40	RDY+	50	+24V IN

L7P

NO	PIN Function								
1	AO	11	+24V IN	21	+24V IN	31	PF+	41	INPOS1+
2	/AO	12	SVON	22	HOME	32	PF-	42	INPOS1-
3	BO	13	POT	23	H-START	33	PR+	43	ORG+
4	/BO	14	NOT	24	ISEL0	34	PR-	44	ORG-
5	ZO	15	A-RST	25	ISEL1	35	ALARM+	45	EOS+
6	/ZO	16	START	26	ISEL2	36	ALARM-	46	EOS-
7	A-TLMT	17	STOP	27	ISEL3	37	RDY+	47	TGON+
8	AGND	18	REGT	28	ISEL4	38	RDY-	48	TGON-
9	A-OVR	19	EMG	29	ISEL5	39	BRAKE+	49	TLMT+
10	AGND	20		30	PULCOM	40	BRAKE-	50	TLMT-


L7N

NO	PIN Function	NO	PIN Function
1	BREAK+	11	HOME
2	BREAK-	12	ALMRST
3	ALARM+	13	PCON
4	ALARM-	14	GAIN2
5		15	
6	+24V IN	16	
7	N-OT	17	READY+
8	P-OT	18	READY-
9	PROBE1	19	ZSPD+
10	PROBE2	20	ZSPD-

L7NH

NO	PIN Function	NO	PIN Function
1	BREAK+	11	POT
2	BREAK-	12	NOT
3	RDY+	13	PCON
4	RDY-	14	GAIN2
5	AGND	15	A-TLMT
6	+24V IN	16	
7	HOME	17	RDY+
8	STOP	18	RDY-
9	PCL	19	ZSPD+
10	NCL	20	ZSPD-

Signal Cable / Connector

Type	Product type	Model Name ^(Note)	Applicable Motor	Specifications	
For Signal	Communication Cable	APC-CN5L7U	All Models of L7 SERIES	[PC – USB Port]  [Servo Drive – CN5]  <ul style="list-style-type: none"> 1. PC Side Connector : USB A Plug 2. Drive Side Connector(CN5) : Mini USB 5P Plug 3. Electric Requirements Spec : Double Shielded, Twisted Pair, EMI-filter attached type (Ex. : KU-AMB518, SANWA) 4. Only 1.8m length of cable is available to use 	

Servo Drive Option

Connector

Type	Product Type	Model Name ^(Note1)	Applicable Drive	Specifications																															
CN	CN1 Connector	APC-CN1NNA	L7S□□□B L7PA□□□U	1. Case Spec. : 10350-52A0-008(3M) 2. Connector Spec. : 10150-3000VE(3M)																															
CN	CN1 Connector	APC-CN2NNA	L7NA□□□B L7NH□□□U	1. Case Spec. : 10320-52A0-008(3M) 2. Connector Spec. : 10120-3000VE(3M)																															
CN	CN2 Connector	APC-CN3NNA	All Models of L7 SERIES	1. Case Spec. : 10314-52A0-008(3M) 2. Connector Spec. : 10114-3000VE(3M)																															
CN	CN3 CN4 EtherCAT Connector	APCS-CN4NNA	L7NA□□□B L7NH□□□U	 Note) EtherCAT use only 4wires(1, 2, 3, 6)	<table border="1"> <thead> <tr> <th>PIN No.</th> <th>Signal</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>TX/RX0 Plus</td> <td>White/Orange</td> </tr> <tr> <td>2</td> <td>TX/RX0 Minus</td> <td>Orange</td> </tr> <tr> <td>3</td> <td>TX/RX1 Plus</td> <td>White/Orange</td> </tr> <tr> <td>4</td> <td>TX/RX2 Plus</td> <td>Blue</td> </tr> <tr> <td>5</td> <td>TX/RX2 Minus</td> <td>White/Blue</td> </tr> <tr> <td>6</td> <td>TX/RX1 Minus</td> <td>Green</td> </tr> <tr> <td>7</td> <td>TX/RX3 Plus</td> <td>White/Brown</td> </tr> <tr> <td>8</td> <td>TX/RX3 Minus</td> <td>Brown</td> </tr> <tr> <td>Plate</td> <td></td> <td>SHILDE</td> </tr> </tbody> </table>	PIN No.	Signal	Color	1	TX/RX0 Plus	White/Orange	2	TX/RX0 Minus	Orange	3	TX/RX1 Plus	White/Orange	4	TX/RX2 Plus	Blue	5	TX/RX2 Minus	White/Blue	6	TX/RX1 Minus	Green	7	TX/RX3 Plus	White/Brown	8	TX/RX3 Minus	Brown	Plate		SHILDE
PIN No.	Signal	Color																																	
1	TX/RX0 Plus	White/Orange																																	
2	TX/RX0 Minus	Orange																																	
3	TX/RX1 Plus	White/Orange																																	
4	TX/RX2 Plus	Blue																																	
5	TX/RX2 Minus	White/Blue																																	
6	TX/RX1 Minus	Green																																	
7	TX/RX3 Plus	White/Brown																																	
8	TX/RX3 Minus	Brown																																	
Plate		SHILDE																																	
CN	STO Cable	APCS-STO□□A	L7NA□□□B L7NH□□□U	1. Cable Length : Only 0.3[m], 1[m], 3[m] of Cable is available to use. 2. Connector Model Name : APCS-ST000A * Caution : During assembly of connector, It can be broken easily without guaranty of LS Mecapion.	<table border="1"> <thead> <tr> <th>PIN No.</th> <th>IO Signal</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>NC</td> <td>-</td> </tr> <tr> <td>2</td> <td>NC</td> <td>-</td> </tr> <tr> <td>3</td> <td>HWB#1 Minus</td> <td>Orange</td> </tr> <tr> <td>4</td> <td>HWB#1 Plus</td> <td>Orange</td> </tr> <tr> <td>5</td> <td>HWB#2 Minus</td> <td>Yellow</td> </tr> <tr> <td>6</td> <td>HWB#2 Plus</td> <td>Yellow</td> </tr> <tr> <td>7</td> <td>EDM Plus</td> <td>White</td> </tr> <tr> <td>8</td> <td>EDM Minus</td> <td>White</td> </tr> </tbody> </table>	PIN No.	IO Signal	Color	1	NC	-	2	NC	-	3	HWB#1 Minus	Orange	4	HWB#1 Plus	Orange	5	HWB#2 Minus	Yellow	6	HWB#2 Plus	Yellow	7	EDM Plus	White	8	EDM Minus	White			
PIN No.	IO Signal	Color																																	
1	NC	-																																	
2	NC	-																																	
3	HWB#1 Minus	Orange																																	
4	HWB#1 Plus	Orange																																	
5	HWB#2 Minus	Yellow																																	
6	HWB#2 Plus	Yellow																																	
7	EDM Plus	White																																	
8	EDM Minus	White																																	

Note1) □□ of Model Name indicates the kind and length of cable. And the declaration is as below.

*APCS-STO□□A





Cable Length(m)	0.3	1	3
Declaration	03	10	30

L7 SERIES SYSTEM

Other Options

■ 200V Braking Resistor

* Option braking resistors are selectable items for user's need.





Type	Product Type	Model Name ^(Note1)	Applicable Drive	Specifications
Resistor	Braking Resistor	APCS-140R50 50Ω/140W	L7□A001□ L7□A002□ L7□A004□	 <p>IRH 140W 50ohm</p>
Resistor	Braking Resistor	APCS-300R30 30Ω/300W	L7□A008□ L7□A010□	 <p>IRV 300W 30ohm</p>
Resistor	Braking Resistor	APC-600R30 15Ω/1200W (30Ω/600*2P)	L7□A020□	
		APC-600R30 10Ω/1800W (30Ω/600*3P)	L7□A035□	 <p>IRV 600S 30ohm IRV 600S 28ohm</p> <p>* L7□A020□ – 2pcs * L7□A050□ – 4pcs (Parallel Connection) L7□A075□ L7□A035□ – 3pcs (Parallel Connection) (Parallel Connection)</p> <p>Note) IRV 600S 30ohm and 600S 28ohm have the same external dimensions.</p>
		APC-600R28 7Ω/2400W (28Ω/600*4P)	L7□A050□ L7□A075□	
Resistor	Braking Resistor	APCS-2000R3.3 3.3Ω/2000W	L7□A150□	

Note1) L7 Series 100W~7.5kW has the internal basic braking resistor. If the machine requires short deceleration time frequently, refer to table above and apply the appropriate braking resistor.

Other Options

■ 400V Braking Resistor

* Option braking resistors are selectable items for user's need.

Type	Product Type	Model Name (Note1)	Applicable Drive	Specifications
Resistor	Braking Resistor	APCS-300R82 82Ω/300W	L7□B010□	
Resistor	Braking Resistor	APCS-600R140 70Ω/1200W (140Ω/600W*2P)	L7□B020□ L7□B035□	
Resistor	Braking Resistor	APCS-600R75 25Ω/1800W (75Ω/600W*3P)	L7□B050□ L7□B075□	
Resistor	Braking Resistor	APCS-2000R13.4 13.4Ω/2000W	L7□B150□	

Note1) L7 Series 100W~7.5kW has the internal basic braking resistor. If the machine requires short deceleration time frequently, refer to table above and apply the appropriate braking resistor.

L7S Series

L7N Series

L7NH Series
L7P SeriesS Series
F SeriesMDM Series
Options

PEGASUS Series

L7 SERIES SYSTEM

Servo Drive Option

Noise Filter

Type	Product Type	Model Name	Applicable Drive	Specifications
Resistor Noise Filter	APCS-TB6-B010LB/E	L7□A 001□ L7□A 002□ L7□A 004□ L7□A 008□ L7□A 010□ L7□B 010□	L7□A 001□ L7□A 002□ L7□A 004□ L7□A 008□ L7□A 010□ L7□B 010□	
		L7□B 020□ L7□B 035□		
		L7□A 020□ L7□A 035□ L7□B 050□		
	APCS-TB6-B040AS	L7□A 050□ L7□B 075□	L7□A 050□ L7□B 075□	
	APCS-TB6-B060LAS	L7□B 150□	L7□B 150□	

Contents

■ Integrated Servo System

PEGASUS Series

Integrated Servo System (EtherCAT)

- Servo Drive Designation _ 116
- Product Feature _ 117
- External Dimensions _ 120




L7 SERIES SYSTEM

Integrated Servo System (EtherCAT)

| PEGASUS Series



■ Servo Drive Designation



PEGASUS Series

Characteristic

● Enhanced efficiency integrated servo system

- Cost effective from installation by integrated system of motor, encoder cable and drive
- Maximization for useful space when installed at limited and small space
- High effectiveness for application of multi axis because there is no limitation for space of installation

● Real-time control through EtherCAT

- High speed, Real-time capability and Synchronization mechanism
- Improved EtherCAT communication speed
- Supporting CoE, EoE and FoE

Identifying the Part of PEGASUS Series



① Input / Output Signal Connector (CN1)

- This Connector is for Sequence Input / Output Signals

② EtherCAT Communication Output Port (OUT)

③ Status LED

- It Indicates the current state of Ether CAT Communication

④ Power Connector (CN3)

⑤ USB Connector (CN5, Mini B type)

- This Connector is to Communicate With a PC

⑥ Node Address Setting Switch

- This Switch is to set the node address of the drive You can set the node addresses from 0 to 15

⑦ EtherCAT Communication Input Port (IN)

⑧ Safety Connector (CN2)

- This Connector connects Safety Devices

L7S Series

L7N Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series Options

L7 SERIES SYSTEM

Specifications of PEGASUS Series

■ Rated Values of Servo Drive

Rated values for servo drive	<input type="checkbox"/> 40 50W	<input type="checkbox"/> 40 100W	<input type="checkbox"/> 60 100W	<input type="checkbox"/> 60 200W	<input type="checkbox"/> 60 300W
Continuous output current [Arms]	1.77	2.38	3.62	5	6.8
Maximum output current [Arms]	3.54	3.57	7.24	10	13.6
Input voltage	DC 48V ~ DC 60V				

■ Basic Specifications

Category		Details						
Use conditions	Control method	PWM controlled sine wave current driving method						
	Operating temperature / storage temperature	0~+40[°C] / -20~ +60[°C]						
	Operating humidity / storage humidity	Below 80% RH / Below 90% RH (no freeze or condensation)						
	Vibration-/impact-resistance	TBD						
	Degree of protection / degree of pollution	TBD						
	Altitude	1000 m or lower						
	Other	To be free from electrostatic noise, strong electrolysis, or radiation.						
Performance	Speed variation	Load variation	At 0 to 100% load: ±3% (at rated speed)					
		Voltage variation	Rated voltage ± 10%: 0% (at rated speed)					
		Temperature variation	25°C: ± 0.1% or less (at rated speed)					
Input/output signal	Input signal		Input voltage range: DC 12 V – DC 30 V The 4-channel input signal can be assigned to 12 functions: POT, NOT, HOME, STOP, PCON, GAIN2, PCL, NCL, PROBE1, PROB2, EMG, and ARST.					
	Output signal		Rated voltage and current: DC 24 V ± 10%, 120 [mA] The 2-channel output signal can be assigned to 11 functions: BRAKE, ALARM, RDY, ZSPD, INPOS1, TLMT, VLMT, INSPD, WARN, TGON, and INPOS2.					
Analog Monitor		Number of channels: 1 Output voltage range: ±4V Angular resolution: 12 bits Stabilization time: 15 us						
USB communication	Connecting device	PC or USB storage medium						
	Communication standard	Conform to the USB 2.0 Full Speed Standard.						
	Function	Firmware download, parameter setting, adjustment, auxiliary functions, and parameter copy function.						
Dynamic brake (three-phase short-circuit)		Activates when servo alarm, servo OFF, or Emergency stop (POT, NOT and EMG) is input.						
Protection functions		Overcurrent, overload, current limit, overheat, overvoltage, undervoltage, overspeed, encoder error, position follow error, etc.						
Auxiliary functions		Gain adjustment, alarm history, JOG drive, programmed JOG drive, etc.						
Safety functions	Input	STO1 and STO2						
	Compatible standard	TBD						

Specifications of PEGASUS Series

EtherCAT Communication Specification

Category		Details
Communication standard	FoE	Firmware download
	EoE	Parameter setting, adjustment, auxiliary functions, and parameter copy through UDP.
	CoE	IEC 61158 Type12, IEC 61800-7 CiA 402 drive profile
Physical layer		100BASE-TX (IEEE802.3)
Connector		RJ45 x 2
Distance		Within 100 m between nodes
DC (Distributed Clock)		Sync by DC mode
LED Display		L/A0(Link/Act IN) L/A1(Link/Act OUT) RUN ERR
CiA402 drive Profile		Supports CSP, CSV, CST, PP, PV, PT, and HM Modes.

Motor Specification

Model	Unit	SAR5A-8	SA01A-8	SB01A-6	SB02A-9	SB03A-9
Frame Size	[mm]	40	40	60	60	60
Rated Power	[W]	50	80	100	200	300
Rated Torque	[N m]	0.16	0.32	0.32	0.64	0.95
	[Kgf cm]	1.62	3.25	3.25	6.5	9.74
Rated Speed	[rpm]	3,000	2,400	3,000	3,000	3,000
Inertia	[gf cm s ²]	0.02	0.0435	0.114	0.186	0.328
	[Kg m ² x 10 ⁻⁴]	0.02	0.0426	0.116	0.182	0.321
Rated Voltage	[Vdc]	Input Power : 48VDC				
Encoder Type	-	Magnetic Encoder (12bit)				


Note1) SA01A-8 can be operated at 3000rpm(100w) with 60Vdc of input power(instead of 48Vdc)

L7 SERIES SYSTEM

External Dimensions of PEGASUS Series


■ PEGA-AR5A

* Unit [mm]



■ PEGA-A01A


* Unit [mm]



External Dimensions of PEGASUS Series


■ PEGA-B01A

*Unit [mm]



■ PEGA-B02A

*Unit [mm]



L7S Series

L7N Series

L7NH Series

L7P Series

F Series

MDM Series

Options


PEGASUS Series

L7 SERIES SYSTEM

External Dimensions of PEGASUS Series


■ PEGA-B03A

* Unit [mm]



■ Accessory Kit


CN1 : I/O Connector



51004-1100 (MOLEX)

Pin Number	Direction	Name	Signals	Descriptions
1	VCC	+24V	+24V INPUT	+24V Vcc Input
2	Input	POT	Positive Over-Traverl	Limit Sensor Input
3	Input	NOT	Negative Over Traverl	
4	Input	HOME	Home Sensor	Home Sensor Input for Homing
5	Input	STOP	Stop Input	Stop Command Input
6	Output	BRAKE+	BRAKE	Output Brake Control Signal
7	Output	BRAKE-		
8	Output	ALARM+	Alarm Output	Servo Alarm Output
9	Output	ALARM-		
10	Output	MONITOR1	Analog Monitor	Analog Monitor Output(0V~5V)
11	GND	AGND	AGND(0V)	Analog Signal Graound


CN2 : Safe Torque Off Connector



43645-3 (MOLEX)

Pin Number	Name	Descriptions
1	HWBB1	Safe Torque Off(STO) input signals
2	HWBB2	
3	COMMON	DC 24V GND

CN3 : Power Connector



MC_1.5-3-STF-3.5
(PHOENIX CONTACT)

Pin Number	Name	Descriptions
1	FG	Frame Ground
2	N(DC 0V)	DC 0V GND
3	VCC(DC 48V)	DC 48V input

MEMO



MEMO



MEMO



MEMO



MEMO



MEMO

